

Manhattan USB-C to Serial Converter cable, 1m, Male to Male, Serial/RS232/COM/DB9, Prolific PL2303GT Chip, Black cable, Three Years Warranty

Gamintojas: **MANHATTAN** · Modelis: **154499** · EAN: **766623154499** · Prekės kodas: **809365**



22,91 €

Kaina su PVM

Be PVM: **18,93 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects a laptop or other USB-C device to a serial device like CNC machine, label/receipt printer, barcode scanner, or programmable logic controller
- ✓ Plug-and-play installation; compatible with Windows®, macOS®, and Linux®
- ✓ Built with the Prolific PL2303GT chipset for dependable serial communication and wide compatibility
- ✓ LED indicators for Power, TX (Transmit), and RX (Receive) enable real-time status monitoring and data flow troubleshooting
- ✓ Supports baud rates up to 3 Mbps for fast and reliable RS-232 data transfer
- ✓ Foil and braid double shielding to reduce EMI and other interference sources
- ✓ Suitable for wide operating temperatures of 0 to 85°C (32 to 185°F)
- ✓ Bus powered: no external power supply needed
- ✓ Ideal for use in industrial, retail/Point of Sale, medical, laboratory, and digital signage applications





Aprašymas

"USB to Serial Converter with Seamless RS232 Serial Connectivity for USB-C Laptops and Devices

The Manhattan USB-C to Serial DB9 / RS232 Adapter Cable offers a reliable and straightforward way to connect modern laptops and USB-C-equipped devices to legacy serial equipment. Whether you're interfacing with CNC machines, barcode scanners, modems, scanners, medical scales, label printers, sensors, cameras, oscilloscopes or programmable logic controllers, this adapter bridges the gap between old and new technology without the need for additional drivers or external power supplies.

Powered by the Prolific PL2303GT Chipset

At the heart of the adapter is the Prolific PL2303GT chipset, a robust and widely supported solution for RS-232 communication. It ensures smooth data transfer and broad compatibility across major operating systems, including Windows®, macOS®, and Linux®. Installation is truly plug-and-play, letting you get to work in seconds - no configuration required.

Reliable, High-Speed Performance

Designed for demanding environments, the adapter supports baud rates up to 3 Mbps, enabling fast and reliable communication with serial devices. Integrated LED indicators for Power, TX (Transmit), and RX (Receive) provide real-time visual feedback, making it easy to monitor connection status and troubleshoot data flow issues on the spot.

Durable, Shielded, and Built to Perform

This adapter features foil and braid double shielding to minimize electromagnetic interference (EMI), helping ensure stable performance in industrial or noisy electronic environments. Its wide operating temperature range of 0 to 85°C (32 to 185°F) makes it suitable for use in a variety of field or lab conditions.

Versatile for a Range of Applications

Whether you're in industrial automation, retail and POS, medical diagnostics, laboratory research, or digital signage, this USB-C to RS232 adapter delivers the compatibility and reliability you need. Bus-powered and compact, it's the perfect tool for technicians, engineers, and IT professionals working across multiple platforms."

Techninė specifikacija

Features	
Cable length	1 m
Connector 1	USB Type-C
Connector 2	D-Sub (DB-9)
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight

Connector 2 form factor	Straight
Connector contacts plating	Nickel
USB version	2
Cable material	Copper
Product colour	Black
Jacket material	Polyvinyl chloride (PVC)
AWG wire size	24/28
Plug and Play	Yes
Operational conditions	
Operating temperature (T-T)	0 - 85 °C
Storage temperature (T-T)	-10 - 85 °C
Certificates	
Compliance certificates	CE, REACH, RoHS, UKCA
Weight & dimensions	
Cable diameter	4.5 mm
Weight	59 g
Packaging data	
Package width	240 mm
Package depth	135 mm
Package height	10 mm
Package weight	67 g
Package type	Bag
Packaging content	
Quantity per pack	1 pc(s)
Matmenys ir svoris	
Svoris	0,06kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Manhattan

ATSAKINGAS ASMUO ES

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

intellinetnetwork.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt