

Lindy 8 Port VGA and USB Combo KVM Switch

Gamintojas: **LINDY** · Modelis: **39526** · EAN: **4002888395267** · Prekės kodas: **809652**



267,89 €

Kaina su PVM

Be PVM: **221,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports up to 8 USB and VGA equipped computers
- ✓ Supports VGA resolutions up to 2048x1536@60Hz
- ✓ Port switching via hotkey, On-Screen Display or front panel buttons
- ✓ PCs are connected via dedicated KVM cables (not included)
- ✓ 2 year warranty



Aprašymas

The Lindy Combo KVM Switch is a hardware solution that allows direct control of multiple computers using a single keyboard, mouse and VGA monitor. It's ideal for system administrators who want to control multiple computers or servers from a single, centralised location.

The switch occupies only a single 1U space in a 19" rack and supports screen resolutions of up to 2048x1536@60Hz, great for ensuring optimum clarity if used in digital media or graphic design scenarios. It provides 3 simple switching modes, via keyboard hotkeys, front panel buttons and On-Screen Display; setup and management options can be accessed only via the OSD.

A local console can be connected to the 2 USB and VGA ports on the rear panel while Daisy Chain VGA ports can be used to connect up to 8 Lindy Combo series switches in order to manage up to 128 multi platform computers with security features and password access, perfect for large-scale control systems in transport hubs or surveillance centres. All the functions are accessible from the administrator through a simple to use On-Screen Display while LEDs on the front panel show the online and selected PC to ensure continuous control and monitoring.

PCs and connected KVM switches can be remove easily with hot plug support, allowing for maintenance to take place without the need for powering down all connected devices, essential within 'always on' environments such as data centres or traffic management setups.

Computers or servers can be connected to the 8 host ports on the rear panel via dedicated VGA and USB KVM cables (not included).These are available in different lengths:

1m - 32185

2m - 32186

3m - 32187

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	8
Video port type	VGA
Console ports	VGA (D-Sub)
VGA (D-Sub) ports quantity	8
Console USB ports quantity	2
DC-in jack	Yes
Performance	
HD type	Full HD
Maximum resolution	2048 x 1536 pixels
Video bandwidth	60 Hz
Daisy chain	Yes
Design	
Rack mounting	Yes
Product colour	Silver
Rack capacity	1U
Housing material	Metal
Cascadable	Yes
Certification	CE, FCC, California Proposition 65
Display	
Built-in display	Yes
Power	
Input voltage	9 V
Input current	2 A
External power adapter	Yes

Sustainability

Compliance certificates	REACH, RoHS
-------------------------	-------------

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 90%

Weight & dimensions

Width	440 mm
Depth	220 mm
Height	44 mm
Weight	1.5 kg

Packaging data

Package width	570 mm
Package depth	250 mm
Package height	110 mm
Package weight	3.3 kg

Packaging content

Cables included	Daisy chain cable
Manual	Yes
AC adapter included	Yes
Rack mount kit	Yes

Logistics data

Harmonized System (HS) code	85176200
-----------------------------	----------

Matmenys ir svoris

Svoris	3,17kg
--------	--------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB

lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH

Markircher Str. 22, 68229 Mannheim, DE

lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

> [Atitikties deklaracija](#)