

InLine HDMI USB KVM over IP Extender, 4K up to 100m

Gamintojas: **INLINE** · Modelis: **64601** · EAN: **4043718276240** · Prekės kodas: **812954**



649,90 €

Kaina su PVM

Be PVM: **537,11 €**

Sandėlyje





Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4K Over 1 Gigabit Network with Ultra low 1 frame/Sec. latency
- ✓ Up to HDMI 2.0 4K 2160p@60Hz 4:2:0 Video Input and HDCP2.2 is supported
- ✓ Supports 7.1 ch Audio or more (LPCM/DTS/Dolby/Dolby ATMOS)
- ✓ Hybrid Video output (Each Receiver can choose different video format independently)
- ✓ HDMI Audio Extract to Analog audio output (2 channel LPCM audio only)
- ✓ Max. Bit Rate control (10 Mbps ~ 800 Mbps)
- ✓ Video Snap shot (Video Capture)
- ✓ USB 2.0 pass-thru for IP KVM application
- ✓ Webpage management
- ✓ RS-232 Serial control command management



Aprašymas

The InLine® 64601 4K over IP Extender comprises two distinct units, the Transmitter and Receiver unit respectively. It's a LAN based extender and working in pairs to extend your HDMI video from local player to a remote display via an active LAN. To connect both units of transmitter and receiver, you can use either a direct CATx cable connection or through a Gigabit Ethernet Switch in between. With the feature of CATx cable, the image can be delivered up to 100m, while still keeping a satisfying image quality at the same time.

The supported resolution can be up to 2160p@60Hz with 7.1 audio channel. Applicable either over an exhibition room, working floors, demo room, control center, or other mission-critical scenarios.

With multiple receivers and transmitters even a Point-to-Point or Point-to-Multipoint and Videowall scenarios are possible to realize.

Features:

- 4K Over 1 Gigabit Network with Ultra low 1 frame/Sec. latency
- Up to HDMI 2.0 4K 2160p@60Hz 4:2:0 Video Input and HDCP2.2 is supported
- Supports 7.1 ch Audio or more (LPCM/DTS/Dolby/Dolby ATMOS)
- Hybrid Video output (Each Receiver can choose different video format independently)
- HDMI Audio Extract to Analog audio output (2 channel LPCM audio only)
- Max. Bit Rate control (10 Mbps ~ 800 Mbps)
- Video Snap shot (Video Capture)
- USB 2.0 pass-thru for IP KVM application
- Webpage management
- RS-232 Serial control command management
- Https/Telnet command management
- Automatic EDID configuration
- Output video rotation
- Output video partial enlargement and shift for videowall and irregular video wall application
- 4-bit DIP switch for 16 stream channel selection
- Small size / VESA mount
- Rack-mount

Specification:

Transmitter:

- TX/RX connector: 1x RJ45 Female
- AV Tnterface: 1x HDMI Female (In), 1x HDMI Female (Out, Loopback)
- USB Device: 1x USB Type B Female
- IR: 1x 3.5mm Jack Female
- RS232: 1x RJ12 Female
- Dimension (LxWxH): 95x115x26mm

Receiver:

- TX/RX connector: 1x RJ45 Female
- AV Tnterface: HDMI Female (Out) x 1
- USB Device: 4x USB Type A Female
- IR: 1x 3.5mm Jack Female
- RS232: 1x RJ12 Female
- Dimension (LxWxH): 115x115x26mm

General:

- Image Resolution: 3840 x 2160 @60Hz

Power Adapter: DC 5V
Operating Temperature: 0~40°C
Storage Temperature: -20~60°C
Humidity Limits: 0~90% RH, Non-condensing

Techninė specifikacija

Features	
Type	Transmitter & receiver
Connectivity technology	Wired
Maximum transfer distance	100 m
Cable types supported	Cat5, Cat6
Rack mounting	Yes
Maximum digital resolution	3840 x 2160 pixels
Maximum refresh rate	30 Hz
Product colour	Black
Transmitter	
Transmitter video port type	HDMI
RJ-45 ports quantity (transmitter)	1
Receiver	
Receiver local video port type	HDMI
RJ-45 ports quantity (receiver)	1
Ports & interfaces	
USB port type	USB Type-A
USB 2.0 ports quantity	5
HDMI version	2
RS-232 ports	2
RJ-45 ports quantity	2
Power	
AC adapter output voltage	5 V
Weight & dimensions	
Transmitter width	11.5 cm
Transmitter depth	9.5 cm
Transmitter height	2.6 cm
Receiver width	11.5 cm
Receiver depth	11.5 cm

Receiver height	2.6 cm
-----------------	--------

Packaging data

Package width	255 mm
---------------	--------

Package depth	295 mm
---------------	--------

Package height	75 mm
----------------	-------

Package weight	1.55 kg
----------------	---------

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Storage temperature (T-T)	-20 - 60 °C
---------------------------	-------------

Technical details

Dimensions (WxDxH)	115 x 115 x 27 mm
--------------------	-------------------

Weight	1.17 kg
--------	---------

Matmenys ir svoris

Svoris	1,55kg
--------	--------

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Intos Electronic AG

Siemensstraße 11, D-35394 Gießen, DE

service@inline-info.com

[intos.de](https://www.intos.de)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt