ATEN 8-Port USB - PS/2 VGA KVM Switch with USB Peripheral port

Gamintojas: **ATEN** · Modelis: **CS1708A** · EAN: **4710423775312** · Prekės kodas: **813266**



464,89 €

Kaina su PVM

Be PVM: **384,21 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior video quality - up to 2048 x 1536; DDC2B
- ✓ One USB-PS/2 console controls up to 8 computers; Daisy-chain up to 31 additional units - control up to 256 computers from a single console
- ✓ Broadcast Mode - operation simultaneously performed on all selected computers... etc
- ✓ Video DynaSync™ - stores the console monitor EDID to optimize display resolution





Aprašymas

The CS1708A KVM switch is a control unit that allows access to multiple computers from a single PS/2 or USB console (keyboard, mouse, and monitor). A single CS1708A can control up to 8 computers. As many as 31 additional switches can be daisy-chained to each other, so that up to 256 computers can all be controlled from a single keyboard-monitor-mouse console. Additionally, a front panel USB port is available for each computer to access any peripherals connected to it on a one-at-a-time basis.

1x KVM Switch with Standard Rack Mounting Kit
1x 2L-5202P PS/2 KVM Cable
1x 2L-5202U USB KVM Cable
1x LIN5-27X6-U21G Console Cable
1x Firmware Upgrade Cable
1x Foot Pad Set(4 PCS)
1x 0AD6-1605-24EG Power Adapter
1x User Instructions

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	256
Keyboard port type	USB, PS/2
Mouse port type	USB, PS/2
Video port type	VGA
Console ports	USB A, VGA (D-Sub)
Console USB ports quantity	1
USB connector type	USB Type-A
DC-in jack	Yes
Performance	
HD type	QXGA
Maximum resolution	2048 x 1536 pixels
Scan interval	1,255 s
DDC/DDC2 supported	Yes
DDC2B support	Yes
Daisy chain	Yes
Firmware upgradeable	Yes
Design	
Rack mounting	Yes
Product colour	Black
Rack capacity	1U
Housing material	Metal
LED indicators	Yes
Push button	Yes
Hot keys	Yes
Display	
Built-in display	No
On Screen Display (OSD)	Yes
Power	
Power source	DC
Input voltage	5.3 V
Power consumption (typical)	5 W
System requirements	

Windows operating systems supported	Yes
Linux operating systems supported	Yes
Mac operating systems supported	Yes
Sustainability	
Compliance certificates	RoHS
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	437.2 mm
Depth	159.9 mm
Height	44 mm
Weight	3.41 kg
Packaging data	
Package width	116 mm
Package depth	540 mm
Package height	233 mm
Package weight	3.85 kg
Packaging content	
Cables included	KVM
Logistics data	
Master (outer) case net weight	10.2 kg
Harmonized System (HS) code	85176200
Master (outer) case width	375 mm
Master (outer) case length	565 mm
Master (outer) case height	258 mm
Master (outer) case gross weight	12.2 kg
Products per master (outer) case	3 pc(s)

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.

Datung Road No.125, Sec. 2, 221 New Taipei City, TW

aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt