ATEN USB VGA KVM Extender with Audio and RS-232 (200m)

Gamintojas: **ATEN** · Modelis: **CE750A-AT-G** · EAN: **4719264643859** · Prekės kodas: **813631**



405,89 €

Kaina su PVM

Be PVM: **335,45 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Local and Remote units connect at distances up to 200 meters using Cat 5e cable
- ✓ Dual console operation – control your system from both the local and remote USB keyboard, monitor, and mouse consoles
- ✓ Built-in ASIC for greater reliability and compatibility
- ✓ USB keyboard and USB mouse ports
- ✓ RS-232 serial ports – allows you to connect to a serial terminal for configuration (Local Unit) or serial devices such as touchscreens and barcode scanners (Remote Unit)
- ✓ Supports stereo speakers and stereo microphone
- ✓ USB overcurrent detection and prevention
- ✓ Pushbutton operating mode selection (Local Unit only) – select between Local and Auto operating modes
- ✓ Built-in 8KV/15KV ESD protection (contact voltage 8KV, air voltage 15KV) and 2KV surge protection
- ✓ Adjustable gain control – automatically and manually adjusts signal strength to compensate for distance







Aprašymas

The CE750A is a USB-based KVM Extender with automatic signal compensation and RS-232 serial functionality that allows access to a computer system from a remote USB console (USB keyboard, monitor, and USB mouse).

Because it allows access to a computer system from a remote console, the CE750A is perfect for use in any type of installation where you need to place the console where it is conveniently accessible, but you want the system equipment to reside in a safe location – for example away from the dust and dirt of the factory floor or the harsh environment of a construction site.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

The CE750A improves on previous designs by the addition of an RS-232 port, on both the Local and Remote Units, that allows you to connect to a serial terminal for configuration (Local Unit) or serial devices such as touchscreens and barcode scanners (Remote Unit).

Techninė specifikacija

Features	
Type	Transmitter & receiver
Connectivity technology	Wired
Maximum transfer distance	200 m
Cable types supported	Cat5
Maximum digital resolution	1920 x 1200 pixels
KVM port selection	Push-buttons
Product colour	Black
Material	Metal
Certification	RoHS
Transmitter	
Transmitter local video port type	VGA
Transmitter local keyboard/mouse port type	USB
Receiver	
Receiver local video port type	VGA
Receiver local keyboard/mouse port type	USB
Weight & dimensions	
Transmitter width	8.63 cm
Transmitter depth	20.2 cm
Transmitter height	2.5 cm
Transmitter weight	470 g
Receiver width	8.51 cm
Receiver depth	20.2 cm
Receiver height	2.5 cm
Receiver weight	470 g
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.
Datung Road No.125, Sec. 2, 221 New Taipei City, TW
aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.