# ATEN CL3800NW rack console 47 cm (18.5") 1920 x 1080 pixels Metal, Plastic Black 1U

Gamintojas: **ATEN** · Modelis: **CL3800NW F** · EAN: **4710469343759** · Prekės kodas: **813796**



**2 465,90 €**

Kaina su PVM

Be PVM: **2 037,93 €**

**Sandėlyje**

**Prekė internetu**
Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ Exclusive LED illumination light - designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions
- ✓ Integrated KVM Console with short depth dual rail design and a 18.5” LED-backlit LCD monitor allows you to work in narrow spaces
- ✓ Supports an external console with USB / DVI / VGA / HDMI connectors
- ✓ The 18.5" LCD screen offers resolutions of up to 1920 x 1080 (Full HD) @ 60Hz for CL3800NW and resolutions of up to 1366 x 768 @ 60Hz for CL3800NX









## Aprašymas

The CL3800 USB HDMI DVI VGA LCD Console is a short depth dual rail LCD KVM console featuring an 18.5" LED-backlit widescreen LCD monitor with an integrated keyboard and touchpad. The short-depth design fits all 19" equipment cabinets, and is especially suitable for shallow racks. In addition

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

to saving valuable space on the rack, the CL3800 also provides a space-saving solution for special environments, such as outside broadcast vans (OB vans) and compact control rooms.

The CL3800 supports three types of video input – HDMI, DVI, and VGA – and provides the ultimate in installation flexibility by allowing users to connect the console and the computer via any of the three types of video source. The CL3800NW’s full HD widescreen LCD monitor ensures excellent video quality and provides ample viewing area.

Furthermore, the dual rail design enables the LCD monitor, keyboard and touchpad to operate independently of each other. To maximize space utilization, the keyboard and touchpad modules can slide back to "hideaway" when not in use, while the thin profile LCD monitor rotates back, flush against the rack, to allow the convenient monitoring of computer activity.

For added convenience, users can choose to manage the computer from an external console. The CL3800 features a port for an external USB mouse on the unit’s front panel, while ports for the second KVM console (USB keyboard/mouse and HDMI, DVI, or VGA monitor) are provided on the rear panel. The CL3800 also includes two mini stereo ports for connecting audio speakers.

With a rich feature set, the CL3800 is designed to exceed the requirements for space utility optimization, superior video quality, adaptive deployment, and operational versatility, and is ideal for applications such as mobile live streaming in the broadcasting sector or control rooms with limited space in any industry.

Note: Optional rack mount kits are available. For more information, refer to Compatible Accessories below.

## Techninė specifikacija

| | |
|---|---|
| **Display** | |
| Display diagonal | 47 cm (18.5") |
| Display resolution | 1920 x 1080 pixels |
| Display | LCD |
| Display brightness | 350 cd/m² |
| Contrast ratio (typical) | 1000:1 |
| Viewing angle, horizontal | 178° |
| Viewing angle, vertical | 178° |
| On Screen Display (OSD) | Yes |
| Pixel pitch | 0.213 x 0.213 mm |
| Display type | TFT |
| Response time | 20 ms |
| Supported resolutions | up to 1920 x 1200 @ 60Hz; 1920 x 1080 @ 60 Hz, DDC2B |
| **Technical details** | |
| Rack capacity | 1U |
| Material | Metal, Plastic |
| Product colour | Black |
| Hot-Plug support | Yes |
| Operating relative humidity (H-H) | 0 - 80% |

| | |
|---|---|
| Built-in KVM switch | Yes |
| Maximum resolution | 1920 x 1200 pixels |
| Rack mounting | Yes |
| Number of computers controlled | 1 |
| On/off switch | Yes |
| LED indicators | Yes |
| Push button | Yes |
| Compliance certificates | RoHS |
| **Ports & interfaces** | |
| 3.5 mm (1/8-inch) in | Yes |
| VGA (D-Sub) ports quantity | 2 |
| DVI connector type | DVI-D |
| DVI input ports | 1 |
| DVI output ports | 1 |
| Keyboard port type | USB |
| Mouse port type | USB |
| Video port type | DVI/HDMI/VGA |
| USB 2.0 Type-A ports quantity | 3 |
| USB 2.0 Type-B ports quantity | 1 |
| I/O ports | 2x HDMI |
| **Keyboard** | |
| Built-in touchpad | Yes |
| Keyboard language | French |
| Keyboard layout | AZERTY |
| Hot keys | Yes |
| **Power** | |
| AC adapter input voltage | 100 - 240 V |
| AC adapter frequency | 50/60 Hz |
| Input current | 1 A |
| AC (power) in | Yes |
| **Operational conditions** | |
| Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -20 - 60 °C |
| **System requirements** | |

| | |
|---|---|
| Windows operating systems supported | Yes |
| Mac operating systems supported | Yes |
| Linux operating systems supported | Yes |
| Other operating systems supported | SunOS |
| **Weight & dimensions** | |
| Width | 514.2 mm |
| Height | 42.8 mm |
| Depth | 480.6 mm |
| Weight | 9.61 kg |
| **Packaging content** | |
| Cables included | AC, KVM |
| Quick installation guide | Yes |
| Manual | Yes |
| AC adapter included | Yes |
| Rack mount kit | Yes |
| Package type | Box |
| **Matmenys ir svoris** | |
| Svoris | 12,95kg |

## Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- Vaizdo įrašas youtube.com/watch?v=bXbkMAEYL0M

## Gamintojo ir saugos informacija

GAMINTOJAS

**ATEN INTERNATIONAL CO., LTD.**
Datung Road No.125, Sec. 2, 221 New Taipei City, TW
aten.com

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt