Lindy 100m USB 3.2 Gen 1 Cat.6A HDBaseT Extender

Gamintojas: **LINDY** · Modelis: **43410** · EAN: **4002888434102** · Prekės kodas: **814429**



376,90 €

Kaina su PVM

Be PVM: **311,49 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Extend 4 USB 3.2 Gen 1 ports up to 100m using Cat.6A network cable (not included)
- ✓ Power over Cable requires a single power supply to be connected to the transmitter or receiver only
- ✓ Supports USB 3.2 Gen 1 (USB 3.0) up to 5Gbps, USB 2.0/1.1 backwards compatibility, RS232 and FSYNC pass-through ports
- ✓ Plug & Play installation






Aprašymas

This Lindy USB 3.2 Gen 1 Cat.6A Extender can be used to extend the distance between USB peripheral devices and the host computer by up to 100m. Supports multiple USB signals, control, bulk, interrupt and isochronous data transfer.
A standard Cat.6A or above network cable* (not included) is used to bridge the connection between the transmitter and the receiver unit at the maximum supported distance of 100m (328.08ft). It's also possible to reach up to 40m using a Cat.6 cable.

The Extender features Power over Cable, which requires a single power supply only to be connected either to the transmitter unit or to the receiver unit. The 4 Type A ports on the Receiver can provide 5V power as well to the connected devices; 2 ports support up to 1.5A each and 2 ports support up to 1A each.

Status LEDs help the user to check power, link between Transmitter and Receiver and if data transfer is running while additional RS232 and FSYNC GPIO pass-though ports allow sending bi-directional commands also for industrial cameras.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

With robust metal housing and mounting brackets, this Extender is the ideal solution for professional applications and industrial environments.

In addition, the power supply is connected via a screw type DC jack, providing a more secure and reliable connection, perfect for professional installations where accidental disconnections could create a major issue.

*: To cover long distances close to the 100m limit, we recommend using HDBaseT-certified Cat.6A (or above) cables.

HDBaseT is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

HDBaseT Trade Mark and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. Using a different cable type, introducing wall plates, couplers or patch panels will result in a reduction of possible distances.

Techninė specifikacija

Features	
Type	Transmitter & receiver
Connectivity technology	Wired
Maximum transfer distance	100 m
Cable types supported	Cat6a
Product colour	Black
Material	Metal
Plug and Play	Yes
LED indicators	Yes
Transmitter	
Transmitter local keyboard/mouse port type	USB
RJ-45 ports quantity (transmitter)	1
Transmitter USB Type-B ports quantity	1
Receiver	
RJ-45 ports quantity (receiver)	1
Receiver USB Type-A ports quantity	4
Ports & interfaces	
USB port type	USB Type-A/USB Type-B
RS-232 ports	4
Power	
AC input voltage	24 V
Input current	2 A
DC-in jack	Yes
Weight & dimensions	

Transmitter width	10 cm
Transmitter depth	8.5 cm
Transmitter height	3 cm
Transmitter weight	500 g
Receiver width	10 cm
Receiver depth	8.5 cm
Receiver height	3 cm
Receiver weight	500 g
Packaging data	
Package width	235 mm
Package depth	150 mm
Package height	80 mm
Package weight	900 g
Packaging content	
AC adapter included	Yes
Cables included	USB Type-A
Manual	Yes
Mounting bracket(s) included	Yes
Included power plug types	AU, EU, UK, US
Screws included	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 90%
Other features	
Warranty period	2 year(s)
Bandwidth	5 Gbit/s
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
Matmenys ir svoris	
Matmenys (I × P × A)	24,00cm × 15,00cm × 8,00cm
Svoris	1,08kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- CE ženklinimas

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.
Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB
lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH
Markircher Str. 22, 68229 Mannheim, DE
lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- CE ženklinimas