

Zebra ZE500 label printer 300 x 300 DPI 305 mm/sec Wired Ethernet LAN

Gamintojas: **ZEBRA** · Modelis: **ZE50043-LOE0000Z** · EAN: **8596375176317** · Prekės kodas: **816956**



4 658,90 €

Kaina su PVM

Be PVM: **3 850,33 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 300 x 300 DPI
- ✓ Maximum printing width: 10.4 cm Print speed: 305 mm/sec
- ✓ Built-in barcodes: 1D, 2D, CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 49, Code 93, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, QR Code, TLC39, UPC-A, UPC-E
- ✓ Connectivity technology: Wired
- ✓ USB port Ethernet LAN
- ✓ Display: LCD
- ✓ 15.4 kg

Aprašymas

ZE500 Print Engines

The ZE500 series takes an innovative approach to OEM print engines. Leveraging customer research, the design focuses on ease of use, integration and servicing. Built with the customer in mind, the ZE500 is designed to keep mission-critical print-and-apply applications operating with no interruptions.

Used For:

- Cross Docking;
- Receiving/Shipping;
- Compliance Labeling;
- Order Labeling.

The elegant design of the ZE500 simplifies maintenance and dramatically reduces downtime. All three rollers can be exchanged in minutes, with no need to access the printer's electronics. The wide open printhead makes cleaning and replacement simple, and the quickchange modular drive

system reduces printer repair time.

Routine operations such as ribbon changing are simple and straightforward (and identical for both print widths). The new graphic display can be deported and rotated, enabling flexible positioning for improved ease of use and integration.

The user experience is much improved: the design enables easy integration with print-and-apply machinery plus has better resistance to dust and water. Expanded connectivity ports and enhanced software control of the applicator port provides further integration flexibility.

Techninė specifikacija

Printing	
Maximum resolution	300 x 300 DPI
Print speed	305 mm/sec
Maximum printing width	10.4 cm
Paper handling	
Ribbon width	10.7 cm
Ribbon length	600 m
Maximum label width	11.4 cm
Maximum roll diameter	10.2 cm
Media thickness	0.254 mm
Media thickness (imperial)	0.010"
Maximum media length	3.81 m
Maximum media length (imperial)	150"
Core diameter	2.54 cm
Ports & interfaces	
Connectivity technology	Wired
Ethernet LAN	Yes
Wi-Fi	No
USB port	Yes
USB 2.0 ports quantity	1
Parallel ports quantity	1
RS-232 ports	1
RS-232 interface	Yes
Performance	
Page description languages	XML, ZPL, ZPL II
Internal memory	16 MB
Flash memory	64 MB

Built-in barcodes	1D, 2D, CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 49, Code 93, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, QR Code, TLC39, UPC-A, UPC-E
Built-in processor	Risc
Processor frequency	133 MHz
Certification	IEC, EN, NRTL, CE, FCC, CCC, ICES, VCCI, NOM, KCC, BSMI, S-Mark, C-Tick, Gost-R
Design	
Product colour	Black
Display	LCD
Built-in display	Yes
Housing material	Metal
Power	
Power requirements	90 - 264V AC, 47/63Hz
System requirements	
Compatible operating systems	Windows 7 Windows XP Windows Vista Windows Server 2008 Windows Server 2003
Operational conditions	
Operating relative humidity (H-H)	20 - 85%
Storage relative humidity (H-H)	5 - 95%
Operating temperature (T-T)	32 - 104 °F
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 71 °C
Storage temperature (T-T)	-40 - 160 °F
Weight & dimensions	
Width	245 mm
Depth	379 mm
Height	300 mm
Weight	15.4 kg
Packaging content	
Bundled software	ZebraDesigner Pro ZebraNet Bridge Enterprise ZBI 2.0 ZBI-Developer
Logistics data	
Harmonized System (HS) code	84433210
Technical details	
Sustainability certificates	ENERGY STAR
Other features	

Networking features

Fast Ethernet

Gamintojo ir saugos informacija

GAMINTOJAS

Zebra

ATSAKINGAS ASMUO ES

Zebra Technologies

Borupvang 3, Ballerup, DK

zebra.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt