StarTech.com USB-C/USB-A to M.2 NVMe Dock Adapter, 10Gbps, Tool-Free External M.2 NVMe SSD Reader, B+M/M-Key

Gamintojas: **STARTECH.COM** · Modelis: **1USB3-NVME-DOCK** · EAN: **065030912563** · Prekės kodas: **817881**



67,91 €

Kaina su PVM

Be PVM: **56,12 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Versatile M.2 NVMe Drive Access: Enable fast, tool-free access to an M.2 NVMe drive through a USB-C or USB-A 10Gbps host; Toaster-style M.2 slot optimizes airflow and is ideal for standard and high-performance M.2 NVMe drives with attached heat sinks
- ✓ Ideal for Diagnostics and Troubleshooting: Quickly troubleshoot M.2 NVMe drives to monitor drive health, test performance, or recover data; Use as a portable M.2 NVMe drive dock for compatibility testing, disk imaging, or storage expansion
- ✓ Portable and Bus-Powered: Compact, lightweight design that fits into any IT toolkit; Runs entirely on USB bus power when connected to an M.2 NVMe drive, with no external power adapter required
- ✓ Driverless Setup and Broad Compatibility: Integrated USB-C cable with USB-A adapter for quick and universal host access on Windows/macOS/Linux; Supports 2230/2242/2260/2280 M.2 NVMe PCIe Gen5 SSDs, up to 10Gbps; Note: M.2 SATA drives are not supported
- ✓ The IT Pro's Choice: Our external drive adapters are lab-tested for enterprise-grade performance, and constructed from 70% post-consumer recycled (PCR) plastic to help reduce material waste; Backed by free lifetime 24/5 multi-lingual technical assistance








Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903


















Aprašymas

Access Ultra-Fast M.2 NVMe drive storage via USB 10Gbps

Access and manage M.2 NVMe SSDs through a single USB-C or USB-A 10Gbps connection. The M.2 NVMe SSD Dock enables fast read and write access for data transfer, recovery, and upgrades. This drive reader is a versatile solution for IT professionals performing backups, disk imaging, or maintenance on M.2 NVMe drives.

External Drive Access over USB-C and USB-A

Connect the M.2 NVMe Dock directly to a laptop or workstation using the integrated USB-C cable with USB-A adapter. The open-top, toaster-style M.2 slot maintains airflow for consistent performance during sustained workloads and provides ample clearance to support NVMe drives with attached heatsinks. The NVMe adapter supports read/write speeds of up to 10Gbps. Please note that M.2 SATA drives are not supported.

Compact Form Factor

Lightweight and portable, the USB-C/USB-A to M.2 NVMe Dock Adapter fits easily into any IT toolkit or workspace. The enclosure is constructed from 70% post-consumer recycled (PCR) plastic with a 35% PCR TPE jacket, and is packaged in 100% plastic-free FSC certified packaging to help reduce material waste. It runs entirely on USB bus power, requiring no external power adapter. Ideal for IT technicians and end users needing portable, fast M.2 NVMe drive access.

Techninė specifikacija

Hard drive	
Storage media type	SSD
Storage drive interface	M.2
Storage drive sizes supported	M.2
Number of storage drives supported	1
Ports & interfaces	
Host interface	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
Features	
Product colour	Black

Maximum data transfer rate	10 Gbit/s
Hot-swap	Yes
S.M.A.R.T. support	Yes
TRIM support	Yes
LED indicators	Yes
UASP support	Yes
Cooling	
Built-in fan	No
Weight & dimensions	
Width	59 mm
Depth	403.7 mm
Height	18 mm
Weight	62 g
Packaging data	
Package width	152 mm
Package depth	100 mm
Package height	30 mm
Package weight	109 g
Packaging content	
User guide	Yes
Interface adapters included	USB Type-A male - USB Type-C female
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 85%
Other features	
Chipset	ASMedia - ASM2362
Mean time between failures (MTBF)	129956 h
Logistics data	
Master (outer) case width	485 mm
Master (outer) case length	325 mm
Master (outer) case height	230 mm
Products per master (outer) case	60 pc(s)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.
Artisans Crescent 45, N5V 5E9 Ontario, London, CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited
Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt