

# Zebra ZD230 label printer Thermal transfer 203 x 203 DPI 152 mm/sec Wired Ethernet LAN

Gamintojas: **ZEBRA** · Modelis: **ZD23042-31EC00EZ** · EAN: **5715063054994** · Prekės kodas: **818463**



## 402,91 €

Kaina su PVM

Be PVM: **332,98 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Thermal Transfer or Direct Thermal print method
- ✓ ZPL and EPL programming languages
- ✓ Single LED status indicator
- ✓ Single button for feed/pause
- ✓ USB connectivity
- ✓ OpenACCESS™ for easy media loading
- ✓ Dual-wall frame construction
- ✓ ENERGY STAR qualified



## Aprašymas

Not all printers are created equally, especially basic models. To reduce costs, value printers are often constructed using less expensive components and fewer features. Many fail to perform under more demanding duty cycles, create delays and downtime for repairs, and require replacement after

only a few years of use. Instead of conserving budget, customers are left with greater expense and hassle. Zebra does it differently. Meet the exception. The ZD230 desktop printer gives you extra features and reliable operation at an affordable price—both at the point of purchase and across the entire lifecycle. Engineered with Zebra quality, it boasts a dual wall construction. And, it offers wireless connectivity for networked, remote printing. Built to last for years, the ZD230 provides an outstanding return on your investment.

## Just the Features You Need

This 4-inch printer produces labels quickly, up to 6" per second, to keep your workflows moving. Increased memory allows you to store more fonts and graphics. A single LED indicator and single button for feed/pause make it easy to operate and identify printer status. Choose from direct thermal or thermal transfer models, and add an optional factory-installed peeler or cutter. The ZD230 features a core set of Print DNA software applications, powered by Link-OS Basic, to deliver a cost-effective and dependable print experience. It is ideal for use in transportation and logistics, light manufacturing, retail and healthcare applications to print a variety of tickets, tags, passes, labels and receipts.

## Backed by Zebra's Worldwide Service and Support

Access support quickly anywhere around the globe through Zebra's trusted network of more than 10,000 partners. Avoid costly repairs and downtime with an affordable service plan that's tailored to the coverage you need for your desktop printer. Zebra's OneCare SV provides the right level of service at the right price. It gives you two years of coverage for normal wear and tear, double the standard warranty coverage, priority turnaround times at the depot and more—all for a tiny fraction of the cost of a single repair.

## Consistently Exceptional Zebra Certified Supplies

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pretest our own line of thermal printing supplies to ensure consistent, optimised performance in your Zebra printer—and peace of mind for you. For industry-leading quality, service and thermal printing expertise, choose Zebra Certified Supplies.

The ZD230 gives you more. The quality and reliability you expect from Zebra, along with the extra features you need. And, it helps you conserve costs now, and for years to come. Gain your competitive edge with Zebra.

## Get Printing Quickly

The ZD230 is simple to install and begin printing – right out of the box. Easily replace legacy printers using ZPL, EPL or non-Zebra command languages. USB, Ethernet, Wi-Fi and Bluetooth® connectivity options enable universal interoperability. The ZD230 can accommodate a 300 M ribbon roll to lengthen the time between media changes. And, Zebra's OpenACCESS™ clamshell design expedites media replacement. It's also ENERGY STAR® qualified to reduce your operational expenses.

## Techninė specifikacija

| Printing               |                  |
|------------------------|------------------|
| Print technology       | Thermal transfer |
| Colour                 | No               |
| Maximum resolution     | 203 x 203 DPI    |
| Print speed            | 152 mm/sec       |
| Maximum printing width | 10.4 cm          |
| Paper handling         |                  |
| Ribbon width           | 10.9 cm          |
| Ribbon length          | 300 m            |

|                                   |                                                                                                                                                                                                                                                     |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum label width               | 11.2 cm                                                                                                                                                                                                                                             |
| Maximum label length              | 0.991 m                                                                                                                                                                                                                                             |
| Maximum roll diameter             | 12.7 cm                                                                                                                                                                                                                                             |
| Media thickness                   | 0.08 - 0.1905 mm                                                                                                                                                                                                                                    |
| Supported paper width             | 25.4 - 112 mm                                                                                                                                                                                                                                       |
| Core diameter                     | 1.27 cm                                                                                                                                                                                                                                             |
| Ports & interfaces                |                                                                                                                                                                                                                                                     |
| Connectivity technology           | Wired                                                                                                                                                                                                                                               |
| Ethernet LAN                      | Yes                                                                                                                                                                                                                                                 |
| Wi-Fi                             | No                                                                                                                                                                                                                                                  |
| USB port                          | Yes                                                                                                                                                                                                                                                 |
| Bluetooth                         | No                                                                                                                                                                                                                                                  |
| USB 2.0 ports quantity            | 1                                                                                                                                                                                                                                                   |
| Performance                       |                                                                                                                                                                                                                                                     |
| Page description languages        | EZPL, XML, ZPL II                                                                                                                                                                                                                                   |
| Internal memory                   | 128 MB                                                                                                                                                                                                                                              |
| Flash memory                      | 256 MB                                                                                                                                                                                                                                              |
| Built-in barcodes                 | 1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Data Matrix, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, QR Code, UPC-A, UPC-E                                                |
| Number of fonts                   | 23                                                                                                                                                                                                                                                  |
| Certification                     | IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus, CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM |
| Design                            |                                                                                                                                                                                                                                                     |
| Product colour                    | Black                                                                                                                                                                                                                                               |
| Display                           | No                                                                                                                                                                                                                                                  |
| Built-in display                  | No                                                                                                                                                                                                                                                  |
| Power                             |                                                                                                                                                                                                                                                     |
| AC input voltage                  | 100 - 240 V                                                                                                                                                                                                                                         |
| AC input frequency                | 50 - 60 Hz                                                                                                                                                                                                                                          |
| Operational conditions            |                                                                                                                                                                                                                                                     |
| Operating relative humidity (H-H) | 10 - 90%                                                                                                                                                                                                                                            |
| Storage relative humidity (H-H)   | 5 - 95%                                                                                                                                                                                                                                             |
| Operating temperature (T-T)       | 4.4 - 41 °C                                                                                                                                                                                                                                         |

|                             |             |
|-----------------------------|-------------|
| Storage temperature (T-T)   | -40 - 60 °C |
| Weight & dimensions         |             |
| Width                       | 197 mm      |
| Depth                       | 267 mm      |
| Height                      | 191 mm      |
| Weight                      | 1.1 kg      |
| Packaging content           |             |
| Cables included             | AC          |
| Logistics data              |             |
| Harmonized System (HS) code | 84433210    |
| Technical details           |             |
| Sustainability certificates | ENERGY STAR |

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

**Zebra**

ATSAKINGAS ASMUO ES

**Zebra Technologies**

Borupvang 3, Ballerup, DK  
[zebra.com](https://zebra.com)

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**

V. Nagevičiaus g. 3, LT-08237 Vilnius  
[info@shopro.lt](mailto:info@shopro.lt)