

StarTech.com 1P1FFCN-USB-SERIAL serijinis kabelis Juoda 0,3 m USB A tipo DB-9

Gamintojas: **STARTECH** · Modelis: **1P1FFCN-USB-SERIAL** · EAN: **065030898362** · Prekės kodas: **819212**



37,90 €

Kaina su PVM

Be PVM: **31,32 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 0,3 m
- ✓ USB A tipo Kištukinis Tiesus
- ✓ DB-9 Lizdinis Tiesus
- ✓ FTDI - FT232R 921,6 Kbit/ai
- ✓ Duomenų bitai: 7, 8 256 B
- ✓ Juoda
- ✓ 1 vnt



Aprašymas

Add an RS-232 null modem serial port to a laptop or desktop, using an available USB-A port

Add RS-232 DCE serial communications support to a desktop or laptop computer and resolve DCE/DTE conflicts directly without the need for additional cross-wired serial cables or adapters.

Serial Port Expansion

The 1-foot (30-centimeter) Null Modem USB Serial Adapter adds an RS-232 serial DB/DE-9 (female) connector to a desktop or laptop via a USB Type-A port. Secure the adapter to a serial device, using pre-installed and removable DB-9 nuts, or install the included slotted D-Sub thumbscrews for compatibility with other serial peripheral devices or cables.

LED Indicators

Data transmission and reception LED indicators on the adapter provide real-time monitoring of port activity. The USB LED indicates when the adapter has successfully enumerated on the desktop or laptop. All the LEDs aid with diagnostics and troubleshooting.

Seamless Connectivity

The adapter is compatible with Windows, macOS, ChromeOS, and Linux. Drivers automatically install to Windows 7 and newer versions, macOS 10.15 and above, and Linux. The USB to RS-232 adapter features COM retention, which automatically reassigns the COM port value if the cable is disconnected and reconnected, or if the system is rebooted.

Built To Last

The rugged TPE construction and Level-4 ESD protection (15kV air and 8kV contact) enhance the reliability and longevity of the USB to Serial Adapter. Copper shielding minimizes Electromagnetic and Radio Frequency Interference (EMI and RFI). Gold-plated connectors enhance signal conductivity.

Techninė specifikacija

Savybės	
Produkto spalva	Juoda
Kabelio ilgis	0,3 m
Jungtis 1	USB A tipo
Jungtis 2	DB-9
1 jungtis – vidinė ar išorinė	Kištukinis
2 jungtis – vidinė ar išorinė	Lizdinis
1 jungties forma	Tiesus
2 jungties forma	Tiesus
Lustų rinkinys	FTDI - FT232R
Sparta	921,6 Kbit/ai

Duomenų bitai	7, 8
FIFO (anksčiau įsigytų atsargų sunaudojimo metodas)	256 B
Pariteto bitas	Vienoda, „Mark“, Ne, Nelyginis, Kosmosas
Stabdos bitai	1, 2
Palaikomos „Windows“ operacinės sistemos	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 Enterprise, Windows 11 Enterprise x64, Windows 11 Home, Windows 11 Pro, Windows 11 x64, Windows 2000, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Palaikomos MAC operacinės sistemos	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos serverio valdymo sistemos	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022
Pakuotės duomenys	
Kiekis pakuotėje	1 vnt
Pakuotės plotis	197 mm
Pakuotės gylis	174 mm
Pakuotės aukštis	19 mm
Paketo svoris	30 g
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-40 - 80 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 80 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Svoris ir matmenys	
Svoris	30 g
Logistikos duomenys	
Pagrindinės (išorinės) dėžės plotis	577 mm
Pagrindinės (išorinės) dėžės ilgis	364 mm
Pagrindinės (išorinės) dėžės aukštis	305 mm
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	80 vnt

Matmenys ir svoris

Matmenys (l × p × a)	20,00cm × 19,00cm × 2,00cm
Svoris	0,07kg

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)
- > [Vaizdo įrašas](#) youtube.com/watch?v=TheDfS4tEeY

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt