

# StarTech.com 3ft (1m) USB-C Charging Cable, Durable and Ultra-Flexible, 240W (5A) PD EPR, USB 2.0 Laptop Charger Cable, USB-IF Certified, Rugged USB-C Charging Cord

Gamintojas: **STARTECH** · Modelis: **S2CEPR1M-USB-CABLE** · EAN: **065030919968** · Prekės kodas: **819235**



**16,90 €**

Kaina su PVM

Be PVM: **13,97 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ **Charge High-Draw USB-C Devices**: Charge high-performance laptops with up to 240W of Power Delivery Extended Power Range (EPR) using this rugged and flexible USB-C cable; Performance markings on connectors ensure quick identification and removes guesswork
- ✓ **Certified for Compatible and Safe Charging**: Trust this USB-IF Certified Cable with E-marker chip to ensure reliable power delivery in critical workflow; Certified cables guarantee safe, regulated charging across USB-C PD-enabled devices
- ✓ **Designed for Everyday Use**: Dual-layer jacket combines a silicone inner layer for flexibility with braided nylon exterior for enhanced durability; Designed to withstand frequent 90° bends, with nickel-plated connectors rated beyond 20,000 insertions
- ✓ **Connect to a High-Power Charging Hub**: Integrate high-wattage charging hubs into workstation setups with reliable support for mobile devices and high-performance laptops, including 16-in MacBook Pro Max M-series; Supports USB 2.0 for general file transfer or sync
- ✓ **The IT Pro's Choice**: Our USB-C cables are rigorously tested in our in-house Innovation Lab for reliable performance, durable construction, and broad compatibility with a variety of devices; Backed by free lifetime 24/5 multi-lingual technical assistance





Aprašymas

Charge high-performance USB-C devices with this rugged and flexible silicone USB-C cable

Connect a charger or hub to a USB PD 3.1-enabled device with this USB-C cable, delivering up to 240W EPR Power Delivery and 5A output for fast charging. Clear connector markings ensure quick identification, eliminating guesswork and ensuring full 240W charging support. Always choose the correct Type-C cable for optimal performance and compatibility.

Rugged and Flexible

The USB-C EPR Charging Cable features a silicone inner jacket with a braided nylon exterior for optimal flexibility and wear protection. The durable nickel-plated connectors are designed for frequent daily use, and are rated to operate beyond 20,000 insertion cycles.

Charge Mobile Devices On The Go

Charge a USB-C device with a USB-C wall charger, car charger, or power bank. The 1-meter (3.3-foot) USB Type-C cable is the ideal length for desk and mobile workstations, commuters, in-car use or to reduce clutter when syncing with a USB-C laptop.

Power a Laptop

With up to 5A of output, the USB-C Charger Cord supports up to 240W of Power Delivery to charge a USB-C laptop, or fast charge a tablet or smartphone. To use, connect the cable from a USB-C laptop to a USB-C wall charger.

Techninė specifikacija

| Features                   |          |
|----------------------------|----------|
| USB version                | USB 2.0  |
| Connector 1                | USB C    |
| Connector 2                | USB C    |
| Connector 1 gender         | Male     |
| Connector 2 gender         | Male     |
| Product colour             | Black    |
| Connector 1 form factor    | Straight |
| Connector 2 form factor    | Straight |
| AWG wire size              | 30       |
| Connector contacts plating | Nickel   |

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Cable jacket material                 | Silicone                                      |
| Cable jacket type                     | Braided                                       |
| Maximum data transfer rate            | 0.48 Gbit/s                                   |
| Cable type                            | Round cable                                   |
| USB Power Delivery (USB PD)           | Yes                                           |
| USB Power Delivery revision           | 3.1                                           |
| USB Power Delivery up to              | 240 W                                         |
| USB Type-C DisplayPort Alternate Mode | No                                            |
| <b>Power</b>                          |                                               |
| Output current (max)                  | 5 A                                           |
| <b>Weight &amp; dimensions</b>        |                                               |
| Cable length                          | 1 m                                           |
| Cable diameter                        | 4.7 mm                                        |
| Weight                                | 41 g                                          |
| <b>Packaging data</b>                 |                                               |
| Package width                         | 220 mm                                        |
| Package depth                         | 128 mm                                        |
| Package height                        | 16 mm                                         |
| Package weight                        | 47 g                                          |
| <b>Packaging content</b>              |                                               |
| Quantity per pack                     | 1 pc(s)                                       |
| <b>Operational conditions</b>         |                                               |
| Operating temperature (T-T)           | 0 - 50 °C                                     |
| Storage temperature (T-T)             | -20 - 70 °C                                   |
| <b>Certificates</b>                   |                                               |
| Compliance certificates               | Federal Communications Commission (FCC), RoHS |
| <b>Logistics data</b>                 |                                               |
| Products per master (outer) case      | 240 pc(s)                                     |
| Master (outer) case width             | 500 mm                                        |
| Master (outer) case length            | 320 mm                                        |
| Master (outer) case height            | 210 mm                                        |
| <b>Matmenys ir svoris</b>             |                                               |
| Matmenys (l × p × A)                  | 16,00cm × 12,00cm × 2,00cm                    |
| Svoris                                | 0,05kg                                        |

## Dokumentai ir vaizdo įrašai

- > [Gaminio lankstinukas](#)
- > [Vaizdo įrašas](#) [youtube.com/watch?v=4tmW1XMr\\_c8](https://youtube.com/watch?v=4tmW1XMr_c8)

## Gamintojo ir saugos informacija

### GAMINTOJAS

#### StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,  
CA  
[startech.com](https://startech.com)

### ATSAKINGAS ASMUO ES

#### StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL  
[startech.com](https://startech.com)

### PLATINTOJAS

#### MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius  
[info@shopro.lt](mailto:info@shopro.lt)