

Lenovo ThinkSystem SR650 V3 server Rack (2U) Intel Xeon Silver 4510 2.4 GHz 32 GB DDR5-SDRAM 1100 W

Gamintojas: **LENOVO** · Modelis: **7D76100WEA** · Prekės kodas: **821965**



4 833,90 €

Kaina su PVM

Be PVM: **3 994,96 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

✓ Intel Xeon Silver 4510 (30MB Cache, 2.4GHz)

✓ 32GB (5600MHz) DDR5-SDRAM (1 x 32)

Aprašymas

The Lenovo ThinkSystem SR650 V3 is an ideal 2-socket 2U rack server for small businesses up to large enterprises that need industry-leading reliability, management, and security, as well as maximizing performance and flexibility for future growth. The SR650 V3 is designed to handle a wide range of workloads, such as databases, virtualization and cloud computing, virtual desktop infrastructure (VDI), infrastructure security, systems management, enterprise applications, collaboration/email, streaming media, web, and HPC.

This product guide provides essential pre-sales information to understand the ThinkSystem SR650 V3 server, its key features and specifications, components and options, and configuration guidelines. This guide is intended for technical specialists, sales specialists, sales engineers, IT architects, and other IT professionals who want to learn more about the SR650 V3 and consider its use in IT solutions.

Techninė specifikacija

Processor

Processor family	Intel Xeon Silver
Processor manufacturer	Intel
Processor model	4510
Processor frequency	2.4 GHz
Processor generation	Intel Xeon Scalable 5th Gen

Processor boost frequency	4.1 GHz
Processor cores	12
Processor cache	30 MB
Number of processors installed	1
Maximum number of SMP processors	2
Memory	
Internal memory	32 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	8 TB
Memory slots	32x DIMM
ECC	Yes
Memory clock speed	5600 MHz
Memory layout (slots x size)	1 x 32 GB
Storage	
Optical drive type	No
Supported SSD sizes	2.5"
Hot-swap	Yes
Supported storage drive interfaces	SAS
Graphics	
Maximum graphics card memory	16 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
VGA (D-Sub) ports quantity	1
Power cables quantity	2
Design	
Chassis type	Rack (2U)
Performance	
Performance management	XClarity Controller Platinum
Trusted Platform Module (TPM)	Yes
Trusted Platform Module (TPM) version	2
Software	

Compatible operating systems

Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server

Power

Redundant power supply (RPS) support

Yes

Power supply

1100 W

Number of redundant power supplies supported

1

Certificates

80 PLUS certification

80 PLUS Titanium

Weight & dimensions

Width

445 mm

Depth

766 mm

Height

87 mm

Gamintojo ir saugos informacija

GAMINTOJAS

Lenovo Group LimitedCourtyard Xibeiwang East Road Building 2, No.10,
100094 Beijing, CNlenovo.com

ATSAKINGAS ASMUO ES

Lenovo France SASRue des Deux Gares 20, 92500 Rueil-Malmaison,
FRlenovo.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt