Vertiv Avocent 32-Port ACS 8000 with dual AC Power Supply and Analog Modem - ACS8032MDAC-404

Gamintojas: **VERTIV** · Modelis: **ACS8032MDAC-404** · EAN: **636430086293** · Prekės kodas: **822180**



5 136,90 €

Kaina su PVM

Be PVM: **4 245,37 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Secure in-band and out-of-band network remote management
- ✓ Fast, automated configuration with Zero Touch Provisioning
- ✓ Access and troubleshoot remote locations using automatic network failover
- ✓ No need for adaptors with automatic Cyclades™ and Cisco pin-out conversions
- ✓ Compliance with data center access and security policies
- ✓ Console event logging and notification
- ✓ Integrated support for 1Gb SFP fiber modules
- ✓ USB ports to support new IT equipment and external devices



Aprašymas

The Avocent ACS 8000 advanced console server offers upgraded and advanced features, that deliver scalable and high-performance solutions for IT administrators. The console server features a dual ARM core processor platform with dual Gigabit Ethernet ports and dual Gigabit fiber ports for redundancy. In addition, there is a sensor port, to connect a variety of sensors for monitoring and logging on the appliance. The serial ports are auto sensing for pin-out and the Avocent ACS 8000 advanced console server also offers robust features to meet the requirements of the demanding data center management applications. Features combine automated discovery tools to ease identification of servers, routers, switches and power devices, connected to any serial port, saving time at initial configuration and installation. To comply with existing data center network access policy, the Avocent ACS 8000 advanced console server provides customizable, multiple access levels for secure management. The console servers provide

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

a complete solution for secure, remote control with advanced console server features, such as enhanced security, data logging and event monitoring. In addition, the Avocent ACS 8000 advanced console server supports network standards, such as Internet Protocol version 6 (IPv6).

Techninė specifikacija

Technical details	
Rack mounting	Yes
Internal modem	Yes
Zero Touch Provisioning (ZTP)	Yes
Web-based management	Yes
Temperature sensor	Yes
Product colour	Black
Management features	
Management protocols	CLI, HTTP/ HTTPS, SNMP
Security	
Authentication method	LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP)
Security algorithms	3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3, SSH, SSH-2
IP address filtering	Yes
One-time password (OTP)	Yes
Ports & interfaces	
Console port	RJ-45
Serial ports quantity	32
USB 2.0 ports quantity	8
Ethernet LAN (RJ-45) ports	2
SFP module slots quantity	2
AC outlet types	C13 coupler
Software	
Operating system installed	Embedded LINUX
Weight & dimensions	
Dimensions (WxDxH)	438.2 x 241.3 x 44.5 mm
Weight	3.4 kg
Power	
Power source type	AC
AC input voltage	106 - 240 V
AC input frequency	50 - 60 Hz

Power consumption (typical)	20 W
Power consumption (max)	35 W
Input current	0.1 A
Number of power supply units	2
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	5 - 95%
Certificates	
Certification	FCC Class A, CE Class A (EU), ICES-003 (Canada), VCCI (Japan), RCM (Australia), Customs Union (CU), KCC (Korea), UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)
Memory	
Flash memory	16000 MB
RAM capacity	1024 MB
RAM type	DDR3L
eMMC capacity	16 GB
Processor	
Processor family	ARM Cortex-A9
Processor architecture	ARM Cortex-A9
Processor cores	2
Processor frequency	667 MHz
Network	
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Cable types supported	Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Fiber
Other features	
Safety	UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)
Matmenys ir svoris	
Matmenys (I × P × A)	56,00cm × 35,00cm × 20,00cm

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Gamintojo ir saugos informacija

GAMINTOJAS

Vertiv

ATSAKINGAS ASMUO ES

Vertiv GmbH
August-Everding-Str 25, 81671 München, DE
vertiv.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt