InLine 17205W „DisplayPort“ kabelis 5 m Balta

Gamintojas: **INLINE** · Modelis: **17205W** · EAN: **4043718347490** · Prekės kodas: **822208**



27,90 €

Kaina su PVM

Be PVM: **23,06 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5 m
- ✓ DisplayPort Tiesus Kištukinis
- ✓ DisplayPort Tiesus Kištukinis
- ✓ „DisplayPort“ versija: 1.4
- ✓ 7680 x 4320 pikseliai 120 Hz 32,4 Gbit/s
- ✓ Balta



Aprašymas

High resolution support for modern workplaces: Transmits razor-sharp images with up to 7680x4320 pixels at 60Hz – ideal for CAD, video editing, or presentation technology.
Reliable signal quality thanks to triple shielding: The robust cable construction effectively protects against electromagnetic interference – for a stable and secure connection.
Long-term investment security: With DisplayPort 1.4 specification, HDR support, and 8K compatibility, the cable meets the highest technical standards.
Professional workmanship with gold-plated contacts: Reduces contact resistance and extends service life with frequent reconnection – particularly important in changing system environments.
Universally applicable in IT and digital signage: Reliably connects PCs, workstations, monitors, and large displays in professional applications.

The InLine® DisplayPort 1.4 cable series offers a professional connection solution for demanding AV installations in office, technical, and industrial environments. It supports the transmission of image content in Ultra High Definition with a resolution of up to 7680x4320 (8K@60Hz) as well as 4K

content with high refresh rates of up to 120Hz. Thanks to support for HDR, RGB/4:4:4, 4:2:2, and 12-bit color depths, the cable delivers excellent image quality and high compatibility.
The triple-shielded design effectively protects against external interference and enables reliable data transmission—ideal for multi-monitor setups, digital signage solutions, or control rooms. Gold-plated contacts ensure durable, stable connections—even with frequent changes of connected devices. The series is ideal for a wide range of installation scenarios, both stationary and mobile.

DisplayPort connector to DisplayPort connector
DisplayPort version: 1.4
Supported resolutions: FUHD 7680x4320 8K@60Hz, UHD 3840x2160 120HZ RGB/4:4:4 8bit HDR OFF, UHD 3840x2160 120HZ RGB/4:2:2 12bit HDR ON, UHD 3840x2160 60HZ RGB/4:4:4 12bit HDR ON, FullHD 1920x1080
Shielding: triple shielded
Color: white
Contacts: gold-plated
Packaging: PE bag with EAN code

Techninė specifikacija

Savybės	
Kabelio ilgis	5 m
Jungtis 1	DisplayPort
Jungtis 2	DisplayPort
1 jungtis – vidinė ar išorinė	Kištukinis
2 jungtis – vidinė ar išorinė	Kištukinis
Maksimali rezoliucija	7680 x 4320 pikseliai
Produkto spalva	Balta
1 jungties forma	Tiesus
2 jungties forma	Tiesus
Jungties kontaktų dengimas	Auksas
„DisplayPort“ versija	1.4
Palaikomos grafikos rezoliucijos	1920 x 1080 (HD 1080), 3840 x 2160, 7860 x 4320
Maksimalus atnaujinimo dažnis	120 Hz
Magnetiškai ekranuoti	Taip
Ekranavimo sluoksnių skaičius	3
AWG laido dydis	28
Palaikoma HDR	Taip
Duomenų perdavimo sparta	32,4 Gbit/s
Spalvų pavyzdžiai	4:2:2, 4:4:4
Kabelio tipas	Apvalusis kabelis
Sertifikatai	
Atitikties sertifikatai	RoHS, TÜV mark, UL

Svoris ir matmenys	
Kabelio skersmuo	7 mm
Svoris	300 g
Pakuotės duomenys	
Pakuotės plotis	180 mm
Pakuotės gylis	240 mm
Pakuotės aukštis	40 mm
Paketo svoris	311 g
Pakuotės tipas	Užspaudžiamas maišelis
Pakuotės turinys	
Kiekis pakuotėje	1 vnt
Logistikos duomenys	
Kilmės šalis	Taivanas
Kitos savybės	
Ilgis	5000 mm
Aukštis	13 mm
Ilgis	5000 mm
Plotis	20 mm

Gamintojo ir saugos informacija

GAMINTOJAS

InLine

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt