InLine HDMI AOC cable, Ultra High Speed HDMI, 8K4K, detachable plug, 50m

Gamintojas: **INLINE** · Modelis: **17950O** · EAN: **4043718333769** · Prekės kodas: **822219**



121,90 €

Kaina su PVM

Be PVM: **100,74 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 50 m
- ✓ HDMI Type-A/HDMI Type-D Straight Male
- ✓ HDMI Type-A/HDMI Type-D Straight Male
- ✓ HDMI version: 2.1
- ✓ 48 Gbit/s
- ✓ Dolby TrueHD, DTS-HD
- ✓ 3D Audio Return Channel (ARC)
- ✓ Black





Aprašymas

Flexible installation thanks to narrow installation paths: Removable HDMI A and HDMI D connectors allow easy routing through cable ducts – ideal for AV installations.
Loss-free signal quality: Active optical HDMI 2.1 technology enables high-resolution video and audio signals in the highest quality.
Versatile combination options: 4-in-1 solution – can be used as HDMI-A/D in both directions, ideal for different connection environments.
Industrial-grade design: Hybrid construction made of fibre optic and copper with aramid protection, gold-plated contacts and robust metal connectors.
Future-proof equipment: Supports 8K@60Hz, 4K@120Hz, HDR, eARC, CEC, HDCP and much more – for professional AV and IT applications.

The InLine® HDMI AOC cable with detachable HDMI plugs is the well-designed solution for professional AV installations with the highest demands on

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

resolution, flexibility and signal quality. Thanks to active optical transmission via fibre optics, it ensures stable, loss-free signal transmission – ideal for digital signage systems, conference rooms or home cinema systems.
The hybrid design of fibre optic and copper, combined with aramid protective braiding and gold-plated contacts, ensures maximum robustness, durability and minimal signal interference. The HDMI A and HDMI D connectors can be removed without tools, making installation in tight spaces particularly easy – perfect for cable ducts, cabinets and flush-mounted solutions.
The cable supports HDMI 2.1 features such as 8K at 60 Hz or 4K at 120 Hz, Dynamic HDR, eARC, HDCP 2.3 and much more, making it ideally equipped for future requirements in presentation technology, entertainment, streaming or broadcasting. The 4-in-1 connection options offer maximum flexibility in practice.

HDMI version: HDMI 2.1 (Ultra High Speed HDMI)
Transmission rate: up to 48 Gb/s
Construction: 4 glass fibres + 7 copper conductors, hybrid
Diameter: 4.8 mm
Temperature range: operation 0 °C to +50 °C, storage -20 °C to +70 °C
Connector: HDMI-A (standard), HDMI-D (micro), detachable
Supported functions: HDR, eARC, HDCP, CEC, DDC, EDID, 3D, Dynamic HDR
Directional (source → display)
Contact material: gold-plated
Connector housing: metal, aramid-protected

Techninė specifikacija

Features	
Cable length	50 m
Connector 1	HDMI Type-A/HDMI Type-D
Connector 2	HDMI Type-A/HDMI Type-D
Connector 1 gender	Male
Connector 2 gender	Male
Product colour	Black
Connector contacts plating	Gold
Connector 1 form factor	Straight
Connector 2 form factor	Straight
HDMI version	2.1
3D	Yes
Supported graphics resolutions	3840 x 2160, 7680 x 4320
Dolby technologies	Dolby TrueHD, DTS-HD
Audio Return Channel (ARC)	Yes
HDCP	Yes
Data transfer rate	48 Gbit/s
High Dynamic Range (HDR) supported	Yes
AWG wire size	30
Cable material	Fibre optic/Copper

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Cable jacket material	Nylon/Polyvinyl Chloride (PVC)
Extended display identification data (EDID)	Yes
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Certificates	
Compliance certificates	TÜV mark, CE
Weight & dimensions	
Cable diameter	4.8 mm
Weight	1.35 kg
Packaging data	
Quantity per pack	1 pc(s)
Package type	Box
Other features	
Depth	50000 mm
Height	10 mm
Width	20 mm
Dimensions (WxDxH)	20 x 50000 x 10 mm
Logistics data	
Country of origin	China
Matmenys ir svoris	
Svoris	1,50kg

Gamintojo ir saugos informacija

GAMINTOJAS

InLine

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt