ATEN CL5716M KVM switch Rack mounting Black

Gamintojas: **ATEN** · Modelis: **CL5716M D** · EAN: **4710423775367** · Prekės kodas: **822492**



1 722,89 €

Kaina su PVM

Be PVM: **1 423,88 €**


Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Rack mounting 1U Black
- ✓ Number of computers controlled: 512
- ✓ Keyboard port type: USB, PS/2 Mouse port type: USB, PS/2 Video port type: VGA
- ✓ SXGA 1280 x 1024 pixels
- ✓ Housing material: Metal, Plastic
- ✓ Hot keys
- ✓ LCD Built-in display
- ✓ AC 27.5 W





Aprašymas

The CL5716M Slideaway™ LCD KVM Switch is a control unit that allows access to multiple computers from a single PS/2 or USB KVM (keyboard, video, and mouse) console. A single CL5716M can control up to 16 computers. As many as 31 additional KVM switches can be daisy-chained to the CL5716M, so that up to 512 computers can all be controlled from a single KVM console.

The CL5716 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17" or 19" LED-backlit LCD monitor, and touchpad in a 1U rack-mountable sliding housing.

Features:

-Exclusive LED illumination light - designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions

-Integrated KVM console with 17" or 19" LED-backlit LCD monitor in a Slideaway™ housing

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

-Available with or without Fingerprint Identification Reader**
-Space saving technology - up to two consoles (one bus) control up to 16 computers
-Daisy-chain up to 31 additional units - control up to 512 computers from a single console (With compatible KVM Swithces: ACS1208A, ACS1216A, CS1708A,CS1716A)
-Dual Interface - supports computers and console with PS/2 or USB keyboards and mice
-LCD module USB port allows each computer to access USB peripherals*
-LCD module rotates up to 115 degrees for a more comfortable viewing angle
-Multiplatform support – Windows, Linux, Mac, and Sun
-Supports multimedia USB keyboards for PC, Mac and Sun
-Auto PS/2 and USB interface detection
-Keyboard and mouse emulation (PS/2 and USB) for smooth switching and simultaneous booting of multiple computers even when the console focus is elsewhere
-Supports external USB mouse
-Superior video quality - supports resolutions up to 1280 x 1024 @ 75 Hz
-No software required - convenient computer selection via front panel pushbuttons, hotkeys and multilingual on-screen display (OSD) menus
-Auto-senses station's position on daisy-chained installations; no need for manual dip switch setting; front panel led indicates station's position
-Port names automatically reconfigured when station sequence is changed
-Two level password security - only authorized users can view and control computers
-Supports one administrator and four user accounts with separate profiles
-Auto Scan mode enables continuous monitoring of user-selected computers
-Broadcast support - commands from the keyboard can be broadcast to all available computers on the installation
-Hot pluggable - add or remove computers without having to power down the switch
-Beeper on/off via hotkey and OSD
-Firmware upgrades to all the chained KVM switches at the same time via the daisy-chain cable
-Keyboard Language support: English (US), English (UK), French, German, German (Swiss), Greek, Hungarian, Italian, Japanese, Korean, Russian, Spanish, Swedish and Traditional Chinese

* The USB peripheral function only works with USB cable set connections. It will not work with PS/2 cable set connections.
**The fingerprint reader can be used as an alternate means of logging in to the switch. From 1 to 4 fingers can be scanned for each user and the administrator, with any one of the recorded fingerprints used to log in.

Package Contents
1x CL5716 KVM Switch with standard Rack Mount Kit
2x Custom KVM Cable (VGA, USB; 1.8m/6ft)
1x Custom Console Cable (VGA, USB, PS/2; 27cm/0.88ft)
1x Firmware Upgrade Cable
1x Power Cord (6ft.)
1x Grounding Wire (4ft.)
1x User Manual
1x Quick Start Guide

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	512
Keyboard port type	USB, PS/2
Mouse port type	USB, PS/2
Video port type	VGA

Console ports	USB A, VGA (D-Sub)
VGA (D-Sub) ports quantity	1
Console USB ports quantity	1
USB connector type	USB Type-A
PS/2 ports quantity	0
Performance	
HD type	SXGA
Maximum resolution	1280 x 1024 pixels
Video bandwidth	75 Hz
Scan interval	1,255 s
DDC2B support	Yes
HDCP	Yes
Hot-Plug support	Yes
Daisy chain	Yes
Number of users	5 user(s)
Firmware upgradeable	Yes
Design	
Rack mounting	Yes
Product colour	Black
Rack capacity	1U
Housing material	Metal, Plastic
LED indicators	Yes
Push button	Yes
Hot keys	Yes
Keyboard language	Chinese Traditional, French, German, Greek, Italian, Japanese, Korean, Russian, Spanish, Swedish, Swiss, UK English, US English
Display	
Built-in display	Yes
Display	LCD
Display diagonal	43.2 cm (17")
On Screen Display (OSD)	Yes
Power	
Power source	AC
Input voltage	100-240 V
Input current	1 A

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Power consumption (typical)	27.5 W
System requirements	
Windows operating systems supported	Yes
Linux operating systems supported	Yes
Mac operating systems supported	Yes
Other operating systems supported	Yes
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	480 mm
Depth	642.7 mm
Height	44 mm
Weight	13.6 kg

Dokumentai ir vaizdo įrašai

- Greitos pradžios vadovas
- Gaminio informacijos lapas

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.
Datung Road No.125, Sec. 2, 221 New Taipei City, TW
aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt