

LogiLink CQ6115S networking cable Black 20 m Cat6a S/FTP (S-STP)

Gamintojas: **LOGILINK** · Modelis: **CQ6115S** · EAN: **4052792049848** · Prekės kodas: **822564**



37,90 €

Kaina su PVM

Be PVM: **31,32 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ PUR patch cord for industrial use, IP20
- ✓ CAT.6A Class EA S/FTP 500 MHz 10G conform ISO/IEC 11801 & EN 50173-1
- ✓ Low smoke zero halogen conform IEC60754-2A & IEC 61034
- ✓ Oil Resistant conform EN 60811-2-1
- ✓ UV / weather resistant according to IEC60068-2-5
- ✓ Max. Operating temperature: -40° – +90° C
- ✓ Outer dimension of the cable: 6.2 mm
- ✓ Color: Black (cable and boot)

Aprašymas

Patch cable, PUR, Cat.6A, S/FTP, black, 20 m" from LogiLink Professional

LogiLink 's Cat.6A PUR patch cable is especially suitable for use in industrial environments. The abrasion-resistant sheath made of durable polyurethane (PUR) protects against external influences such as heat, oil, moisture, UV rays and other adverse influences. This high quality cable is suitable for fixed network installation and occasional free movement in dry and damp environments, and outdoors at low mechanical stress. This cable is not waterproof and not suitable for underground!

Techninė specifikacija

Features

Cable length	20 m
Cable standard	Cat6a

Cable shielding	S/FTP (S-STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Male
Jacket material	Polyurethane (PUR)
AWG wire size	27
Data transfer rate	10000 Mbit/s
Frequency	500 MHz
Suitable for outdoor use	Yes
Oil-resistant	Yes
Operational conditions	
Operating temperature (T-T)	-40 - 90 °C
Sustainability	
Doesn't contain	Halogen
Certificates	
Compliance certificates	RoHS
Certification	ISO/IEC 11801, EN50173-1, ANSI/TIA-568-C.2, IEC 60754-2, IEC 61034, EN 60811-2-1, IEC 60754
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	250 mm
Package depth	290 mm
Package weight	650 g
Logistics data	
Harmonized System (HS) code	84733080
Master (outer) case width	400 mm
Master (outer) case length	300 mm
Master (outer) case gross weight	11.3 kg
Master (outer) case height	300 mm
Products per master (outer) case	16 pc(s)

Dokumentai ir vaizdo įrašai

- › [Gaminio lankstinukas](#)
- › [Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

2direct GmbH

Langenstück 5, 58579 Schalksmühle, DE

info@2direct.de

2direct.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

- › [Atitikties deklaracija](#)