DELL PowerEdge R360 server 480 GB Rack (1U) Intel Xeon 6 6315P 2.8 GHz 32 GB DDR5-SDRAM 700 W

Gamintojas: **DELL** · Modelis: **GNYR5** · EAN: **5397184969694** · Prekės kodas: **822592**



4,776.90€

Kaina su PVM

Be PVM: **3,947.85€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No OS
- ✓ Intel Xeon 6 6315P (12MB Cache, 2.8GHz)
- ✓ 32GB DDR5-SDRAM (1 x 32) & 480GB SSD
- ✓ iDRAC9, Enterprise 16G





Aprašymas

Processing performance, GPU support

The 1U, single-socket PowerEdge R360 is an entry-level rack server for customers desiring versatility, affordability, and processing power.

Techninė specifikacija

Processor	
Processor family	Intel Xeon 6
Processor manufacturer	Intel

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Processor model	6315P
Processor frequency	2.8 GHz
Processor boost frequency	5.2 GHz
Performance cores	4
Processor cores	4
Processor cache	12 MB
Number of processors installed	1
Thermal Design Power (TDP)	55 W
System bus rate	16 GT/s
Processor threads	4
Memory types supported by processor	DDR5-SDRAM
Memory clock speeds supported by processor	4800 MHz
Memory	
Internal memory	32 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	128 GB
Buffered memory type	Unregistered (unbuffered)
Memory slots	4x DIMM
ECC	Yes
Memory layout (slots x size)	1 x 32 GB
Memory data transfer rate	5600 MT/s
Storage	
Total storage capacity	480 GB
RAID support	Yes
Optical drive type	No
Number of SSDs installed	1
SSD capacity	480 GB
SSD size	2.5"
Supported SSD sizes	3.5"
Number of SSDs supported	4
Supported RAID controllers	Front PERC H355 Front Load
Hot-Plug support	Yes
Drive writes per day (DWPD)	1
Storage drive adapter included	Yes
Storage drive adapter type	2.5" - 3.5"

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Network	
LAN controller	Broadcom 5720
Ethernet LAN	Yes
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
VGA (D-Sub) ports quantity	1
Serial ports quantity	1
Expansion slots	
PCI Express x8 slots	1
PCI Express x16 slots	1
Design	
Chassis type	Rack (1U)
Product colour	Black
Bezel	Yes
Performance	
Remote administration	iDRAC9, Enterprise 16G
Software	
Operating system installed	No
Compatible operating systems	Canonical® Ubuntu® Server LTS Microsoft® Windows Server® with Hyper-V RedHat® Enterprise Linux SUSE® Linux Enterprise Server VMware® ESXi®
Power	
Redundant power supply (RPS) support	No
Power supply	700 W
Number of main power supplies	1
Power supply input voltage	200 - 240 V
Certificates	
80 PLUS certification	80 PLUS Titanium
Carbon footprint	
Total carbon footprint (kg of CO2e)	1140
Total carbon emissions, standard deviation (kg of CO2e)	943

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Carbon emissions, manufacturing (kg of CO2e)	307.8
Carbon emissions, logistics (kg of CO2e)	102.6
Carbon emissions, energy usage (kg of CO2e)	718.2
Carbon emissions, end-of-life (kg of CO2e)	11.4
PAIA version	PAIA 1.4.0, 2024
Weight & dimensions	
Width	482 mm
Height	42.8 mm
Packaging content	
Packaging content	ReadyRails™ Sliding Rails Without Cable Management Arm,Riser Config 0 Rack Power Cord 2M (C13/C14 10A)
Other features	
Data transfer rate	6 Gbit/s
Bytes per sector	512e
Target workload	Read Intensive (RI)
Matmenys ir svoris	
Matmenys (I × P × A)	52.00cm × 92.00cm × 23.00cm

Dokumentai ir vaizdo įrašai

- User manual
- Declaration of conformity

Gamintojo ir saugos informacija

MANUFACTURER

DELL

EU RESPONSIBLE PERSON

Dell B.V.
Transformatorweg 383, 1014 AK Amsterdam, NL
dell.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- Declaration of conformity