

## Zebra ZD220 etikečių spausdintuvas Perkėlimas terminiu būdu 203 x 203 DPI 102 mm/sec Vielinis

Gamintojas: ZEBRA · Modelis: ZD22042-T1EG00EZ · EAN: 8596375234321 · Prekės kodas: 825447



### 226,90 €

Kaina su PVM

Be PVM: 187,52 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

### Pagrindinės savybės

- ✓ Perkėlimas terminiu būdu
- ✓ 203 x 203 DPI
- ✓ Didžiausias spausdinimo plotis: 10,4 cm Spausdinimo greitis: 102 mm/sec
- ✓ Įdiegti brūkšniniai kodai: CODABAR (NW-7), Code 11, Code 49, Code 93, Code-128 Codabar Library, Code-39 Library, Duomenų matrica, EAN13, EAN8, MaxiCode, PDF417, UPC-A, UPC-E
- ✓ Ryšio technologija: Vielinis
- ✓ USB prievadas
- ✓ 1,1 kg

### Aprašymas

Not all printers are created equally, especially basic models. To reduce costs, value printers are often constructed using less expensive components. Many fail to perform under more demanding duty cycles, create delays and downtime for repairs, and require replacement after only a few years of use. Instead of conserving budget, customers are left with greater expense and hassle.

Zebra does it differently. The ZD220 desktop printer gives you reliable operation and basic features at an affordable price—both at the point of purchase and across the entire lifecycle. Engineered with Zebra quality, it boasts a dual-wall construction for added durability. And, it is ENERGY STAR® qualified to reduce your operational expenses. Built to last for years, the ZD220 provides an outstanding return on your investment.

### Basic Features for Simple Operation

This 4-inch printer produces labels quickly, up to 4" per second, to keep your workflows moving. Increased memory allows you to store more fonts and graphics. A single LED indicator and single button for feed/pause make it easy to operate and identify printer status. Choose from direct thermal or thermal transfer models, and add an optional factory-installed peeler. The ZD220 features a core set of Print DNA software applications, powered

by Link-OS® Basic, to deliver a cost-effective and dependable print experience.

## Backed by Zebra's Worldwide Service and Support

Access support quickly anywhere around the globe through Zebra's trusted network of more than 10,000 partners. Avoid costly repairs and downtime with an affordable service plan that's tailored to the coverage you need for your desktop printer. Zebra's OneCare SV provides the right level of service at the right price. It gives you two years of coverage for normal wear and tear, double the standard warranty coverage, priority turnaround times at the depot and more—all for a tiny fraction of the cost of a single repair.

## Get Printing Quickly

The ZD220 is simple to install and begin printing – right out of the box. USB connectivity allows for universal interoperability. Easily replace legacy printers using ZPL, EPL or non-Zebra command languages. And, media changes are expedited with Zebra's OpenACCESS™ clamshell design. It is ideal for use in transportation and logistics, light manufacturing, retail and healthcare applications to print a variety of tickets, tags, passes, labels and receipts.

## Consistently Exceptional Zebra Certified Supplies

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pretest our own line of thermal printing supplies to ensure consistent, optimized performance in your Zebra printer—and peace of mind for you. For industry-leading quality, service and thermal printing expertise, choose Zebra Certified Supplies.

The ZD220 gives you the quality and reliability you expect from Zebra. And, it helps you conserve costs now, and for years to come. Gain your competitive edge with Zebra.

## Techninė specifikacija

| Spausdinimo greitis            |                          |
|--------------------------------|--------------------------|
| Spausdinimo technologija       | Perkėlimas terminiu būdu |
| Spalva                         | Ne                       |
| Maksimali rezoliucija          | 203 x 203 DPI            |
| Spausdinimo greitis            | 102 mm/sec               |
| Didžiausias spausdinimo plotis | 10,4 cm                  |
| Popieriaus tiekimas            |                          |
| Kaspino plotis                 | 10,9 cm                  |
| Juostos ilgis                  | 74 m                     |
| Maksimalus etiketės plotis     | 10,4 cm                  |
| Maksimalus etiketės ilgis      | 0,991 m                  |
| Maksimalus rulono diametras    | 12,7 cm                  |
| Ruošinio storis                | 0.08 mm                  |
| Ryšys                          |                          |
| Ryšio technologija             | Vielinis                 |
| Ethernet LAN jungtis           | Ne                       |
| USB prievadas                  | Taip                     |

|                                            |                                                                                                                                                                                                                                                     |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Bluetooth                                  | Ne                                                                                                                                                                                                                                                  |
| USB 2.0 portų kiekis                       | 1                                                                                                                                                                                                                                                   |
| <b>Veikimo charakteristikos</b>            |                                                                                                                                                                                                                                                     |
| Puslapio aprašymo kalbos                   | EPL, EPL2, XML, ZPL, ZPL II                                                                                                                                                                                                                         |
| Vidinė atmintis                            | 128 MB                                                                                                                                                                                                                                              |
| Flash atmintis                             | 256 MB                                                                                                                                                                                                                                              |
| Išdiegti brūkšniniai kodai                 | CODABAR (NW-7), Code 11, Code 49, Code 93, Code-128 Codabar Library, Code-39 Library, Duomenų matrica, EAN13, EAN8, MaxiCode, PDF417, UPC-A, UPC-E                                                                                                  |
| Šriftų skaičius                            | 16                                                                                                                                                                                                                                                  |
| Sertifikavimas                             | IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABIS, IN-Metro, BIS, NOM |
| <b>Konstrukcija</b>                        |                                                                                                                                                                                                                                                     |
| Produkto spalva                            | Juoda                                                                                                                                                                                                                                               |
| Ekranas                                    | Ne                                                                                                                                                                                                                                                  |
| Įmontuotas ekranas                         | Ne                                                                                                                                                                                                                                                  |
| <b>Energijos valdymas</b>                  |                                                                                                                                                                                                                                                     |
| AC įėjimo įtampa                           | 100 - 240 V                                                                                                                                                                                                                                         |
| AC įėjimo dažnis                           | 50 - 60 Hz                                                                                                                                                                                                                                          |
| Kištuko tipas                              | C tipas                                                                                                                                                                                                                                             |
| Tinka naudoti šalyje / vietovėje           | Europa, Jungtinė Karalystė                                                                                                                                                                                                                          |
| <b>Aplinkos sąlygos</b>                    |                                                                                                                                                                                                                                                     |
| Darbo santykinės drėgmės diapazonas        | 10 - 90%                                                                                                                                                                                                                                            |
| Sandėliavimo santykinis drėgmės diapazonas | 5 - 95%                                                                                                                                                                                                                                             |
| Darbo temperatūros diapazonas (TT)         | 4,4 - 41 °C                                                                                                                                                                                                                                         |
| Sandėliavimo temperatūros norma (T-T)      | -40 - 60 °C                                                                                                                                                                                                                                         |
| <b>Svoris ir matmenys</b>                  |                                                                                                                                                                                                                                                     |
| Plotis                                     | 197 mm                                                                                                                                                                                                                                              |
| Ilgis                                      | 267 mm                                                                                                                                                                                                                                              |
| Aukštis                                    | 191 mm                                                                                                                                                                                                                                              |
| Svoris                                     | 1,1 kg                                                                                                                                                                                                                                              |
| <b>Pakuotės duomenys</b>                   |                                                                                                                                                                                                                                                     |
| Kiekis pakuotėje                           | 1 vnt                                                                                                                                                                                                                                               |
| <b>Pakuotės turinys</b>                    |                                                                                                                                                                                                                                                     |

|                  |    |
|------------------|----|
| Pridėti kabeliai | AC |
|------------------|----|

|                              |      |
|------------------------------|------|
| Kintamosios srovės adapteris | Taip |
|------------------------------|------|

#### Logistikos duomenys

|                                |          |
|--------------------------------|----------|
| Darniosios sistemos (DS) kodas | 84433210 |
|--------------------------------|----------|

#### Techninė informacija

|                      |             |
|----------------------|-------------|
| Tvarumo sertifikatai | ENERGY STAR |
|----------------------|-------------|

#### Kitos savybės

|                         |                                                                                                                     |
|-------------------------|---------------------------------------------------------------------------------------------------------------------|
| Palaikomi medijos tipai | Roll-fed, fan-fold, die cut, continuous with or without black mark, tag stock, continuous receipt paper, wristbands |
|-------------------------|---------------------------------------------------------------------------------------------------------------------|

|                  |        |
|------------------|--------|
| LED indikatoriai | Būsena |
|------------------|--------|

#### Matmenys ir svoris

|        |        |
|--------|--------|
| Svoris | 3,44kg |
|--------|--------|

### Dokumentai ir vaizdo įrašai

› [Naudojimo instrukcija](#)

### Gamintojo ir saugos informacija

GAMINTOJAS

**Zebra**

ATSAKINGAS ASMUO ES

**Zebra Technologies**

Borupvang 3, Ballerup, DK

[zebra.com](https://zebra.com)

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**

V. Nagevičiaus g. 3, LT-08237 Vilnius

[info@shopro.lt](mailto:info@shopro.lt)