

APC AP4423A automatinis perjungimo jungiklis (ATS)

Gamintojas: **APC** · Modelis: **AP4423A** · EAN: **731304432449** · Prekės kodas: **826087**



1 221,89 €

Kaina su PVM

Be PVM: **1 009,83 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Seamless switching with <10ms transfer time
- ✓ Minimized disruption with field-replaceable NMC
- ✓ Efficient temperature and humidity control
- ✓ Dual-input power cables for faster uptime of critical equipment
- ✓ Connect up to 32 rack ATS and manage them from a single IP address



Aprašymas

Increase availability

An APC Rack Automatic Transfer Switch makes it possible to connect single-powered hardware to two different power sources, in order to increase the availability of this connected hardware and prevent costly downtime. Because an APC Rack ATS uses two input power cords (not included), it can be connected to two different power sources at the same time. By then connecting single-powered hardware to the Rack ATS, this hardware can have access to 2 separate power sources. If one source fails, the Rack ATS immediately switches to the second feed, without the connected hardware being affected.

Easy to use

You can read the status of the APC Rack ATS at a glance via the front panel interface, but you can also manage it remotely thanks to its built-in network management functionality.

Convenience

Because this Rack ATS is equipped with multiple outputs, multiple single-powered devices can be connected to the ATS at the same time, so that all benefit from the security of two feeds.

Safety

The built-in intelligent interface allows this APC rack ATS to monitor both input power sources, detect deviations in voltage or frequency and then take a user-defined action, such as sending an alarm or switching.

Accessories

Connect the APC ATS using 2x the AP9875, (C19-Schuko), AP9876 (C19-IEC309 16A) or AP9877 (C19-C20) and provide the ATS with a temperature and humidity sensor (AP9335TH). You can prevent loose power cords with a retention bracket the AP7769.

Warranty extension

The factory warranty of this APC Rackmount Automatic Transfer Switch is 2 years and can be extended to 3 years using WBEXTWAR1YR-AC-03.

Features

APC Rack Automatic Transfer Switch AP4423A

Input: 230V, input connection type: C20 (2x)

Output 230V, output connection type: C13 (8x) + C19 (1x)

Max power: 3680Watt

Includes: Rack mounting brackets, Serial Communication cable - RJ12 to female DB-9

APC NetShelter Rack Automatic Transfer Switch (ATS) AP4423A is the Fifth-Generation range of high availability switches offering greater control of your IT equipment from Cloud to Edge. With Industry leading reliability, agility, and manageability the APC NetShelter Rack ATS provides redundant power to single-corded equipment loads in the IT rack. AP4423A is single phase 1U Rack ATS with 16A rated current, 230V rated voltage and 3700VA load capacity. It comes with 2 IEC C20 inlet and 8 IEC C13, 1 IEC C19 outlet sockets. This has been upgraded with APC NMC3 and various technical advancements for network port sharing, environmental monitoring and enhanced security. It has 2-years of standard warranty and 5-years of extended warranty for peace of mind and use for years to come. Users can access and configure Rack ATS through secure Web UI, SNMP, CLI and are fully compatible with EcoStruxure IT.

Techninė specifikacija

Energijos valdymas	
Įvesties eksploatacinė įtampa (min.)	207 V
Įvesties eksploatacinė įtampa (maks.)	253 V
AC įėjimo dažnis	50 - 60 Hz
Įvesties srovė	16 A
Išėjimo srovė	16 A
Konstrukcija	
Forma	Stelažas

Rėmo pajėgumas	1U
Produkto spalva	Juoda
Sertifikavimas	CE, cUL listed, EN 55022 class A, FCC part 15 class A, UL listed
Ryšys	
Lizų kiekis	9 AC išvestis(ys / čių)
AC išėjimo tipai	C13 šakotuvus, C19 šakotuvus
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-5 - 45 °C
Sandėliavimo temperatūros norma (T-T)	-25 - 65 °C
Darbo santykinės drėgmės diapazonas	5 - 95%
Techninė informacija	
Bendras anglies pėdsakas (kg of CO2e)	432,5
Svoris ir matmenys	
Plotis	432 mm
Ilgis	236 mm
Aukštis	44 mm
Svoris	3,74 kg
Pakuotės duomenys	
Pakuotės plotis	600 mm
Pakuotės gylis	356 mm
Pakuotės aukštis	114 mm
Paketo svoris	5,51 kg
Matmenys ir svoris	
Matmenys (I × P × A)	60,00cm × 36,00cm × 12,00cm
Svoris	5,24kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Vaizdo įrašas 1](#) youtube.com/watch?v=cCcm_37VLCA
- › [Vaizdo įrašas 2](#) youtube.com/watch?v=iunRiD8YB3s

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 Rueil Malmaison, FR

se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt