

AVer CAM520 Pro3 8 MP Black 1920 x 1080 pixels 60 fps

Gamintojas: **AVERMEDIA** · Modelis: **61U3430000AC** · EAN: **4719552127627** · Prekės kodas: **826198**



1 135,90 €

Kaina su PVM

Be PVM: **938,76 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Full HD 1080p
- ✓ Smart Composition
- ✓ 36X Total Zoom Presents Every Detail
- ✓ SmartFrame
- ✓ WDR Enterprise-Grade Imaging
- ✓ HDMI Enables Dual Display and 3-Way Output



Aprašymas

Professional USB 3.1 Conferencing Camera for Mid-to-Large Rooms

AVer CAM520 Pro3 offers extreme versatility to users by 36X total zoom PTZ camera, upgraded AVer SmartFrame, Preset Framing and Sony WDR Sensor. Moreover, HDMI connection enables dual-display and 3-way output to bring more streaming selections. Especially, the CAM520 Pro3 delivers Smart Composition, this AI function has ability to capture attendee's images quickly with installation-free usage and achieve productive video conference in mid to large meeting rooms.

Mastering The Detail Through 36X* Total Zoom Lens To Boost Up Your Business

Creating the error-less meeting environment with CAM520 Pro3 PTZ lens. Capture a wide shot with a 80° diagonal field of view, focus on presenters, attendee, content on whiteboards or physical object with flexible pan and tilt controls. Powerful handle all the details by a 12X optical lens and 36X* total zoom, CAM520 Pro3 is notably equipped 24X lossless zoom to delivers outstanding image and clarity to remote participants and partners. What's a top choice conference camera for Mid-to-Large room solution!

Delicate Capture The Visual of Attendees Precisely by AVer Smart Composition And Flexibility To Present Various Layouts

The CAM520 Pro3 is proud to be one of very first PTZ cameras in the video conferencing industry provide Smart Composition function which is often presented in high-end models only. Automatically cropping each participant's face or body in great aspect via AI algorithm, Smart Composition is a click-to-play feature with no requirement on any software setting! Smartly integrate head-shot and half-body view, convert from individual visual to group image smoothly, CAM520 Pro3 delivers the great portrait of participants, each one shares equal high-def clarity. Stress-free in meeting setup and get the most productive result.

Conduct More Efficiency And Security Meetings Through The Upgraded AVer SmartFrame

With enhanced SmartFrame, AVer guarantees to elevate your meeting efficiently and safety. It utilizes AI tech to automatically capture and focus on the key individuals in the frame, ensuring that all participant exhibiting any facial disposition or masked facade from an impressive distance of 7 meters!

CAM520 Pro3 provides Preset Framing mode which can follow the presenters efficiently through preset areas. By setting multiple preset viewing areas, camera will automatically shift to as the presenter moves without any manual control!

HDMI Enables Dual Display and 3-Way Output Creating Diverse Display Preferences

Simultaneously presenting in 1080p/60fps via USB 3.1 streaming or RTSP/RTMP H.264 broadcasting and HDMI streaming, CAM520 Pro3 enables a 2nd display for virtual meetings. AVer offers various connection options to create the seamless hybrid meeting experiences for your business.

Enjoy Enterprise-Grade Imaging Without Limitation

CAM520 Pro3 provides lifelike meetings even in sunshine meeting room (ex: in high-contrast backlight environments). By applying the Sony sensor and advanced image-tuning algorithm, CAM520 Pro3 can automatically refining highlights, shadows, and white balance beautifully. Furthermore, with AVer Virtual Streaming technology, the CAM520 Pro3 can be utilized as a camera video source for virtual meetings through a single Ethernet connection, and by the presence of a PoE+ port streamlines the setup process and reduces expenses associated with installation. You deserve to experience enterprise-grade imaging in every meeting.

Techninė specifikacija

Camera

Megapixel (approx.)

8 MP

Optical zoom	12x
Combined zoom	36x
Focal length range	3.9 - 46.8 mm
Field of view (FOV) angle	80.5°
Horizontal field of view	72.8°
Vertical field of view	44.1°
Flip & mirror	Yes
Aperture range (F-F)	1.6 - 2.8
White balance	Auto, Manual
Closest focusing distance	1 m
Wide Dynamic Range (WDR)	Yes
Number of camera presets	10
PTZ control	Yes
Video	
Maximum video resolution	1920 x 1080 pixels
Maximum frame rate	60 fps
HD type	Full HD
Supported video modes	240p, 360p, 480p, 720p, 900p, 1080p
Video formats supported	M-JPEG, NV12, YUV, YUY2
Design	
Product colour	Black
Mounting type	Stand
Tilt angle range	-30 - 90°
Pan range	-170 - 170°
LED indicators	Status
Web-based management	Yes
Country of origin	Taiwan
Ports & interfaces	
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	1
RS-232 ports	1
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Power	
Power source type	AC

AC input frequency	50/60 Hz
AC input voltage	100 - 240 V
DC input voltage	12 V
Input current	2 A
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 80%
Packaging content	
Power supply included	Yes
Remote control included	Yes
Cables included	AC, USB
Warranty card	Yes
Screws included	Yes
Quick start guide	Yes
Mounting kit	Yes
Cable ties included	Yes
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Other operating systems supported	ChromeOS
Minimum processor family	Core i5
Minimum processor speed	3.2 GHz
Minimum processor	Intel Core i5-4460
Minimum RAM	8192 MB
Performance	
Remote control function	Yes
Remote control type	IR
Plug and Play	Yes
Audio	
Built-in microphone	Yes
Built-in speaker(s)	Yes
Network	

Ethernet LAN data rates	10,100,1000 Mbit/s
-------------------------	--------------------

Supported network protocols	RTSP, RTMP
-----------------------------	------------

Logistics data

Products per master (outer) case	2 pc(s)
----------------------------------	---------

Products per pallet	84 pc(s)
---------------------	----------

Harmonized System (HS) code	8517691000
-----------------------------	------------

Weight & dimensions

Remote control dimensions (W x H x D)	200 x 50 x 21 mm
---------------------------------------	------------------

Width	143 mm
-------	--------

Depth	153 mm
-------	--------

Height	182 mm
--------	--------

Weight	1.5 kg
--------	--------

Packaging data

Package width	518 mm
---------------	--------

Package depth	264 mm
---------------	--------

Package height	284 mm
----------------	--------

Package weight	3.8 kg
----------------	--------

Package type	Box
--------------	-----

Matmenys ir svoris

Svoris	3,80kg
--------	--------

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

› [Vaizdo įrašas 1](#) youtube.com/watch?v=gqlzl7tzMA4

› [Vaizdo įrašas 2](#) youtube.com/watch?v=oh-ko3_C2yE

Gamintojo ir saugos informacija

GAMINTOJAS

AVer Information Inc.

Da-An Rd., Tucheng Dist. 157, 23642 New Taipei
City, TW
aver.com

ATSAKINGAS ASMUO ES

AVer Information Europe B.V.

Westblaak 134, 3012 KM Rotterdam, NL
aver.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt