

StarTech.com 5G2A1SGBB-USB-C-HUB knyginių kompiuterių dokas / jungčių replikatorius Vielinis USB 3.2 Gen 1 (3.1 Gen 1) Type-C Pilka

Gamintojas: **STARTECH** · Modelis: **5G2A1SGBB-USB-C-HUB** · EAN: **065030899284** · Prekės kodas: **826577**



121,90 €

Kaina su PVM

Be PVM: **100,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ Priimančioji sąsaja: USB 3.2 Gen 1 (3.1 Gen 1) Type-C
- ✓ „USB Power Delivery“
- ✓ Ethernet LAN jungtis 10,100,1000,2000 Mbit/ai Wake-on-LAN pasirengimas
- ✓ Auto MDI/MDI-X Pilnai abipusis (duplex) Jumbo Frames palaikymas



Aprašymas

Add a unique combination of serial, USB and Ethernet ports to your laptop or PC

This USB Type-C Hub with RS-232 Serial, Gigabit Ethernet, and 100W USB-C Power Delivery Pass-Through adds two USB 3.2 Gen 1 (5Gbps) Type-A ports to a USB enabled computer. The attached 2ft (60cm) USB-C host cable includes a tethered USB-C to USB-A adapter that enables the USB Hub to easily connect to both USB-A and USB-C host computers.

RS-232 Serial

The USB Hub adds an RS-232 serial DB/DE-9M (male) connector to a desktop or laptop. The USB to RS-232 adapter features COM retention, which automatically reassigns the COM port value if the cable is disconnected and reconnected, or if the system is rebooted.

Gigabit Ethernet

The USB hub features a Gigabit Ethernet Network Interface Controller (NIC). The Ethernet adapter is compatible with the IEEE 802.3u/ab standards and supports Wake-on-LAN (WoL), Jumbo Frames, and V-LAN Tagging. The network adapter enhances laptop network reliability, security, and performance, by utilizing wired 10/100/1000Mbps Ethernet.

USB Power Delivery Pass-Through

This USB hub features 100W USB Power Delivery 3.0 pass-through (85W laptop charging). Connect a power source to the USB-C PD pass-through port to power the connected host device. PD 3.0 features Fast Role Swap (FRS) to prevent USB data disruption when switching power sources (USB-C power adapter to bus power).

The USB hub features Overcurrent Protection (OCP) for added protection to the USB hub and any connected devices. OCP prevents faulty USB peripherals from drawing more power than is safely allocated.

Plug and Play

This device is compatible with most major operating systems, including Windows, macOS, and Linux. The Hub is automatically detected, configured, and installed upon connection to a host computer.

Enhance Productivity and Device Management with the StarTech.com Connectivity Tools Application

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

- USB Event Monitoring Utility: Track and log connected USB devices.
- MAC Address Pass-Through Utility: Improve network security.
- Wi-Fi Auto Switch Utility: Enable users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/connectivity-tools

Techninė specifikacija

Ports & interfaces	
Connectivity technology	Wired
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 2.0 ports quantity	0
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2

HDMI ports quantity	0
Microphone in	No
Headphone outputs	0
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	100 W
Serial ports quantity	1
DC-in jack	No
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000,2000 Mbit/s
Wake-on-LAN ready	Yes
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Jumbo frames support	Yes
Jumbo frames	9000
Flow control support	Yes
Auto MDI/MDI-X	Yes
Full duplex	Yes
VLAN tagging	Yes
Performance	
Product colour	Grey
Card reader integrated	No
Colour name	Space Gray
Data transfer rate	5 Gbit/s
LED indicators	Yes
UASP support	Yes
Power	
Power consumption (max)	15 W
Wireless charging	No
Software	

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 Enterprise, Windows 11 Enterprise x64, Windows 11 Home, Windows 11 Pro, Windows 11 x64, Windows 2000, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma
Linux operating systems supported	Yes
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022
Other operating systems supported	Windows XP Embedded
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	128 mm
Depth	55 mm
Height	19 mm
Weight	105 g
Packaging data	
Package width	149 mm
Package depth	216 mm
Package height	36 mm
Package weight	110 g
Packaging content	
Quick start guide	Yes

Interface adapters included	USB Type-A male - USB Type-C female
Technical details	
Compliance certificates	CE, RoHS
Logistics data	
Products per master (outer) case	40 pc(s)
Master (outer) case width	370 mm
Master (outer) case length	445 mm
Master (outer) case height	315 mm
Other features	
Chipset	VIA - VL817-Q7, VIA - VL103-Q4, ASIX - AX88179A, FTDI - FT232RL
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Svoris	0,15kg

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS	ATSAKINGAS ASMUO ES	PLATINTOJAS
StarTech.com Ltd.	StarTech.com Limited	MB KOMPIUTERIŲ GURU
Artisans Crescent 45, N5V 5E9 Ontario, London, CA	Laarderhoogtweg 25, 1101 EB Amsterdam, NL	V. Nagevičiaus g. 3, LT-08237 Vilnius
startech.com	startech.com	info@shopro.lt