InLine 95477 low/medium/high voltage cable Medium voltage cable

Gamintojas: **INLINE** · Modelis: **95477** · EAN: **4043718342785** · Prekės kodas: **827040**



20,90 €

Kaina su PVM

Be PVM: **17,27 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ High nominal and working voltage: with a nominal voltage of 1.0/1.0 kV AC and an operating voltage of 1.5 kV DC in accordance with EN 50618, the cable is ideally designed for the requirements of modern solar systems.
- ✓ Robust construction: With an external cable diameter of 5.5 mm and a nominal wall thickness of the insulation of 0.7 mm and the coating of 0.8 mm, the cable is robust and durable.
- ✓ Conductor cross-section: 4 mm², fine-wired
- ✓ Conductor material: copper, tinned
- ✓ DC line resistance: 5.0 9 Ohm/km
- ✓ Voltage test on cable: AC 6.5 kV, DC 15 kV
- ✓ Current carrying capacity: Tested according to EN 50618
- ✓ Ozone and weather resistance, UV resistance: Tested according to EN 60811 / 50618
- ✓ Flame resistance: complies with EN 60332-1-2, LS0H (Low Smoke Zero Halogen)
- ✓ Insulation: halogen-free, low-smoking, cross-linked polyolefin (XLPO)

Aprašymas

The solar cable H1Z2Z2-K, 4mm², incl. solar plug in a set of two (black/red) has been specially developed for wiring photovoltaic systems and offers maximum reliability and durability. With its robust construction and outstanding technical properties, it ensures that the PV system will operate efficiently and safely for years to come.The H1Z2Z2-K 4mm² solar cable is the optimal choice for safe and efficient cabling of your photovoltaic system. With its high-quality construction and comprehensive protective features, it ensures reliable power transmission and helps to maximise the energy efficiency of your system.

Note on the wire cross-section:

The required wire cross-section depends on the current and the distance or cable length. If in doubt, please consult a solar technician to find out which wire cross-section you need.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Techninė specifikacija

Features	
Product type	Medium voltage cable
Product colour	Black, Red
Insulation thickness	0.7 mm
Conductor material	Tinned copper
Conductor cross section	4 mm²
Fire-resistant	Yes
Power	
Operating voltage (max)	1500 V
Logistics data	
Country of origin	Taiwan
Technical details	
Doesn't contain	Halogen
Package volume	500 cm³
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Length	0.75 m
Diameter	5.5 mm
Weight	141 g
Packaging data	
Package width	190 mm
Package depth	250 mm
Package height	20 mm
Package weight	154 g
Matmenys ir svoris	
Svoris	0,15kg

Gamintojo ir saugos informacija

GAMINTOJAS

Intos Electronic AG
Siemensstraße 11, D-35394 Gießen, DE
service@inline-info.com
intos.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.