

Cudy AC1200 86mm Wall-Plate Wi-Fi Access Point

Gamintojas: **CUDY** · Modelis: **AP1300E WALL** · EAN: **6971690793883** · Prekės kodas: **827684**



65,90 €

Kaina su PVM

Be PVM: **54,46 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4-Stream Dual-Band Wi-Fi 5
- ✓ 867 Mbps + 300 Mbps Wi-Fi
- ✓ 1x GbE PoE In, 1x GbE
- ✓ 802.3at/af, Passive PoE
- ✓ Watchdog, Schedule Reboot
- ✓ Covers 50 m² (540 ft²)
- ✓ 40 Connected Devices
- ✓ Multi-AP Management



Aprašymas

AC1200 Dual-Band

Fast, Reliable Wi-Fi in Every Room

Dual-band WiFi allows newer devices to stream on the less congested 5 GHz band, ensuring smooth video calls, 4K playback and gaming, while IoT and legacy devices stay reliably connected on 2.4 GHz band.

Built for Modern Spaces

Effortlessly integrates into any Interior

With its sleek, minimalist design, the device fits naturally into any room without disrupting your décor, delivering high-performance Wi-Fi while staying visually unobtrusive.

Efficient Heat Dissipation

Equipped with multiple cooling vents, the AP1300E Wall prevents overheating to maintain proper temperature and stable performance, even under heavy workloads.

Seamless Experiences in Multiple Scenarios

Apartment

Enjoy dedicated, high-speed Wi-Fi in every unit with zero signal overlap. Its sleek, low-profile design blends seamlessly into modern interiors.

Dormitory

Provide secure, high-speed access for each user without cross-room interference or weak zones. Designed to handle multiple users across closely packed rooms.

Hotel

Covers up to 50 m² (540 ft²), delivering fast, secure Wi-Fi in every guest room. Sleek design and easy integration with VoIP, IPTV, and other devices.

Office

Ensure reliable connectivity for each workspace or meeting room. Perfect for flexible, room-based deployments in modern offices.

Gigabit Wired Connection

Equipped with two Gigabit Ethernet ports—including one that supports PoE IN, AP1300 Wall allows your VoIP phones, IPTV, or other wired devices to stay reliably connected to the network for smooth calls and streaming.

Effortless Wall-Mount Installation

Fits perfectly in a standard electrical box. It simplifies setup by eliminating the need for complex wiring or additional equipment.

Centralized AP Management

Easily manage up to 200 access points with Cudy AP Controller Model:C200P , enabling efficient batch configuration and firmware updates through a unified interface.

Techninė specifikacija

Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	1167 Mbit/s
Maximum data transfer rate (2.4 GHz)	300 Mbit/s

Maximum data transfer rate (5 GHz)	867 Mbit/s
Ethernet LAN data rates	10,100,1000 Mbit/s
Number of simultaneously connected devices (max)	128
Networking standards	IEEE 802.3, IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11v, IEEE 802.11k
Number of users	40 user(s)
Bluetooth	No
MIMO	Yes
MIMO type	Multi User MIMO
Spread spectrum method	OFDMA
VLAN support	Yes
Quality of Service (QoS) support	Yes
Maximum outdoor range	80 m
Security	
Security algorithms	WPA, WPA2, WPA3
Parental control	Yes
IGMP snooping	Yes
Protocols	
DHCP server	Yes
Management features	
Syslog	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	0
WAN connection	Ethernet (RJ-45)
Power	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
Power consumption (typical)	10 W
Power consumption (max)	4 W
Design	
Placement	Wall
Product colour	White
Reset button	Yes

Internal	No
Antenna	
Antenna type	Internal
Antenna direction type	Omni-directional
Antennas quantity	4
Performance	
Flash memory	16 MB
Technical details	
Products per shipping (inner) case	50 pc(s)
Weight & dimensions	
Width	86 mm
Depth	86 mm
Height	43 mm
Weight	145 g
Packaging data	
Package width	91 mm
Package depth	57 mm
Package height	89 mm
Package weight	220.1 g
Packaging content	
AC adapter included	No
PoE adapter included	No
Mounting kit	Yes
Quick start guide	Yes
Bundled software	Cudy Software
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Logistics data	
Warranty period	1 year(s)
Country of origin	China
Matmenys ir svoris	

Svoris

0,20kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Cudy

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

- › [Atitikties deklaracija](#)