

StarTech.com ST4300USBM sąsajos šakotuvas USB 3.2 Gen 1 (3.1 Gen 1) Type-B 5000 Mbit/ai Juoda

Gamintojas: **STARTECH** · Modelis: **ST4300USBM** · EAN: **065030841603** · Prekės kodas: **827954**



151,90 €

Kaina su PVM

Be PVM: **125,54 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Priimančioji sąsaja: USB 3.2 Gen 1 (3.1 Gen 1) Type-B
- ✓ Lizdo sąsajos: USB 3.2 Gen 1 (3.1 Gen 1) Type-A
- ✓ Portų kiekis: 4
- ✓ 5000 Mbit/ai
- ✓ Juoda Plienas



Aprašymas

Industrial-grade | 8kV Air | 4kV Contact | Metal | Mountable | 5 Gbps

This TAA compliant 4-port industrial USB 3.2 Gen 1 hub gives you the scalability you need in harsh industrial environments, product and repair labs, conference rooms or office workstations. With its rugged industrial grade metal housing, it is designed to meet the advanced requirements of connecting a high number of devices in factories and office environments.

Perfect for Harsh Environments

This industrial USB hub delivers reliable performance with a metal, heavy-duty housing. It supports wide-range 7-24V DC terminal block input, giving you the flexibility to power the hub as required, based on your own power input capabilities.

Perfect for factory environments, the rugged hub also supports a wide operating temperature range (0°C to 55°C) and offers ESD protection to each USB port, which can help prevent damage to your connected devices.

Connect & Charge More USB Devices

Designed for a high volume of connections, this robust USB 3.2 Gen 1 hub offers four connection ports, for connecting more USB devices and peripherals.

The hub also supports USB battery charging specification 1.2, delivering up to 2.4A on any port to a maximum of 20W total, so you can charge your mobile devices faster than traditional USB ports allow.

Locate the Hub Where You Need It Most

With versatile installation options, you can install the hub where it's best suited for your environment. With built-in mounting brackets and an included 1.8-meter USB host cable, you can securely mount the USB 3.2 Gen 1 hub to most surfaces such as a wall, under a desk or rack.

StarTech.com offers an external power adapter, ITB20D3250, sold separately. The universal DC power adapter can be used as an alternative, back up or replacement power supply for StarTech.com's line of industrial USB hubs.

Works with Older USB Devices

The rugged USB hub supports the full 5 Gbps bandwidth of USB 3.2 Gen 1 and is backward compatible with previous USB devices. You can connect your legacy peripherals alongside your newer USB 3.2 Gen 1 devices without any disruptions.

The ST4300USBM is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Techninė specifikacija

Ryšys	
Portų kiekis	4
Priimančioji sąsaja	USB 3.2 Gen 1 (3.1 Gen 1) Type-B
Lizdo sąsajos	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	4
Gnybtų kaladėlės prievadas	Taip
DC įėjimo lizdas	Taip
Savybės	
Duomenų perdavimo sparta	5000 Mbit/ai
Produkto spalva	Juoda
Korpuso medžiaga	Plienas

LED indikatoriai	Energija, USB
Pakeitimas neišjungus	Taip
„Plug and Play“ funkcija	Taip
Sertifikavimas	RoHS, CE, FCC, TAA, REACH
Energijos valdymas	
Energijos suvartojimas	36 W
Išėjimo įtampa	12 V
Išėjimo srovė	3 A
Kištuko tipas	M tipas
Sistemos reikalavimai	
Palaikomos „Windows“ operacinės sistemos	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Palaikomos MAC operacinės sistemos	„Mac OS X 10.4 Tiger“, „Mac OS X 10.5 Leopard“, Mac OS X 10.6 Snow Leopard
Svoris ir matmenys	
Plotis	59,6 mm
Ilgis	152 mm
Aukštis	24 mm
Svoris	301 g
Pakuotės duomenys	
Kiekis pakuotėje	1 vnt
Pakuotės plotis	295 mm
Pakuotės gylis	190 mm
Pakuotės aukštis	72 mm
Paketo svoris	1,2 kg
Pakuotės turinys	
Kintamosios srovės adapteris	Taip
Pridedamos maitinimo šakutės tipai	AU, EU, NA, UK
Pridėti kabeliai	USB
Instrukcija	Taip
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 55 °C

Sandėliavimo temperatūros norma (T-T)	-20 - 85 °C
Darbo santykinės drėgmės diapazonas	5 - 95%
Veikimo charakteristikos	
Vidutinis laikas tarp trikčių (MTBF)	245881 h
Logistikos duomenys	
Pagrindinės (išorinės) dėžės plotis	555 mm
Pagrindinės (išorinės) dėžės ilgis	402 mm
Pagrindinės (išorinės) dėžės aukštis	343 mm
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	14 vnt
Darniosios sistemos (DS) kodas	84719000
Kitos savybės	
Lustų rinkinys	VIA/VLI - VL811+
Matmenys ir svoris	
Matmenys (I × P × A)	30,00cm × 19,00cm × 7,00cm
Svoris	1,18kg

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt