

Intellinet Cat6a 10G Shielded Toolless RJ45 Modular Field Termination Plug, For Easy and Quick High-quality Cable Assembly in the Field, STP, for Solid & Stranded Wire, Gold-plated Contacts, Metal Housing

Gamintojas: **INTELLINET** · Modelis: **790796** · EAN: **766623790796** · Prekės kodas: **832398**



13,90 €

Kaina su PVM

Be PVM: **11,49 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ For easy, time-saving and tool-free high-performance network cable assembly in the field
- ✓ Cat6a STP 360° shielded premium RJ45 plug for 10G and PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- ✓ 50 micro-inch gold-plated contacts
- ✓ Supports solid wire with AWG 26/1 to 23/1 and stranded wire with AWG 27/7 to 23/7
- ✓ Adjustable strain relief
- ✓ Compliant with ANSI/TIA-568-D, ISO/IEC 11801 and IEC 60603-7-51
- ✓ Standard 8P8C design, compatible with all network RJ45 connections
- ✓ Compatible and color-coded with T568A and T568B
- ✓ Fits round cable



Aprašymas

Field-installable Cat6a STP RJ45 Modular Plug for easy, fast and tool-free high-quality cable assembly

The Cat6a 10G Shielded Toolless RJ45 Modular Field Termination Plug from Intellinet Network Solutions is designed for time-saving, high-quality cable terminations, even when out in the field for such devices as security cameras, industrial electronics and more. Without any special tools, the cable can be assembled within two minutes. This plug is suitable for both stranded and solid conductor cables for high-performance network applications up to 10GBase-T with PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE. For maximum signal integrity, it is equipped with gold-plated contacts and 360° STP shielding.

Techninė specifikacija

Features	
Connector(s)	RJ45
Product colour	Stainless steel
Connector gender	Male
Connector form factor	Straight
Cable standard	Cat6a
Cable shielding	U/FTP (STP)
Connector contacts plating	Gold
Contact resistance	20 mΩ
Current	1.5 A
Certification	CE RoHS FCC ISO/IEC 11801 IEC 60603-7-51 Cat5 (ANSI/TIA/EIA-568-D) Cat5e (TIA/EIA-568-D) Cat6 (ANSI/TIA-568-D) Cat6a (ANSI/TIA-568-D)
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-40 - 70 °C
Weight & dimensions	
Weight	20 g
Width	15 mm
Depth	41 mm
Height	18 mm
Matmenys ir svoris	
Svoris	0,02kg

Dokumentai ir vaizdo įrašai

› [Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

intellinetnetwork.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt