

# Manhattan Long Range CCD Handheld Barcode Scanner, USB, 500mm Scan Depth, Cable 1.5m, Max Ambient Light 30,000 lux (sunlight), Black, Three Year Warranty

Gamintojas: **MANHATTAN** · Modelis: **460835** · EAN: **766623460835** · Prekės kodas: **834405**



## 96,90 €

Kaina su PVM

Be PVM: **80,08 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Helps speed data entry, reduce errors and improve efficiency – ideal for retail transactions and automated processes
- ✓ Keyboard Wedge Decoder displays data as if directly entered from keyboard
- ✓ Wide scan field provides quick, accurate reads with up to 500 scans per second up to 50 cm (20 in.) away
- ✓ Detects many popular symbologies including UPC, EAN and GS1 DataBar
- ✓ Switchable interface integrates with most PCs
- ✓ Easy to install and use without software or special training
- ✓ Three-Year Warranty



## Aprašymas

## Improve speed, accuracy and productivity\_x000D\_

Manhattan CCD Long-Range Contact Barcode Scanners deliver high-quality scanning for a wide range of data collection functions to help improve routine transactions, automate paper-based processes and increase productivity. The CCD (charge-coupled device) scan engine features no moving parts for years of reliable service reading popular barcodes, including UPC, EAN and GS1 DataBar. Easy to implement and simple to use, a built-in keyboard wedge decoder sends scanned data to an active application where it appears as if it was manually typed or directly keyed into the computer. Its versatile switchable USB or PS/2 cable interface integrates with most PCs without an external power supply. With a scan rate of 500 scans per second and an accurate read range of up to 50 cm (20 in.), this model offers an effective and efficient, all-purpose daily scanning solution for point-of-sale, shipping, warehousing, office and industrial applications to minimize manual data entry, speed transactions and reduce errors.

Techninė specifikacija

| Scanning                                 |                                                                                                                          |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Type                                     | Handheld bar code reader                                                                                                 |
| Scanner type                             | 1D                                                                                                                       |
| Sensor type                              | CCD                                                                                                                      |
| Linear (1D) barcodes supported           | Codabar, Code 11, Code 128, Code 32, Code 39, Code 93, Industrial 2 of 5, Interleaved 2 of 5, JAN, MSI, Plessey, Telepen |
| 2D (matrix & stacked) barcodes supported | Not supported                                                                                                            |
| Scanner resolution                       | 0.1 mm                                                                                                                   |
| Read rate (max)                          | 500 reads/s                                                                                                              |
| Light levels (direct sunlight)           | 0 - 30000 lx                                                                                                             |
| Ports & interfaces                       |                                                                                                                          |
| Connectivity technology                  | Wired                                                                                                                    |
| Standard interfaces                      | USB                                                                                                                      |
| Cable length                             | 1.5 m                                                                                                                    |
| Performance                              |                                                                                                                          |
| Product colour                           | Black                                                                                                                    |
| Housing material                         | Acrylonitrile butadiene styrene (ABS), Rubber                                                                            |
| Certification                            | FCC CE                                                                                                                   |
| Power                                    |                                                                                                                          |
| Power source type                        | USB                                                                                                                      |
| Input voltage                            | 5 V                                                                                                                      |
| Power consumption                        | 150 mA                                                                                                                   |
| Weight & dimensions                      |                                                                                                                          |
| Weight                                   | 440 g                                                                                                                    |
| Width                                    | 90 mm                                                                                                                    |
| Depth                                    | 193 mm                                                                                                                   |
| Height                                   | 72 mm                                                                                                                    |

## Operational conditions

|                                   |             |
|-----------------------------------|-------------|
| Operating temperature (T-T)       | 0 - 50 °C   |
| Storage temperature (T-T)         | -20 - 70 °C |
| Operating relative humidity (H-H) | 20 - 95%    |

## Technical details

|                         |                                             |
|-------------------------|---------------------------------------------|
| Compliance certificates | CE, Federal Communications Commission (FCC) |
|-------------------------|---------------------------------------------|

## Logistics data

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 84716070 |
|-----------------------------|----------|

## Matmenys ir svoris

|        |        |
|--------|--------|
| Svoris | 0,44kg |
|--------|--------|

## Dokumentai ir vaizdo įrašai

[> Gaminio lankstinukas](#)

## Gamintojo ir saugos informacija

GAMINTOJAS

Manhattan

ATSAKINGAS ASMUO ES

**IC Intracom Vertriebs GmbH**  
Löhbacher Str. 7, D-58553 Halver, DE  
[intellinetnetwork.eu](http://intellinetnetwork.eu)

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**  
V. Nagevičiaus g. 3, LT-08237 Vilnius  
[info@shopro.lt](mailto:info@shopro.lt)