

Epson TM-T88VII (112A0) 180 x 180 DPI Wired & Wireless Thermal POS printer

Gamintojas: **EPSON** · Modelis: **C31CJ57112A0** · EAN: **8715946697109** · Prekės kodas: **835797**



411,90 €

Kaina su PVM

Be PVM: **340,41 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Reliable hardware Backed by our tried and trusted build quality
- ✓ High performance Max print speed 500mm/s
- ✓ Connectivity and interface options USB, Ethernet, USB Host as standard; serial, PoweredUSB, options
- ✓ Backwards compatible Fully compatible with the existing T88V and T88VI software
- ✓ Reduced environmental impacts Low power consumption, support for Phenol-free paper



Aprašymas

High-speed receipt printer

Market-leading¹, high-performance and eco-conscious receipt printers, backed by proven reliability

The TM-T88VII is our new high-performance receipt printer range. It features a range of design, connectivity and usability improvements and enhancements to improve the user experience.

Reliable and high-performance

Avoid downtime by choosing proven, reliable hardware from the market leader¹. Fast print speeds of 500mm/s and high-quality, printed legible receipts will ensure happy customers.

Backwards compatible

The TM-T88VII is fully compatible with the existing T88V and T88VI software so there are no expensive costs associated with changing business infrastructure. The printer also has same footprint as previous models, meaning no additional costs of having to change the counters/tills.

Eco-conscious

The TM-T88VII demonstrates reduced environmental impacts, with lower noise level, lower power consumption and smaller, more efficient power supply. The printer is now compatible with more eco-friendly, Phenol-free paper.

Reliable hardware Backed by our tried and trusted build quality

High performance Max print speed 500mm/s

Connectivity and interface options USB, Ethernet, USB Host as standard; serial, PoweredUSB, options

Backwards compatible Fully compatible with the existing T88V and T88VI software

Reduced environmental impacts Low power consumption, support for Phenol-free paper

Techninė specifikacija

Printing	
Print technology	Thermal
Type	POS printer
Maximum resolution	180 x 180 DPI
Print speed	500 mm/sec
Character size	1.41 x 3.39 mm
Printing characters	Text, Graphic, Barcode, 2D barcode
Character sets	ANK
Paper handling	
Printing media thickness	48 - 80 µm
Maximum roll diameter	8.3 cm
Supported paper width	80 mm
Media thickness	48 - 80 mm
Ports & interfaces	
Connectivity technology	Wired & Wireless
USB port	Yes

Serial interface	Yes
USB connector	USB Type-A / USB Type-B
Serial interface type	RS-232
Near Field Communication (NFC)	Yes
Optional connectivity	Wireless LAN
Network	
Ethernet LAN	Yes
Features	
Sound pressure level (printing)	52 dB
Sound pressure level (standby)	52 dB
Mean time between failures (MTBF)	360000 h
Autocutter durability	3 million cuts
Paper save function	Yes
Print head life	200 km
Country of origin	Philippines
Mounting position	Horizontal/Vertical
Wall mountable	Yes
Built-in sensors details	Paper End Sensor, Paper Near End Sensor, Cover Open Sensor, Receipt paper sensor
Certification	CE
Design	
Product colour	Black
Power	
Power consumption (printing)	27.9 W
AC input voltage	24 V
Power consumption	27900 mA
Power consumption (standby)	1400 mA
Power consumption (standby)	1.4 W
Operational conditions	
Operating temperature (T-T)	5 - 45 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
System requirements	
Pre-installed software	Server Direct Print, ePOS-Device, ePOS-Display, ePOS-Print
Weight & dimensions	

Width	145 mm
Depth	195 mm
Height	148 mm
Weight	1.7 kg
Packaging data	
Quantity per pack	1 pc(s)
Package width	195 mm
Package depth	235 mm
Package height	260 mm
Package weight	2.7 kg
Print technology	
Column capacity	42/56
Logistics data	
Pallet weight (UK)	0 g
Harmonized System (HS) code	84433210
Products per pallet	112 pc(s)
Pallet gross weight	0 g
Products per pallet (UK)	168 pc(s)
Other features	
Buffer size	4 KB
Mean cycles between failures (MCBF)	70000000
Technical details	
Changeable interface	Y
Lifetime	20000000 lines
Matmenys ir svoris	
Svoris	2,70kg

Gamintojo ir saugos informacija

GAMINTOJAS

Seiko Epson

Owa, Suwa 3-3-5, Nagano, JP

corporate.epson

ATSAKINGAS ASMUO ES

Epson Deutschland

Schiessstraße 49, D-40549 Düsseldorf, DE

epson.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt