

Manhattan Mini DisplayPort 1.2a to DVI-D 24+1 Cable, 1080p@60Hz, 1.8m, Male to Male, Compatible with DVD-D, Black, Lifetime Warranty

Gamintojas: **MANHATTAN** · Modelis: **152150** · EAN: **766623152150** · Prekės kodas: **838026**



17,90 €

Kaina su PVM

Be PVM: **14,79 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Mini DisplayPort 1.2a male to DVI-D 24+1 male gold-plated connections
- ✓ Connect to monitor, projector or other display with Extended- or Mirrored-Display modes
- ✓ Converts from Mini DisplayPort (DP, DP++) source to DVI-D monitor, projector or other display
- ✓ Lifetime Warranty
- ✓ Supports existing HD (720p, 1080i and 1080p@60Hz), enhanced (480p) and standard (NTSC or PAL) video formats



Aprašymas

Superior connections for quality digital video performance._x000D_

Manhattan Mini DisplayPort 1.2a to DVI Cables help deliver the brightest, most accurate colours and sharpest detail when connecting high-definition monitors, LCD and plasma displays, digital projectors and other DVI- or DP-equipped display devices. Manhattan Mini DisplayPort 1.2a to DVI Cables are engineered and constructed of quality materials to deliver dependable signals in digital video applications. Full foil and braided shielding, moulded boots with strain relief, protective PVC jackets and gold-plated connections help provide maximum conductivity and clear, crisp signal

transmissions with reduced distortion.

Techninė specifikacija

Features	
Cable length	1.8 m
Connector 1	Mini DisplayPort
Connector 2	DVI-D
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
HDCP	Yes
DisplayPort version	1.2a
Dual Link DVI	Yes
Supported video modes	1080p
Data transfer rate	2.7 Gbit/s
Maximum refresh rate	60 Hz
Product colour	Black
Magnetically shielded	Yes
Jacket material	Polyvinyl chloride (PVC)
AWG wire size	28
Converter type	Passive video converter
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-10 - 80 °C
Operating relative humidity (H-H)	0 - 96%
Certificates	
Certification	UL 20276
Weight & dimensions	
Weight	190 g
Packaging data	
Package type	Polybag
Packaging content	

Quantity per pack 1 pc(s)

Logistics data

Harmonized System (HS) code 84733080

Matmenys ir svoris

Svoris 0,19kg

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Manhattan

ATSAKINGAS ASMUO ES

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

intellinetnetwork.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt