

Zebra RS6100 Nešiojamas brūkšninių kodų skaitytuvas 2D LED Pilka, Geltona

Gamintojas: **ZEBRA** · Modelis: **RS61B0-KESSXWR** · EAN: **5715063153284** · Prekės kodas: **839257**



1 058,90 €

Kaina su PVM

Be PVM: **875,12 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Nešiojamas brūkšninių kodų skaitytuvas Pilka, Geltona
- ✓ Skenerio tipas: 2D Jutiklio tipas: LED
- ✓ Codabar, Code 11, Code 128, Code 39, Code 93, GS1 DataBar, MSI Aztec Code, Sudėtiniai kodai, Duomenų matrica, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
- ✓ 2688 x 1520 pikseliai
- ✓ Bevielis
- ✓ Mažo nuotolio radijo ryšys (NFC)
- ✓ Maitinimo šaltinio tipas: Baterija Ličio-jonų (Li-Ion) 735 mAh

Aprašymas

Maximum versatility, power and performance

Introducing Zebra's most powerful and versatile wearable scanner — the RS6100. This small and practically weightless wearable scanner is less than half the size and weight of its predecessor, the RS6000. An advanced multi-focus scan engine captures 1D and 2D barcodes at close range and on the top shelf of a rack 40 ft./12.2 m away, regardless of condition — scratched, dirty, poorly printed, under shrinkwrap and more. With five interchangeable wearing options, there's a style that will maximize comfort for every user. Use it anywhere — from warehouse aisles, freezers and coolers to the seat of a fork truck and out on the dock in rain, snow, blazing summer heat or subzero winter cold. The RS6100 is always in service with its removable battery — no downtime needed for charging, just swap in a fully charged battery. Choose cordless freedom with two battery options or corded battery-free operation. And since the RS6100 and RS5100 share common trigger assemblies, batteries and mounts, upgrading from the RS5100 is easy and cost-effective.

Power the RS6100 via a corded adapter that connects to select Zebra mobile devices, including wearable and handheld computers.

Five interchangeable wearing styles

Five different mounts provide users with the freedom to choose the wearing style they prefer to maximize comfort, simplify task execution — and increase job satisfaction. All mounting accessories are interchangeable — swap at any time to maximize user comfort for scan-intensive tasks. The Enterprise Hand Mount accessory gives every hand a snug, comfortable and secure custom fit with a range of sizes for right and left hands — and users can adjust the scanner position on the hand to achieve the perfect balance and optimal scan angle for the ultimate in comfort and user productivity. For workers who prefer to wear the scanner on one finger, there are two single finger mount options — single and double triggers. The single trigger can be removed and rotated, allowing users to easily switch between left and right finger mounting. The double trigger enables workers to change hands on the fly — without removing the trigger. All triggers support continuous scanning mode. And the optional vibrating trigger signals an error or exception, allowing users to take corrective actions. The ambidextrous, one-size-fits-all back of hand mount accommodates gloves and easily fits into the smallest of spaces. And a retracting lanyard trigger worn around the neck or on a belt keeps the scanner handy, yet out of the way.

Use it everywhere — including the freezer

Use the RS6100 in freezers and coolers, out on the dock in the sweltering heat and subzero cold, rain, snow — the RS6100 is built to handle it all.

Techninė specifikacija

Nuskaitymas	
Tipas	Nešiojamas brūkšninių kodų skaitytuvas
Skenerio tipas	2D
Jutiklio tipas	LED
Palaikomi linijiniai (1D) brūkšniniai kodai	Codabar, Code 11, Code 128, Code 39, Code 93, GS1 DataBar, MSI
Palaikomi 2D (matricos ir sudėtiniai) brūkšniniai kodai	Aztec Code, Sudėtiniai kodai, Duomenų matrica, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
Optinio jutiklio skiriamoji geba (plotis x aukštis)	2688 x 1520 pikseliai
Bangos ilgis	515 nm
Pitch skaitymo kampas	-60 - 60°
Pokrypio skaitymo kampas	-60 - 60°
Ryšys	
Ryšio technologija	Bevielis
Mažo nuotolio radijo ryšys (NFC)	Taip
Veikimo charakteristikos	
Produkto spalva	Pilka, Geltona
Energijos valdymas	
Maitinimo šaltinio tipas	Baterija
Baterija	
Baterijos technologija	Ličio-jonų (Li-Ion)
Baterijos talpa	735 mAh

Svoris ir matmenys

Svoris	76 g
Plotis	66,6 mm
Ilgis	32,7 mm
Aukštis	21 mm

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	-30 - 50 °C
Darbo santykinės drėgmės diapazonas	5 - 95%

Matmenys ir svoris

Svoris	0,14kg
--------	--------

Dokumentai ir vaizdo įrašai

[› Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zebra

ATSAKINGAS ASMUO ES

Zebra TechnologiesBorupvang 3, Ballerup, DK
zebra.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt