ASUS PRIME Z890-P WIFI Intel Z890 LGA 1851 (Socket V1) ATX

Gamintojas: **ASUS** · Modelis: **90MB1I70-M0EAY0** · EAN: **4711387754818** · Prekės kodas: **843021**



331,90 €

Kaina su PVM

Be PVM: **274,30 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Intel LGA 1851 (Socket V1) Intel Core Ultra (Series 2)
- ✓ PC ATX Intel Z890 7.1 kanalai
- ✓ DDR5-SDRAM 4 DIMM Maksimali vidinė atmintis: 192 GB
- ✓ HDD & SSD M.2, SATA III RAID palaikymas Palaikomų saugojimo tvarkyklių skaičius: 8
- ✓ BIOS tipas: UEFI AMI 256 Mbit
- ✓ 2.5 Gigabit Ethernet „Wi-Fi“ Wi-Fi 7 (802.11be) Bluetooth 5.4













Aprašymas

ASUS PRIME series motherboards are expertly engineered to unleash the full potential of the latest Intel® Core™ Ultra Processors (Series 2). Boasting a robust power design, comprehensive cooling solutions and intelligent tuning options, the PRIME Z890-P WIFI motherboard provides users and PC DIY builders with a range of performance optimizations via intuitive software and firmware features. It’s designed to be Advanced AI PC-ready, offering the power and connectivity needed for demanding AI applications.

Performance

AI Solutions

ASUS AI Solutions include AI Advisor as your technical expert with expertise in PC performance, AI Networking II for real-time bandwidth optimization and AI Cooling II for automated temperature control.

AI Advisor

ASUS AI Advisor allows users to explore the functionality and advanced features of ASUS motherboards in a simple and straightforward way.1

AI Networking II

Optimized network performance, helping to ensure seamless connectivity and maximized WiFi 7 speeds.

AI Cooling II

Optimized thermals and reduced noise via dynamic adjustment of fan speeds, based on CPU temperatures.

Performance

NPU Boost

The integrated NPU in Intel® Core™ Ultra Processors (Series 2) efficiently accelerates AI workflows — and NPU Boost lets you do more with it. This BIOS feature overclocks the NPU with just one click, increasing performance by up to 24%.4

Performance

Robust power design

Stable power is crucial for maximizing the performance of Intel® Core™ Ultra Processors (Series 2). The PRIME Z890-P WIFI is designed to meet the needs of high-core-count CPUs. It features 14(80A) + 1(80A) + 2(80A) + 1(80A) power stages that integrate high-side and low-side MOSFETs and drivers into packages rated for up to 80 amperes each. This configuration ensures optimal power delivery, efficiency, stability and performance for both current and future Intel® processors.

Enhanced Memory & Storage Performance

AEMP III for Ultimate DDR5 Performance

ASUS Enhanced Memory Profile III (AEMP III) is an advanced firmware feature that empowers users to achieve unparalleled memory performance with cutting-edge CUDIMM memory. Through a two-phase comprehensive tuning process, AEMP III first optimizes the clock driver and then the memory frequency. This results in the best balance between performance and stability, even at cutting-edge speeds of DDR5-7600 or higher.5

DIMM Fit

DIMM Fit is an ASUS-exclusive BIOS feature that precisely analyzes individual memory modules to optimize performance and pinpoint potential issues. This offers peak efficiency, compatibility, and system stability. Whether you are an overclocker seeking ultimate performance, a competitor pursuing the most responsive gameplay, or a content creator prioritizing rock-solid stability, DIMM Fit provides optimizations tailored to your needs and your hardware configuration.

Four M.2 slots (up to 128Gbps)

The PRIME Z890-P WIFI offers a total of four M.2 slots, including one that supports data-transfer speeds of up to 128Gbps via PCIe 5.0, three that support 64Gbps via PCIe 4.0. This enables quicker boot-up and app load times with OS or application drives.6

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Cooling

Cooler by design

The PRIME Z890-P WIFI motherboard is engineered with multiple onboard heatsinks and an array of hybrid fan headers to help ensure your rig stays cool and stable under intense workloads.

Cooling

Smart cooling precision

ASUS Fan Xpert 4

ASUS Fan Xpert 4 software offers comprehensive control over fans and AIO coolers. Auto-Tuning mode configures settings with one click, while Extreme Quiet mode reduces fan speeds for silent operation during light tasks. Controls are also available via the UEFI BIOS.

Cooler compatibility

ASUS AIO coolers offer robust performance, high overclocking potential, bold aesthetics and customizable functionality for new motherboards, empowering you to build your dream gaming rig.7

Flexibility

Empowering connections

The PRIME Z890-P WIFI motherboard offers a versatile range of connectivity, including support for WiFi 7, the latest version of PCI Express, while an arsenal of USB ports includes Type-C connections, and Thunderbolt™ 4 which expands compatibility and bandwidth even further.

WiFi 7

The next-gen WiFi 78 supports 160 MHz bandwidth in the 6 GHz band and 4096 QAM. Multi-Link Operation (MLO) ensures stable connections and low latency, supporting 2.4, 5, and 6 GHz bands for enhanced coverage and throughput.

Thunderbolt™ 4 Type-C® ports

Thunderbolt™ 4 Type-C® port delivers up to 40Gbps of bidirectional bandwidth for the latest super-speed devices and drives. The port can be employed for up to one external 8K display, and PCIe bandwidth extends to up to 32Gbps.

PCIe 5.0 slot

The latest processors introduce PCIe 5.0 support, doubling data transfer speeds compared to PCIe 4.0, enhancing signal integrity, and providing backward-compatible CEM connectors and support for previous PCIe versions.

Customization

Personalization

The PRIME Z890-P WIFI enhances the user experience across the board, from simplifying BIOS setting adjustments to offering customizable RGB lighting controls for a uniquely personal system aesthetic.

UEFI BIOS

The UEFI interface delivers easy-to-use configuration options for PC beginners, and advanced features for veterans.

TurboV Core

Intuitive overclocking within Windows. No BIOS interface, no reboots. Simple and swift performance tuning at your fingertips.

ASUS GlideX

Enable seamless screen sharing and control across PCs, tablets, and smartphones via wired or wireless connections, supporting multiple platforms.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

ASUS DriverHub

Simplify driver management with automatic detection, one-click installation and update for smooth, efficient system performance.

Armoury Crate

Customize Aura Sync RGB and control ASUS devices. Includes product registration and updates.

Aura Sync

Complete RGB lighting control for enthusiast systems, ensuring seamless synchronization with compatible hardware.

Addressable Gen2 RGB headers

Three Addressable Gen2 headers detect LED counts on compatible RGB devices, automatically adjusting lighting effects accordingly.

Customization

DIY friendly

The PRIME Z890-P WIFI motherboard features EZ PC DIY innovations that simplify and speed up the PC building process, making DIY easy and convenient.

Q-Antenna

With Q-Antenna, attaching a WiFi antenna to your PC is now easy and fast. Instead of slowly rotating two fasteners until they finally lock in, they just snap into place. Less hassle, and more consistent performance.9

PCIe Slot Q-Release

A physical lever unlocks the first PCIe slot’s security latch with one tap, greatly simplifying the process of detaching a PCIe card from the motherboard when it’s time to upgrade to a new graphics card or other compatible device.

M.2 Q-Latch

The innovative ASUS Q-Latch makes it easy to install or remove an M.2 SSD without the need for specific tools or screws. This design employs a simple locking mechanism to secure the drive and neatly detach it with one tap.

Q-LED Core

The Q-LED Core display produces color-coded lights during the Power-On Self-Test (POST) that can help you troubleshoot potential issues.

Pre-mounted I/O shield

Our pre-installed I/O shield safeguards ports, simplifies the build process, increases functionality and enhances aesthetics for PC DIY enthusiasts.

BIOS FlashBack™

BIOS FlashBack™ simplifies BIOS updates. Just load the BIOS file onto a FAT32 USB stick, insert it into the BIOS FlashBack™ port, and press a button — no CPU or memory needed.

SafeSlot

PCIe 5.0 is twice as fast as PCIe 4.0. ASUS has adapted our SMT manufacturing for the faster SafeSlot, a reinforced metal sheath that ensures secure card installation and faster data speeds.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Techninė specifikacija

Procesorius	
Procesoriaus gamintojas	Intel
Procesoriaus lizdas	LGA 1851 (Socket V1)
Procesorių suderinamumas	Intel Core Ultra (Series 2)
Atmintis	
Palaikomi atminties tipai	DDR5-SDRAM
Atminties angų skaičius	4
Maksimali vidinė atmintis	192 GB
Atminties angų tipas	DIMM
Atminties kanalai	Dviejų kanalų
ECC suderinamumas	Ne-ECC
Palaikomas atmintinės taktinis dažnis (didžiausias)	7600 MHz
Nebuferizuota atmintis	Taip
Duomenų laikymo valdikliai	
Palaikomi saugojimo kaupiklių sąsajos	M.2, SATA III
Palaikomi saugojimo kaupiklių tipai	HDD & SSD
Palaikomų kietųjų diskų skaičius	4
Palaikomų saugojimo tvarkyklių skaičius	8
RAID palaikymas	Taip
RAID lygiai	0, 1, 5, 10
Grafika	
Paralelinio apdorojimo technologijos parama	Nepalaikomas
Integruotas grafikos adapteris	Ne
Vidinis I/O	
USB 2.0 jungtys	2
USB 3.2 (3.1 1 kart.) jungtys	2
USB 3.2 (3.1 2 kart.) jungtys	1
SATA III jungčių skaičius	4
S/PDIF out jungtis	Taip
Priekinio skydelio audio jungtis	Taip
ATX maitinimo jungtis	Taip
CPU fan jungtis	Taip
Šasi fenų jungčių skaičius	4

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

EPS maitinimo jungtis (8-kaisčiai)	Taip
COM jungčių skaičius	1
TPM jungtis	Taip
„Thunderbolt“ kolektoriai	1
12 V maitinimo jungtis	Taip
RGB LED kontaktų pagrindas	Taip
Galinė panelė I/O jungtys	
USB 2.0 portų kiekis	4
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	2
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	0
USB 3.2 2 kart. (3.1 2 kart.) A tipo prievadų skaičius	1
USB 3.2 2 kart. (3.1 2 kart.) C tipo prievadų skaičius	1
Ethernet LAN (RJ-45) portų kiekis	1
VGA (D-Sub) portų kiekis	0
HDMI portų kiekis	1
DVI-D prievadų skaičius	0
HDMI versija	2.1
„DisplayPort“ kiekis	1
„DisplayPort“ versija	1.4
Ausinių išvestys	1
Įvedimas	Taip
Tinklas	
„Wi-Fi“	Taip
Ethernet LAN jungtis	Taip
Eterneto sąsajos tipas	2.5 Gigabit Ethernet
„Wi-Fi“ standartas	Wi-Fi 7 (802.11be)
Wi-Fi standartai	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax), Wi-Fi 7 (802.11be)
Bluetooth	Taip
Bluetooth versija	5.4
Savybės	
Taikoma	PC
Motininės plokštės formos faktorius	ATX
Motininės plokštės sisteminio valdiklio šeima	Intel
Pagrindinės plokštės lustas	Intel Z890

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Garso išvesties kanalai	7.1 kanalai
Produkto spalva	Juoda
Aušinimo tipas	Pasyvus
Maitinimo šaltinio tipas	ATX
Palaikomos „Windows“ operacinės sistemos	Windows 10, Windows 11
Plėtotės lizdas	
„PCI Express x16“ (4 kartos) lizdai	3
„PCI Express x16“ („Gen 5.x“) lizdai	1
M.2 (M) angų skaičius	4
BIOS	
BIOS tipas	UEFI AMI
BIOS atminties dydis	256 Mbit
Pakuotės duomenys	
Pakuotės plotis	353 mm
Pakuotės gylis	273 mm
Pakuotės aukštis	68 mm
Paketo svoris	1,89 kg
Svoris ir matmenys	
Plotis	305 mm
Ilgis	244 mm
Pakuotės turinys	
Pridėti kabeliai	SATA
Kitos savybės	
Greito diegimo vadovas	Taip
Grįžimo į BIOS (Back-to-BIOS) mygtukas	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	36,00cm × 27,00cm × 7,00cm
Svoris	1,83kg

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

GAMINTOJAS

ASUSTeK Computer Inc
Li-Te Road 15, 112 Taipei, TW
asus.com

ATSAKINGAS ASMUO ES

ASUS France S.A.R.L.
Allee bienvenue 10, 93160 Paris, FR
channel.asus.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt