ACT Powercord mains connector CEE7/7 male (angled) - C15 (angled left) IEC60320 black 2 m

Gamintojas: **ACT** · Modelis: **AK5348** · EAN: **8716065558197** · Prekės kodas: **844098**

19,90 €

Kaina su PVM

Be PVM: **16,45 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cable length: 2 m
- ✓ Connectors: CEE7/7 male (angled) - C15 (angled left) IEC60320
- ✓ The C15 connector is high temperature resistant up to 120°C
- ✓ Maximum load: 250V~/10A
- ✓ Colour: black
- ✓ Suitable for servers, network switches; e.g. HP and Cisco

Aprašymas

The CEE 7/7 to C15 powercord is often used where a higher temperature is expected at the equipment side. The C15 connector is high temperature resistant up to 120°C. This cable is also used for powering network switches.

ACT provides many types of power cables: CEE 7/7, Euro, UK, USA, Italian, Danish, Swiss and Indian/South African cables. ACT supplies powercables with the following connectors: CEE 7/7, IEC60320 C5, C7, C13, C14, C19, C20 and IEC60309 CEE1. ACT offers different types of power split cables and power cables in the following colors: black, white, red, blue, green and yellow.

Techninė specifikacija

Features

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Product colour	Black
Connector 1 gender	Female
Connector 2 gender	Male
Cable length	2 m
Connector 1	CEE7/7
Connector 2	IEC C15
Connector 2 standard	IEC 60320
Connector 1 form factor	Angled
Connector 2 form factor	Angled
Jacket material	Neoprene
Conductor material	Copper
Cable type	H05RN-F
Number of conductors	3
Conductor cross section	0.75 mm²
Compatibility	Suitable for servers, network switches; e.g. HP and Cisco
Power	
Input voltage	250 V
Input current	10 A
Operational conditions	
Operating temperature (T-T)	-10 - 70 °C
Certificates	
Compliance certificates	VDE, CE
Packaging data	
Quantity per pack	1 pc(s)
Matmenys ir svoris	
Svoris	1,00kg

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt