

StarTech.com DK30CHHPDEU knyginių kompiuterių dokas / jungčių replikatorius Vielinis USB 3.2 Gen 1 (3.1 Gen 1) Type-C Juoda, Sidabras

Gamintojas: **STARTECH** · Modelis: **DK30CHHPDEU** · EAN: **065030883474** · Prekės kodas: **845364**



117,90 €

Kaina su PVM

Be PVM: **97,44 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ Priimančioji sąsaja: USB 3.2 Gen 1 (3.1 Gen 1) Type-C
- ✓ „USB Power Delivery“
- ✓ Ethernet LAN jungtis 10,100,1000 Mbit/s
- ✓ Kabelio spynos lizdas



Aprašymas

USB 3.1 Gen 1 Type-C Docking Station | Mac & Windows® | 3x USB-A | 1x USB-C | GbE | Mountable | 65W PD

This USB-C docking station is ideal for use in large organizations to meet widespread office productivity requirements and compatibility with all USB-C and Thunderbolt 3 laptops. The USB-C dock features support for Dual HDMI monitors, 65W Power Delivery 3.0, fast-charge, and both USB-C and USB-A peripheral ports.

Dual Full HD 1080p HDMI Displays

The USB-C docking station adds dual HDMI monitors support to your workstation, with full high definitions resolutions of 1920x1080 or 1920x1200 at 60Hz. With more screen space, you can access multiple applications and reference material on one display while composing on the other.

Charge Devices via USB-C & USB-A

The USB-A and USB-C charge ports can charge your smartphone, tablet or other USB peripherals whether you're working or away from your desk, and even if you disconnect your laptop.

65W Power Delivery

Using a single cable, the dock powers and charges your laptop as you work with 65W PD for faster charging, using the 90W power adapter.

Convenient Setup with a Modest Desktop Footprint

With a smaller size and extended length 3.3' (1 meter) host cable, this USB-C dock fits easily into a workspace environment. Even where desk space is limited, this dock can be mounted to the wall, monitor or underneath the desk with StarTech.com mounting brackets (SSPMSUDWM & SSPMSVESA). These mounting brackets are specifically designed for our docks and hubs to give you the customized setup you need.

The Connections You Need

Connect your devices with four USB 3.1 ports: 1x USB-C and 3x USB-A. Fast-charge your USB-C or USB-A smartphone. The dock provides a GbE port (Wake-on-LAN) and a 3.5 mm 4-position headset audio jack. It also includes a security lock slot (K-slot) to protect against theft.

Enhance Productivity and Device Management with the StarTech.com Connectivity Tools Application

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

-

Advanced Windows Layout Utility : To setup and save custom windows layouts.

-

Mac Address Pass-Through Utility : To improve network security.

-

USB Event Monitoring Utility : To track and log connected USB devices

-

Wi-Fi Auto Switch Utility : Enabling users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/Connectivity-Tools

The IT Pro's Choice Since 1985

StarTech.com conducts thorough compatibility and performance testing on all our products to ensure we are meeting or exceeding industry standards and providing high-quality products to IT Professionals. Our local StarTech.com Technical Advisors have broad product expertise and work directly with our StarTech.com Engineers to provide support for our customers both pre and post-sales.

DK30CHHPDEU is backed by a StarTech.com 3-year warranty and free lifetime technical support.

The StarTech.com Advantage

Techninė specifikacija

Ryšys

Ryšio technologija	Vielinis
Priimančioji sąsaja	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 2.0 portų kiekis	0
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	3
HDMI portų kiekis	2
Ausinių išvestys	1
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	1
„USB Power Delivery“	Taip
USB maitinimo tiekimas iki	60 W
Jungtinis ausinių / mikrofono prievadas	Taip
DC įėjimo lizdas	Taip

Tinklas

Ethernet LAN jungtis	Taip
Ethernet LAN (RJ-45) portų kiekis	1
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Pilnai abipusis (duplex)	Ne

Veikimo charakteristikos

Produkto spalva	Juoda, Sidabras
Integruotas kortelių skaitytuvas	Ne
Duomenų perdavimo sparta	5 Gbit/s
HD tipas	„Full HD“
Maksimali skaitmeninė raiška	1920 x 1200 pikseliai
Palaikomų ekranų skaičius	2
Kabelio spynos lizdas	Taip
Laido spynos lizdo tipas	Kensington
UASP palaikymas	Taip

Energijos valdymas

AC įėjimo įtampa	100 - 240 V
Įvesties srovė	1.5 A
Išėjimo įtampa	20 V
Išėjimo srovė	4,5 A
Kištuko tipas	N tipas
Suderinamų energijos šaltinio kištukinių lizdų tipai	EU

Programinė įranga

Palaikomos „Windows“ operacinės sistemos	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Palaikomos MAC operacinės sistemos	Mac OS X 10.15 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Palaikoma operacinė sistema „Linux“	Ubuntu 18.04 LTS, Ubuntu 20.04 LTS
Kitos palaikomos operacinės sistemos	ChromeOS

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-20 - 70 °C
Darbo santykinės drėgmės diapazonas	0 - 95%

Svoris ir matmenys

Plotis	80 mm
Ilgis	150 mm
Aukštis	30 mm
Aukštis (galas)	30 cm

Pakuotės duomenys

Kiekis pakuotėje	1 vnt
Pakuotės plotis	145 mm
Pakuotės gylis	234 mm
Pakuotės aukštis	82 mm
Paketo svoris	1 kg

Pakuotės turinys

Pridėti kabeliai	C tipo USB
Greitos pradžios vadovas	Taip
Techninė informacija	
Atitikties sertifikatai	CE, RoHS
Logistikos duomenys	
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	4 vnt
Pagrindinės (išorinės) dėžės plotis	245 mm
Pagrindinės (išorinės) dėžės ilgis	345 mm
Pagrindinės (išorinės) dėžės aukštis	165 mm
Darniosios sistemos (DS) kodas	84733020
Kitos savybės	
Lustų rinkinys	DisplayLink DL3900, Realtek RTS5423, Realtek RTS5411E
Tvarumas	
Tvarumo reikalavimų laikymasis	Taip
Matmenys ir svoris	
Svoris	1,03kg

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas
- › Vaizdo įrašas 1 youtube.com/watch?v=V1e8gfpHE8s
- › Vaizdo įrašas 2 youtube.com/watch?v=0OUcYYrHpqs
- › Vaizdo įrašas 3 youtube.com/watch?v=pzZ6ygna0tk

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
[startech.com](https://www.startech.com)

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
[startech.com](https://www.startech.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt