

Zyxel NWA90AX PRO 2400 Mbit/ai Balta Maitinimas per Eternetą (PoE)

 Gamintojas: **ZYXEL** · Modelis: **NWA90AXPRO-EU0102F** · EAN: **4718937630592** · Prekės kodas: **852403**


130,90 €

Kaina su PVM

 Be PVM: **108,18 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2,4 GHz 575 Mbit/ai
- ✓ 5 GHz 2400 Mbit/ai
- ✓ Didžiausias duomenų perdavimo greitis: 2400 Mbit/ai
- ✓ IEEE 802.11n, IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g
- ✓ 802.1x RADIUS, EAP, WEP, WPA, WPA2, WPA2-Enterprise, WPA2-PSK, WPA3
- ✓ Maitinimas per Eternetą (PoE)
- ✓ Vidinis Integruota antena



Aprašymas

Multi-gig WiFi 6 access point for small businesses

Zyxel NWA90AX Pro

AX3000 Dual-Radio Multi-gig PoE Access Point with secure authentication support

Multi-gig WiFi 6 access point for small businesses

Delivering AX3000 WiFi speed with 2.5G Ethernet uplink port, the Zyxel NWA90AX Pro provides the powerful and fastest WiFi 6 speed for small businesses, SoHo, and home offices.

Small business owners looking for an affordable WiFi 6 access point with multi-gig connectivity, Zyxel's NWA90AX Pro is no doubt the ideal choice for them to support more connected devices and applications with the fastest speeds.

Boost your WiFi performance

To better leverage the faster speeds in 5Ghz band, Zyxel NWA90AX Pro equips with 3x high-gain antennas to boost WiFi signals and extend coverage, especially to previously hard-to-reach areas.

In addition to the WiFi boost, NWA90AX Pro also comes with the premium multi-gig Ethernet connections. As it can run on the common-type Cat5e cabling, a 2.5G uplink port breaks through the 1.0G bottleneck without re-cabling, making it easy to create an affordable high-speed network environment for your business or home.

Secure authentication to protect business networks

With the support of captive portal and IEEE802.1x authentication, the NWA90AX Pro not only offers small business users the enterprise-level security to protect their networks, but also the flexible opportunity to customize wireless network usage login for marketing and business recognition.

Set up your wireless network in minutes!

No networking expertise required - The NWA90AX Pro is designed to be easily configured and installed in places like small hotels, retail stores, restaurants, or home offices.

The simple configuration allows you to set up the network for your customers and employees in minutes. The AP can be managed either with Nebula Cloud networking platform or the device's local interface.

Easy deployment with Zyxel's Smart Mesh

Zyxel's Smart Mesh technology automatically forms dynamic wireless links between access points and mitigates the complex, inconvenient cabling for WiFi deployment.

The Smart Mesh technology can save you from extra wiring by enabling the wireless connectivity between APs for extended range and flexible deployment.

Manage it your way!

The NWA90AX Pro with NebulaFlex offers the flexible manageability for you to freely choose between the device's local web interface or onboarding to our super easy Nebula cloud management interface that you never need to worry about forgetting the IP address or lost account and password when managing it on cloud.

Techninė specifikacija

Savybės

2,4 GHz

Taip

5 GHz	Taip
6 GHz	Ne
Didžiausias duomenų perdavimo greitis	2400 Mbit/ai
Maksimalus duomenų perdavimo greitis (2,4 GHz)	575 Mbit/ai
Maksimalus duomenų perdavimo greitis (5 GHz)	2400 Mbit/ai
Eterneto LAN duomenų perdavimo norma	1000,2500 Mbit/ai
Tinklo standartai	IEEE 802.11n, IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g
MIMO	Taip
MIMO tipas	Multi User MIMO
„Wi-Fi“ multimedijos (WMM) / (WME)	Taip
VLAN palaikymas	Taip
Saugumas	
Apsaugos algoritmų palaikymas	802.1x RADIUS, EAP, WEP, WPA, WPA2, WPA2-Enterprise, WPA2-PSK, WPA3
MAC adresų filtravimas	Taip
Protokolai	
Valdymo protokolai	SNMP
Valdymo funkcijos	
Web pagrįstas valdymas	Taip
Firmware tobulinimas	Taip
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	1
DC įėjimo lizdas	Taip
Energijos valdymas	
Maitinimas per Eternetą (PoE)	Taip
AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50/60 Hz
Įvesties srovė	0.3 A
Išėjimo įtampa	12 V
Išėjimo srovė	2 A
Konstrukcija	
Talpinimo	Lubos
Produkto spalva	Balta
LED indikatoriai	Taip
Antena	

Antenos tipas	Vidinis
Antenos ypatybės	Integruota antena
Antenos stiprinimo lygis (max)	4 dBi
Svoris ir matmenys	
Plotis	140 mm
Ilgis	140 mm
Aukštis	37,5 mm
Svoris	352 g
Pakuotės duomenys	
Pakuotės plotis	240 mm
Pakuotės gylis	155 mm
Pakuotės aukštis	60 mm
Paketo svoris	668 g
Aplinkos sąlygos	
Darbo santykinės drėgmės diapazonas	10 - 90%
Darbo temperatūros diapazonas (TT)	0 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Sandėliavimo santykinis drėgmės diapazonas	10 - 90%
Matmenys ir svoris	
Matmenys (I × P × A)	14,00cm × 14,00cm × 4,00cm
Svoris	0,68kg

Dokumentai ir vaizdo įrašai

› [Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zyxel Networks Corporation

Industry East RD. IX, Hsinchu Science Park 2,
30076 Hsinchu, TW
zyxel.com

ATSAKINGAS ASMUO ES

Zyxel Networks A/S

Adenauerstraße 20/A3, 52146 Würselen, DE
zyxel.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt