

D-Link DWM-314-G mobiliojo ryšio įrenginys Korinio tinklo modemai / maršrutizatoriai

Gamintojas: **D-LINK** · Modelis: **DWM-314-G** · EAN: **790069475245** · Prekės kodas: **853011**



430,91 €

Kaina su PVM

Be PVM: **356,12 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4 GbE LAN ports ensure reliable connectivity and reduce extra switch cost
- ✓ Plug & Play design for quick and easy integration
- ✓ Durable zinc-plated steel case is corrosion-resistant to ensure device longevity



Aprašymas

Unleash 5G Power for Superior M2M Connectivity

The DWM-314-G 5G Multi-Connect Modem harnesses 5G technology to accelerate ultra-fast speed, reduce latency, and ensure reliable connectivity with its automatic failover feature, enhancing machine-to-machine communication. Ideal for smart parking poles, kiosks and ATMs, this modem supports real-time data transfer and remote management. Built-in 4-port Gigabit Ethernet simplify setup and reduce the extra power supply wires and the need for additional switch, making it perfect for space-constrained environments and cost saving. Additionally, secure VPN capabilities safeguard data transmission, ensuring robust security for all connected devices.

Plug & Play for Easy Installation

Designed for instant setup, the DWM-314-G 5G modem offers real-time remote access and uninterrupted connectivity over long distances. Equipped with dual SIM slots and simply insert two Micro-SIM cards (3FF) for a reliable connection to the high-speed 5G network with seamless 4G/5G switching and for failover redundancy, even if one carrier network is down. Convenient wall and DIN-rail mounting options allow the DWM-314-G to be mounted virtually anywhere. This plug-and-play modem ensures robust service even in challenging environments.

Robust Build Quality

The industrial-grade casing provides reliable high-speed connectivity in extreme conditions. The corrosion-resistant zinc-plated steel case with wide operating temperature range and humidity tolerance mean that the DWM-314-G is ready for the most demanding M2M applications in virtually any environment.

Techninė specifikacija

Konstrukcija	
Įtaiso tipas	Korinio tinklo modemas / maršrutizatorius
Produkto spalva	Juoda
Ethernet LAN funkcijos	
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
DHCP serveris	Taip
Mobilusis ryšys	
Trumpųjų pranešimų paslauga (SMS)	Taip
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	4
Saugumas	
Portų ekspedijavimas	Taip
VPN palaikymas	OpenVPN WireGuard
Pakuotės turinys	
Pridėti kabeliai	AC
Veikimo charakteristikos	
Web pagrįstas valdymas	Taip
Energijos valdymas	
Maitinimo šaltinio tipas	DC
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-30 - 70 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 85 °C
Darbo santykinės drėgmės diapazonas	10 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%

Svoris ir matmenys

Plotis	131 mm
Ilgis	99 mm
Aukštis	40 mm

Matmenys ir svoris

Svoris	1,15kg
--------	--------

Dokumentai ir vaizdo įrašai

[› Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL

dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt