

Zyxel NWA90BE PRO 5764 Mbit/ai Balta Maitinimas per Eternetą (PoE)

Gamintojas: **ZYXEL** · Modelis: **NWA90BEPRO-EU0102F** · EAN: **4718937648931** · Prekės kodas: **856077**



147,90 €

Kaina su PVM

Be PVM: **122,23 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2,4 GHz 688 Mbit/ai
- ✓ 5 GHz 4324 Mbit/ai
- ✓ 6 GHz 5764 Mbit/ai
- ✓ Didžiausias duomenų perdavimo greitis: 5764 Mbit/ai
- ✓ IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3at, IEEE 802.3bt
- ✓ WEP, WPA, WPA2, WPA3
- ✓ Maitinimas per Eternetą (PoE)
- ✓ Vidinis



Aprašymas

Powerful. Secure. Wireless.

Future-Ready WiFi 7 for Small Businesses and SoHo Users

Future-Ready WiFi 7 for Small Businesses and SoHo Users

Zyxel's NWA90BE PRO is a WiFi 7 access point designed for small businesses and SoHo users seeking a cost-effective yet high-performance upgrade. Ideal for home offices, compact workspaces, and residential use, it delivers a seamless transition to WiFi 7 with faster speeds and dependable, wide-reaching coverage.

Unleash WiFi 7 Speeds with Enterprise-Grade Power

Powered by a Qualcomm quad-core CPU, the BE6500 (2.4GHz: 2x2:2, 5/6GHz: 2x2:2) dual-radio access point delivers blazing-fast WiFi 7 speeds of up to 6.5Gbps, ensuring enterprise-grade performance in a compact design.

Equipped with a 2.5GbE port, the NWA90BE PRO offers a cost-effective way to experience WiFi 7's full potential, delivering multi-gigabit speeds without disrupting your current network setup.

Smart Mesh MLO: More Bandwidth, Less Hassle

Smart Mesh MLO (Multiple Link Operation) technology automatically establishes dynamic wireless links, eliminating the need for complex, inconvenient cabling in WiFi deployments.

Unlike traditional mesh networks that rely on a single radio for data transmission, the NWA90BE PRO utilizes dual-radio backhaul, delivering superior bandwidth, enhanced interference resistance, and ultra-low latency for seamless, high-performance connectivity.

Secure Authentication to Safeguard Business Networks

With support for a captive portal, IEEE 802.1X/RADIUS authentication, the NWA90BE PRO not only offers small business users enterprise-level security to protect their networks, but also provides flexible options to customize wireless network login pages for marketing and brand recognition.

Connected - In Just a Few Clicks!

You can be connected in minutes with just a few simple clicks on the Nebula mobile app. The easy step-by-step wizard guides you through the entire installation process, and the intuitive app makes it easy to change settings as needed.

Nebula, The Intelligent Cloud Management

Nebula offers comprehensive monitoring and reporting capabilities, including real-time notifications for critical events via email or the mobile app.

With Nebula, you can enjoy a streamlined experience for network installation and management without the need for additional costs for software or hardware controllers.

Techninė specifikacija

Savybės	
2,4 GHz	Taip
5 GHz	Taip
6 GHz	Taip
Didžiausias duomenų perdavimo greitis	5764 Mbit/ai

Maksimalus duomenų perdavimo greitis (2,4 GHz)	688 Mbit/ai
Maksimalus duomenų perdavimo greitis (5 GHz)	4324 Mbit/ai
Didžiausia duomenų perdavimo sparta (6 GHz)	5764 Mbit/ai
Eterneto LAN duomenų perdavimo norma	1000,2500 Mbit/ai
Tinklo standartai	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3at, IEEE 802.3bt
MIMO	Taip
MIMO tipas	Multi User MIMO
„Wi-Fi“ multimedijos (WMM) / (WME)	Taip
Greitas tarpvietinis ryšys	Taip
VLAN palaikymas	Taip
Saugumas	
Apsaugos algoritmų palaikymas	WEP, WPA, WPA2, WPA3
Automatinė bėlavdžio paskirstymo sistema (WDS)	Taip
RADIUS kompiuterių tinklo protokolas	Taip
Valdymo funkcijos	
Duomenys perduodami į debesies platformą	Taip
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	1
USB 2.0 portų kiekis	0
DC įėjimo lizdas	Taip
Energijos valdymas	
Maitinimas per Eternetą (PoE)	Taip
AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50/60 Hz
DC įtampos stiprumo intervalas	12 V
Įvesties srovė	0.3 A
Išėjimo srovė	1,5 A
Konstrukcija	
Talpinimo	Lubos
Produkto spalva	Balta
Antena	
Antenos tipas	Vidinis
Antenos stiprinimo lygis (max)	3 dBi

Svoris ir matmenys

Plotis	150 mm
Ilgis	150 mm
Aukštis	35 mm
Svoris	412 g

Pakuotės duomenys

Pakuotės plotis	244 mm
Pakuotės gylis	168 mm
Pakuotės aukštis	60 mm
Paketo svoris	785 g

Pakuotės turinys

Kintamosios srovės adapteris	Taip
Montavimo rinkinys	Taip

Aplinkos sąlygos

Darbo santykinės drėgmės diapazonas	10 - 95%
Darbo temperatūros diapazonas (TT)	0 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Sandėliavimo santykinis drėgmės diapazonas	10 - 90%

Matmenys ir svoris

Matmenys (I × P × A)	15,00cm × 15,00cm × 4,00cm
Svoris	1,13kg

Gamintojo ir saugos informacija

GAMINTOJAS

Zyxel Networks Corporation

Industry East RD. IX, Hsinchu Science Park 2,
30076 Hsinchu, TW
zyxel.com

ATSAKINGAS ASMUO ES

Zyxel Networks A/S

Adenauerstraße 20/A3, 52146 Würselen, DE
zyxel.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt