

Vertiv Geist AGS5M1R5-06CF13-2PS6PS6B211-D power distribution unit (PDU) 6 AC outlet(s) 0U Black

Gamintojas: **VERTIV** · Modelis: **VA5G21A0** · Prekės kodas: **859183**



2 596,90 €

Kaina su PVM

Be PVM: **2 146,20 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Remotely reboot outlets to power cycle unresponsive IT equipment or increase runtime of critical equipment upon power failure with outlet-level control
- ✓ Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime
- ✓ Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime
- ✓ Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs
- ✓ Daisy-chain up to 50 devices on a single IP address and reduce deployment time with self-configuration of downstream devices



Aprašymas

Rack Transfer Switch (RTS) delivers redundant power to single corded devices. The RTS automatically detects the loss of power and switches the power load (no phase-synchronization required) to the alternative power source in less than 4-8 milliseconds without the need for human intervention.

Techninė specifikacija

Design	
PDU types	Switched
Rack capacity	0U
Type	Single-phase
Mounting	Horizontal
Product colour	Black
Display	LED
Ports & interfaces	
AC outlets quantity	6 AC outlet(s)
AC outlet types	C13 coupler, C19 coupler
Power plug	IEC 60309
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1
USB ports quantity	1
Features	
Reset button	Yes
Cable length	3 m
Management features	
Monitoring	Current, Power, Voltage
Supported network protocols	DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP
Power	
Nominal input voltage	200-240 V
Maximum current	16 A
AC input frequency	50/60 Hz
Load capacity	230 VA
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Weight & dimensions	
Width	432 mm
Depth	457 mm
Height	44 mm
Packaging data	

Package weight 5.44 kg

Matmenys ir svoris

Svoris 1,00kg

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Vertiv

ATSAKINGAS ASMUO ES

Vertiv GmbH

August-Everding-Str 25, 81671 München, DE
[vertiv.com](https://www.vertiv.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt