

Vertiv Geist VA4U21A0 power distribution unit (PDU) 12 AC outlet(s) 1U Black

Gamintojas: **VERTIV** · Modelis: **VA4U21A0** · Prekės kodas: **859185**



2 292,90 €

Kaina su PVM

Be PVM: **1 894,96 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vertiv Geist Rack Transfer Switch gives backup power to single corded devices in case of power loss
- ✓ VA4U21A0 is a 16A/20A, 120V/208V/230V, rPDU with (12) Combination C13/C19 outlets and (2) C20 inlet
- ✓ Vertiv Geist Next-Generation IMD has a 128x128 high-contrast LCD for monitoring data
- ✓ Helps ensure that data and operations are protected with the enhanced security features
- ✓ Vertiv Geist rPDUs are individually tested, CE Marked, Complies with IEC 60950-1 (CB Certificate Available), and RoHS certified



Aprašymas

The Vertiv Geist Rack Transfer Switch VA4U21A0 is a 16A/20A, 120V/208V/230V, single phase unit level monitored rPDU with (12) Combination C13/C19 outlets and (2) C20 inlet providing 1.9kW/3.3kW/3.6kW power capacity. This unit provides backup power to single-corded devices and helps ensure continuity in the event of power loss. It quickly detects power loss on the main source and automatically switches to the secondary source within less than 4 to 8 milliseconds. It is integrated with the Vertiv Geist Next-Generation IMD which displays power data via its 128x128 high-visibility LCD. It has an internal sensor that intelligently adjusts the orientation based on horizontal or vertical installation. This includes a redundant power-sharing port that connects two IMDs in the rack and provides backup power in case of power loss. Enhanced security with a secure boot is added to the device to help ensure data and operations are protected. The units are CE Marked, comply with IEC 60950-1 (CB Certificate Available), RoHS certified, and are individually tested for functionality and reliability.

Techninė specifikacija

Design	
PDU types	Monitored
Rack capacity	1U
Type	Single-phase
Mounting	Horizontal
Product colour	Black
Ports & interfaces	
AC outlets quantity	12 AC outlet(s)
AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	2
USB ports quantity	1
Management features	
Monitoring	Current, Power, Voltage
Supported network protocols	DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Modbus TCP/IP, Syslog, TACACS+
Power	
Nominal input voltage	100 - 240 V
Maximum current	20 A
Load capacity	230 VA
Maximum power	3600 W
Certificates	
Certification	UL & c-UL Listed 62368-1, RCM Mark(EMC Only), CE Marked, UKCA Marked, Complies with IEC 62368-1
Weight & dimensions	
Width	431.8 mm
Depth	457.2 mm
Height	43.7 mm
Packaging data	
Package weight	6.8 kg
Matmenys ir svoris	
Svoris	1,00kg

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Vertiv

ATSAKINGAS ASMUO ES

Vertiv GmbH

August-Everding-Str 25, 81671 München, DE

[vertiv.com](https://www.vertiv.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt