

D-Link DBR-X3000-AP WLAN prieigos taškas 3000 Mbit/ai Balta Maitinimas per Eternetą (PoE)

Gamintojas: **D-LINK** · Modelis: **DBR-X3000-AP** · EAN: **790069477379** · Prekės kodas: **859274**



110,90 €

Kaina su PVM

Be PVM: **91,65 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2,4 GHz 574 Mbit/ai
- ✓ 5 GHz 2402 Mbit/ai
- ✓ Didžiausias duomenų perdavimo greitis: 3000 Mbit/ai
- ✓ IEEE 802.3af
- ✓ WPA, WPA2, WPA3-Enterprise, WPA3-Personal
- ✓ Maitinimas per Eternetą (PoE)
- ✓ Antenų kiekis: 3 Vidinis



Aprašymas

AX3000 Wi-Fi 6 Smart AP

The AX3000 Wi-Fi 6 Smart AP leverages Wi-Fi 6 dual-band technology with PoE support to extend wireless coverage and provide high-speed connectivity throughout a building. It ensures reliable performance, efficient network management, and enhanced security. Centrally managed through D-Link DBR series business routers.

High-Speed Wi-Fi 6 Connectivity

The latest Wi-Fi 6 technology leverages the power of the 802.11ax standard to deliver faster, more efficient wireless performance, even in high-density environments. With speeds up to 3 Gbps, the DBR-X3000-AP enables lightningfast downloads, seamless streaming, and responsive real-time applications.

Wi-Fi 6 incorporates advanced features like MU-MIMO and OFDMA, which allow multiple devices to connect simultaneously without compromising speed or reliability. This results in a smoother user experience, reduced latency, and increased overall network capacity, making it ideal for both business-critical applications and high-traffic public areas.

WPA3 Wi-Fi Security

The DBR-X3000-AP is equipped with advanced security features to protect sensitive data and ensure a secure browsing experience for all users. It supports the latest WPA3 encryption protocol, which offers stronger protections against unauthorized access and safeguards user privacy with more robust encryption standard.

Central Management

The DBR-X3000-AP is managed through a D-Link DBR series business router and controlled via a unified dashboard. This centralized approach streamlines configuration, monitoring, and control of network settings, simplifying administrative tasks. It ensures consistent policy enforcement and offers realtime insights into network activity, enhancing overall efficiency and security.

Power Over Ethernet

The DBR-X3000-AP enables power over Ethernet (PoE), simplifying installation by delivering both data and power over a single Ethernet cable. With PoE compatibility, there's no need for additional power outlets or wiring, making it ideal for flexible and cost-effective deployments in various environments, including office, and retail spaces. This feature not only reduces installation time and costs but also allows for greater flexibility in placing access points where they are needed most, without being limited by traditional power sources. PoE ensures a reliable power supply, maximizing uptime and network stability.

Captive Portal

Captive portals are used in public Wi-Fi hotspots, guest networks, and enterprise environments to control user access. Users are redirected to a login or terms acceptance page before accessing the network. This process enhances security, enables user management, and can also display important information.

Techninė specifikacija

Savybės	
2,4 GHz	Taip
5 GHz	Taip
6 GHz	Ne
Didžiausias duomenų perdavimo greitis	3000 Mbit/ai
Maksimalus duomenų perdavimo greitis (2,4 GHz)	574 Mbit/ai
Maksimalus duomenų perdavimo greitis (5 GHz)	2402 Mbit/ai
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Tinklo standartai	IEEE 802.3af
VLAN palaikymas	Taip
Saugumas	

Apsaugos algoritmų palaikymas

WPA, WPA2, WPA3-Enterprise, WPA3-Personal

Ryšys

Ethernet LAN (RJ-45) portų kiekis

1

USB 2.0 portų kiekis

0

DC įėjimo lizdas

Taip

Energijos valdymas

Maitinimas per Ethernetą (PoE)

Taip

Išėjimo įtampa

12 V

Išėjimo srovė

1 A

Konstrukcija

Talpinimo

Lubos, Siena

Produkto spalva

Balta

Atstatymo mygtukas

Taip

LED indikatoriai

Energija, Būsena

Antena

Antenos tipas

Vidinis

Antenų kiekis

3

Antenos stiprinimo lygis (max)

4 dBi

Svoris ir matmenys

Plotis

170 mm

Ilgis

33,7 mm

Aukštis

170 mm

Matmenys ir svoris

Svoris

1,05kg

Dokumentai ir vaizdo įrašai[› Gaminio lankstinukas](#)**Gamintojo ir saugos informacija**

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL

dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt