InLine 92504B wire connector USB-A / Terminal block, 5-pin Black, Green

Gamintojas: **INLINE** · Modelis: **92504B** · EAN: **4043718346110** · Prekės kodas: **862799**

15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Female/Female Straight
- ✓ Black, Green
- ✓ 1 pc(s)

Aprašymas

Time savings during installation: Quick wiring via screw terminals for 16–26 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.
Clear terminal assignment & secure contact: 5-pin terminals with pressure plate, clearly labeled 1: –, 2: D+, 3: D–, 4: +, 5: S (shield) – ideal for service, testing, and prototyping.
Versatile industrial use: For quick connection of USB 2.0 signals in test setups, laboratories, commissioning, or troubleshooting – no soldering required.
Compact design: Only approx. 50 mm total length; can also be integrated into tight setups or adapter strips to save space.
High signal quality: An insulation resistance of ≥ 10 MΩ at 300 V DC and a rated current of 0.7 A per pin ensure reliable signal transmission – even under continuous load and in industrial environments.

The InLine® USB-A terminal block adapter offers a practical solution for transferring USB-2.0 signals to a 5-pin terminal block without soldering or cable connection. Typical applications can be found in the areas of service, test setups, development, or prototyping.
The standard-size USB-A socket is directly connected to a 5-pin screw terminal block. The clear labeling of the terminals – 1: Ground (–), 2: D+, 3: D–,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

4: Voltage (+), 5: Shield (S) – enables easy and reliable signal assignment. The terminal connections with a 5.0 mm grid dimension support single wires in the 16–26 AWG range.
Wiring is carried out with the aid of a flat-head screwdriver. Thanks to its compact housing, the adapter is particularly space-saving – e.g. in test equipment, mobile measuring stations, or in laboratories.

USB interface:USB-A 2.0, female connector
Number of pins / assignment:5 terminals / 1: – / 2: D+ / 3: D– / 4: + / 5: S
Connection technology: Screw terminal with pressure plate, 5.0 mm pitch
Connection range:16–26 AWG
Actuation: With flat-blade screwdriver ≤ 2.5 mm
Rated current:0.7 A per pin
USB operating voltage (VBUS):5 V DC
Test voltage (insulation resistance):300 V AC / 1 minute
Insulation resistance:≥ 10 MΩ @ 300 V DC
Operating temperature:–20 °C to +105 °C
Insulation layer:EVA insulation on underside
Dimensions:approx. 50 × 21 × 14 mm (L × W × H)

Techninė specifikacija

Features	
Connector(s)	USB-A / Terminal block, 5-pin
Product colour	Black, Green
Connector gender	Female/Female
Connector form factor	Straight
AWG wire size	26/16
Dielectric strength	300 V
Contact resistance	10 mΩ
Current	0.7 A
Operational conditions	
Operating temperature (T-T)	-20 - 105 °C
Certificates	
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Dimensions (WxDxH)	21 x 50 x 14 mm
Weight	11 g
Width	21 mm
Depth	50 mm
Height	14 mm
Packaging data	

Quantity per pack	1 pc(s)
Package width	70 mm
Package depth	135 mm
Package height	15 mm
Package weight	13 g
Package volume	100 cm³
Package type	Polybag
Logistics data	
Country of origin	Taiwan
Matmenys ir svoris	
Svoris	0,01kg

Gamintojo ir saugos informacija

GAMINTOJAS

Intos Electronic AG
Siemensstraße 11, D-35394 Gießen, DE
service@inline-info.com
intos.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt