

AudioCodes 4K Video USB Camera Mid size room

Gamintojas: **AUDIOCODES** · Modelis: **RXVCAM50-M** · Prekės kodas: **866656**



545,90 €

Kaina su PVM

Be PVM: **451,16 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Angle of View: 102°(D) / 100°(H) / 64°(V)
- ✓ Smart zoom and auto framing technology
- ✓ Plug and play via USB interface
- ✓ High quality image and natural color in all lighting conditions
- ✓ Compact and lightweight with smart mounting for fast and easy deployment
- ✓ Managed by AudioCodes One Voice Operations Center (OVOC)



Aprašymas

The AudioCodes RXVCam50M video camera is designed for all types of meeting rooms and conference rooms. They boast vivid image quality, leveraging HD 4K resolution for an exceptional video conferencing experience. Smart zoom and face detection technology combine to power an auto framing feature that automatically adjusts the camera's ePTZ (electronic pan, tilt and zoom), so that every meeting participant can be clearly seen – all with no user intervention required whatsoever

Techninė specifikacija

Camera

Megapixel (approx.)

8.28 MP

Camera type

Single camera

Sensor type	CMOS
Optical sensor size	25.4 / 2.5 mm (1 / 2.5")
Zoom capability	Yes
Digital zoom	10x
Focal length range	2.26 mm
Vertical field of view	64°
Minimum illumination	0.1 lx
F-number (relative aperture)	1.8
PTZ control	Yes
Aspect ratio	16:9
3D NR (Noise Reduction)	Yes
Video	
Maximum video resolution	3840 x 2160 pixels
Maximum frame rate	30 fps
HD type	4K Ultra HD
Resolution at capture speed	640x480@25fps, 640x480@30fps, 1280x720@25fps, 1280x720@30fps, 1920x1080@25fps, 1920x1080@30fps, 3840x2160@30fps
Video formats supported	H.264, H.265, MJPG, YUY2
Supported graphics resolutions	640 x 480 (VGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 3840 x 2160
Design	
Product colour	Black
Ports & interfaces	
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	1
Power	
Power source type	DC
DC input voltage	5 V
Input current	1 A
Power consumption (typical)	5 W
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-10 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Packaging content	
Remote control included	Yes
Cables included	USB

Quick start guide Yes

System requirements

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Minimum processor family	Core 2 Duo
Minimum processor speed	2.4 GHz
Minimum RAM	2048 MB

Performance

Plug and Play Yes

Weight & dimensions

Width	220 mm
Depth	93.8 mm
Height	56.5 mm

Matmenys ir svoris

Svoris 0,50kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

AudioCodes Ltd.

Ofra Haza Street 6, 6032303 Or Yehuda, IL
audiocodes.com

ATSAKINGAS ASMUO ES

AudioCodes GmbH

Hanauer Landstrasse 148a, 60314 Frankfurt am
Main, DE
audiocodes.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt