

StarTech.com 3m Blue Ultra Slim Cat6A Ethernet Cable, Snagless, FTP, Pure Bare Copper Wire, 34AWG Slim RJ45 Network Patch Cord, Individually Tested

 Gamintojas: **STARTECH** · Modelis: **N6APATSTP34BLS3M** · EAN: **065030917759** · Prekės kodas: **866839**


15,90 €

Kaina su PVM

 Be PVM: **13,14 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **Streamline Cabling in Tight Spaces**: Ultra Slim Cat6a Cables are 40% thinner than standard CAT6a, offering greater flexibility and easier routing in dense IT setups; U/FTP shielding with drain wire supports stable 10Gbps performance for reliable uptime
- ✓ **Built for Performance**: 50-micron gold-plated contacts ensure a precise fit for minimal insertion loss; 34AWG bare copper in U/FTP foil-shielded pairs delivers reliable signaling; Flexible 3.7 mm O.D. TPE jacket supports tight bends and is RoHS-compliant
- ✓ **Tested for Reliability**: Compliant with ANSI/TIA-568-C.2 standards for true Cat6a performance up to 500MHz; Individually Tested for minimal Near-End Crosstalk (NEXT) and Return Loss (RL); NOTE: Not rated for PoE applications
- ✓ **Enhance Visibility and Airflow**: Translucent RJ45 boot transmits port-LED light for faster link checks; Ultra slim cables improve passive airflow and ease access for troubleshooting in high-density server racks and patch panels
- ✓ **The IT Pro's Choice**: Designed for reliability in edge and on-prem deployments, our network cables are lab-tested and field-proven for seamless integration and maximum uptime; Backed by free lifetime 24/5 multi-lingual technical assistance



Built for Reliability and Performance



Optimize Dense Rack Environments

Ultra Slim Design allows cables to be routed more easily to improve airflow and cooling.




Ultra Slim, Easy Routing

Handle, bend, and route with ease for easier patch work.



Install-Friendly Connector Design

Standard RJ45 connector design allows for easy installation.



StarTech.com

Head to Head Made Easy

- Designed & Built for IT Pros
- Rigorous Testing & Certifications
- Free 24/5 Multi-Lingual Assistance
- IT Connectivity from Legacy to Latest
- Trusted by IT Professionals Since 1985



Aprašymas

Route Ultra Slim Cat6a cables through high density installations for optimal flexibility and airflow

Connect reliably to a 10Gbps network using this ultra slim Cat6a Ethernet cable, ideal for high-density network installations.

Improved Airflow

The Ultra Slim Cat6a Patch Cord is 40% thinner than standard Cat6a Ethernet cables, enabling greater airflow and heat dissipation in confined spaces. It is also more flexible for easier cable routing in crowded network racks and patch panels.

This cable features snagless connectors that protect the RJ45 clips during installation, reducing snags or breakage when routing through narrow gaps or in between devices.

Durable Construction

The Ultra Slim Cat6a Cable features 50-micron gold-plated RJ45 contacts for precise mating and minimal signal loss. Its 4-pair Unshielded Foiled Twisted Pair (U/FTP) design with 34 AWG pure bare copper conductors ensures low resistance and reliable throughput, using pair-level foil shielding to suppress EMI and crosstalk. The flexible TPE jacket provides durability and easy handling for everyday installations. Note: This cable is not rated for PoE applications.

Tested for Reliability

Each cable is individually tested using a Fluke® DSX2-8000 CableAnalyzer™ to meet ANSI/TIA 568 C.2-1 requirements for guaranteed Cat6a performance, ensuring consistent signal integrity with minimal Near-End Crosstalk (NEXT) and Return Loss (RL). It delivers dependable 10 Gigabit Ethernet performance for switches, routers, and other high-speed network devices.

Techninė specifikacija

Features	
Cable length	3 m
Cable standard	Cat6a
Cable shielding	U/FTP (STP)
Connector 1	RJ-45
Connector 2	RJ-45

Product colour	Blue
Connector 1 gender	Male
Connector 2 gender	Male
Cable shape	Round
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
Jacket material	Thermoplastic elastomer (TPE)
Conductor type	Stranded
Conductor material	Copper
Cabling technology	10GBase-T
Ethernet interface type	Fast Ethernet, Gigabit Ethernet, 5 Gigabit Ethernet, 2.5 Gigabit Ethernet, 10 Gigabit Ethernet
AWG wire size	34
Data transfer rate	10000 Mbit/s
Frequency	500 MHz
Snagless cable boot	Yes
Plug and Play	Yes
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Storage temperature (T-T)	-20 - 75 °C
Operating relative humidity (H-H)	0 - 90%
Certificates	
Compliance certificates	RoHS, CE
Weight & dimensions	
Outer diameter	3.7 mm
Weight	38 g
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	200 mm
Package depth	140 mm
Package height	25 mm
Package weight	52 g

Logistics data

Master (outer) case width	460 mm
Master (outer) case length	300 mm
Master (outer) case height	200 mm
Products per master (outer) case	40 pc(s)

Matmenys ir svoris

Svoris	0,05kg
--------	--------

Dokumentai ir vaizdo įrašai

[› Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.Artisans Crescent 45, N5V 5E9 Ontario, London,
CAstartech.com

ATSAKINGAS ASMUO ES

StarTech.com LimitedLaarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt