

Capture CA-SC-10200B barcode reader Handheld bar code reader 1D/2D LED Black

Gamintojas: **CAPTURE** · Modelis: **CA-SC-10200B** · EAN: **5715063320150** · Prekės kodas: **870251**



133,90 €

Kaina su PVM

Be PVM: **110,66 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Practical and user-friendly setup
- ✓ Supports multilingual data output
- ✓ Single-scan configuration with the iCode
- ✓ LED-aimer helps users aim faster and with greater accuracy
- ✓ Superior first-time read
- ✓ Omni-directional scanning
- ✓ Reads electronic barcodes from smartphone screens
- ✓ Reads most challenging and problematic barcodes
- ✓ Withstands drops from up to 1.8m onto concrete

Aprašymas

The Capture Viper handheld scanner is built to deliver maximum value. The Viper not only brings exceptional reading performance, but can also output data in numerous languages to cover a vast range of scanning requirements. Supported by the latest imaging technology it rapidly scans barcodes from product labels, membership cards, and electronic coupons, whether 1D or 2D. Even faded or damaged barcodes.

Techninė specifikacija

Scanning	
Type	Handheld bar code reader
Scanner type	1D/2D
Sensor type	LED
Linear (1D) barcodes supported	Code 128, Code 32, Code 39, GS1 DataBar, IATA, Interleaved 2 of 5, MSI, Matrix 2 of 5, Plessey, Telepen, U.P.C.

2D (matrix & stacked) barcodes supported	Aztec Code, Codablock, Code 16K, Code 49, Composite Codes, Data Matrix, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code
Optical sensor resolution (W x H)	640 x 480 pixels
Light levels (direct sunlight)	0 - 100000 lx
Pitch reading angle	-55 - 55°
Motion tolerance (cm/s)	62.7
Ports & interfaces	
Connectivity technology	Wired
Standard interfaces	USB
Bluetooth Low Energy (BLE)	Yes
Performance	
Product colour	Black
Housing material	Acrylonitrile butadiene styrene (ABS), Synthetics
International Protection (IP) code	IP52
Protection features	Bump resistant, Dust resistant, Splash proof
LED indicators	Battery level, Power, Status
Built-in display	No
Programming function	Yes
Power	
Battery technology	Lithium-Ion (Li-Ion)
Battery type	Built-in battery
Weight & dimensions	
Weight	156 g
Width	97 mm
Depth	65 mm
Height	155 mm
Packaging data	
External power adapter	Yes
Package weight	300 g
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Technical details

Compliance certificates	CE, RoHS
-------------------------	----------

Other features

Safety	Withstands multiple drops from 1.8m (6ft) to concrete
--------	---

Light source	660nm LED
--------------	-----------

Maximum operating distance	100 m
----------------------------	-------

Matmenys ir svoris

Svoris	0,16kg
--------	--------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

EET Group A/S

Bregnerødvej 133D, 3460 Birkerød, DK

eetgroup.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt