

Manhattan HDMI 4K@60Hz Cable with Ethernet - CL3 rated, 10m, Suitable for In-Wall use, For ALL 4K & 1080p/HD uses - when upgrading now or have it ready for when you need it, Male to Male, Black, Ultra HD 4k x 2k, Lifetime Warranty, Premium High Speed

Gamintojas: **MANHATTAN** · Modelis: **356992** · EAN: **766623356992** · Prekės kodas: **870722**



42,89 €

Kaina su PVM

Be PVM: **35,45 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ CL3 rating for in-wall installations with enhanced flame resistance and fire safety compliance
- ✓ Resolutions up to 4K@60Hz UHD (3840 × 2160), 1440p@144Hz (WQHD), 1080p@240Hz, 3D video, and Deep Color
- ✓ HDR for superior contrast and brilliant colors
- ✓ Supports Dolby Vision™ and Dolby Atmos®
- ✓ Gold-plated contacts for corrosion-free connections
- ✓ Foil and braid double shielding to reduce EMI and other interference sources
- ✓ Up to 18 Gbps bandwidth
- ✓ 4:4:4 chroma subsampling for true color accuracy and maximum sharpness
- ✓ HDMI Ethernet Channel (HEC) to add network connectivity to an HDMI link without a separate Ethernet cable
- ✓ HDMI Consumer Electronics Control (CEC) so one remote can be used with all compatible HDMI devices





Aprašymas

CL3 HDMI Cable 10m (33ft) for Safe In-Wall Installation and a Clean, Clutter-Free Setup

Designed for professional in-wall routing, this CL3-rated HDMI cable is the ideal choice for wall-mounted TVs, projectors, and conference room installations. The in-wall safety rating helps reduce fire risks compared to standard cables, making it a reliable option for permanent, code-friendly installations without visible cable clutter.

Stunning Ultra HD Performance for Movies, Gaming, and Presentations

Enjoy sharp, smooth video quality with support for resolutions up to 4K@60Hz UHD (3840 x 2160). The cable also handles high refresh rate formats like 1440p@144Hz and 1080p@240Hz, making it a great fit for gaming setups and fast-motion content. Support for 3D video and Deep Color ensures impressive depth and vibrant image detail across a wide range of devices.

HDR, Dolby Vision and Dolby Atmos Support

With HDR support, you get superior contrast, brighter highlights, and richer color reproduction - perfect for modern TVs and HDR content. Compatibility with Dolby Vision and Dolby Atmos ensures an immersive entertainment experience with cinema-grade visuals and audio when used with supported equipment.

Durable Construction with Gold-Plated Contacts and Double Shielding

Built for long-term performance, the HDMI male-to-male connectors feature gold-plated contacts for corrosion-resistant, stable connections. Foil and braid double shielding helps reduce EMI and other interference sources, ensuring clean signal transmission even in challenging environments such as behind walls, near power cables, or AV equipment.

Built-In Ethernet and ARC for Simplified Connectivity

The integrated HDMI Ethernet Channel (HEC) enables network connectivity over the HDMI link, eliminating the need for an additional Ethernet cable in compatible setups. Audio Return Channel (ARC) simplifies your audio wiring by allowing TV audio to be sent back through the same HDMI cable to a soundbar or AV receiver - no separate audio cable required.

Techninė specifikacija

Features	
Cable length	10 m
Connector 1	HDMI Type A (Standard)
Connector 2	HDMI Type A (Standard)
Connector 1 gender	Male
Connector 2 gender	Male

Product colour	Black
Connector contacts plating	Gold
Connector 1 form factor	Straight
Connector 2 form factor	Straight
3D	Yes
Supported graphics resolutions	3840 x 2160, 2560 x 1440, 1920 x 1080 (HD 1080)
Supported video modes	1080p, 1440p, 2160p
Dolby technologies	Dolby Atmos, Dolby Vision
Audio Return Channel (ARC)	Yes
HDMI Ethernet channel	Yes
HDCP	Yes
HDCP version	2.3
RGB support	4:4:4
Data transfer rate	18 Gbit/s
High Dynamic Range (HDR) supported	Yes
Maximum refresh rate	240 Hz
AWG wire size	30
Cable type	Round cable
Cable jacket material	Polyvinyl chloride (PVC)
Magnetically shielded	Yes
Number of shielding layers	2
Bend radius (min)	2.4 cm
Plug and Play	Yes
Colour sampling	4:4:4
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Storage temperature (T-T)	-20 - 80 °C
Operating relative humidity (H-H)	0 - 96%
Certificates	
Compliance certificates	CE, RoHS, REACH, UKCA
Weight & dimensions	
Weight	443 g
Packaging data	
Quantity per pack	1 pc(s)

Package weight 455 g

Matmenys ir svoris

Svoris 0,43kg

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Manhattan

ATSAKINGAS ASMUO ES

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

intellinetnetwork.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt