

D-Link DAP-E3620 wireless access point 2882 Mbit/s White Power over Ethernet (PoE)

Gamintojas: **D-LINK** · Modelis: **DAP-E3620** · EAN: **790069482274** · Prekės kodas: **872514**

nuclias



140,90 €

Kaina su PVM

Be PVM: **116,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Affordable Wi-Fi 7 upgrade for everyday business use
- ✓ BE3600 dual-band Wi-Fi for modern teams and offices
- ✓ Reliable performance in environments
- ✓ 2.5GbE uplink for faster end-to-end connectivity
- ✓ Simple PoE+ deployment with one-cable setup
- ✓ Enterprise-grade security with WPA3 support
- ✓ Easy traffic separation with VLAN-to-SSID mapping
- ✓ Built-in captive portal for guest access
- ✓ Flexible deployment modes for multiple scenarios
- ✓ Centralized management for easy operations



Aprašymas

Wi-Fi 7 Technology

Dual-band Wi-Fi 7 (802.11be), BE3600 class (2x2 + 2x2), delivering lower latency and higher efficiency for multi-user traffic

Easy Installation

Flexible ceiling or wall mounting for SMB deployments, while PoE+ simplifies cabling and accelerates installation

Customizable Captive Portal

Per-SSID captive portal support enables branded guest access, promotions, and flexible login workflow

VLAN per SSID

Each SSID to a dedicated VLAN for traffic segmentation, enabling simple separation of networks through policy-based control

Advanced Security

Supports WPA3-Personal/WPA3-Enterprise, 802.1X, and ACL-based access control to help reduce unauthorized access

Centralized Management

Centralized management through Nuclias Unity or Nuclias hardware/software controllers (DNH-1000, DNC-5000)

Faster Wi-Fi 7 for

Better Business Experiences

Dual-band Wi-Fi 7 (802.11be, BE3600 class) built for business environments — more speed, less latency, more devices.

- 5 GHz up to 2882 Mbps + 2.4 GHz up to 688 Mbps — combined throughput for demanding workloads, video collaboration, and dense device environments.
- Multi-Link Operation (MLO) uses both bands simultaneously, cutting latency and keeping connections stable when one band is congested.
- 4096-QAM enables faster data transmission for smoother streaming, gaming, and downloads.
- Designed for offices, hospitality, retail, and SMB deployments, it provides stable, scalable wireless performance for staff, guests, and connected devices—helping improve productivity, user experience, and operational efficiency.

Flexible Deployment for Any Network Need

Deploy in the mode that fits your infrastructure. Switch between access point, wireless bridge, or hybrid coverage without additional hardware.

Access Point Mode

Standard Wi-Fi coverage for wired networks — offices, classrooms, and public hotspots.

WDS with Access Point Mode (Wireless bridging + local coverage)

Extends coverage wirelessly while broadcasting a local SSID — connects floors or buildings without new cabling.

WDS Mode (No AP Broadcasting)

Pure wireless backhaul between two wired networks — no local SSID. Ideal for linking switches, cameras, or servers across sites.

High-Speed 2.5GbE PoE+ Uplink — No Wired Bottleneck

- Full Wi-Fi 7 throughput — the 2.5GbE uplink matches wireless capacity so your wired network never limits wireless performance.
- Single cable for power and data — IEEE 802.3at PoE+ eliminates the need for a separate power adapter, simplifying installation anywhere a switch port can reach.

Techninė specifikacija

Features		
2.4 GHz		Yes
5 GHz		Yes
6 GHz		No
Maximum data transfer rate		2882 Mbit/s
Maximum data transfer rate (2.4 GHz)		688 Mbit/s
Maximum data transfer rate (5 GHz)		2882 Mbit/s
Ethernet LAN data rates		2500 Mbit/s
Frequency band		2.4 - 5.85 GHz
Networking standards		IEEE 802.11be, IEEE 802.11ax, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3at
MIMO		Yes
MIMO type		Multi User MIMO
Band steering		Yes
Security		
Security algorithms		WPA, WPA2, WPA3, 802.1x RADIUS, AES, WPA-Personal, WPA-Enterprise, WPA3-Personal, WPA3-Enterprise
MAC address filtering		Yes
Service Set Identifier (SSID) features		SSID broadcast
Auto Wireless Distribution System (WDS)		Yes
Remote Authentication Dial-In User Service (RADIUS)		Yes
Management features		
Web-based management		Yes
Syslog		Yes
Ports & interfaces		
Ethernet LAN (RJ-45) ports		1
USB 2.0 ports quantity		0
Power		
Power over Ethernet (PoE)		Yes
DC voltage range		12 V

Input current	2.5 A
Power consumption (max)	14.17 W

Design

Placement	Ceiling
Product colour	White
Reset button	No
LED indicators	Power, Status, Link, Wi-Fi

Antenna

Antenna type	Internal
Antennas quantity	4
Antenna gain level (max)	4 dBi

Weight & dimensions

Width	186 mm
Depth	186 mm
Height	37 mm
Weight	550 g

Packaging content

AC adapter included	No
---------------------	----

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 65 °C
Storage relative humidity (H-H)	5 - 95%

Matmenys ir svoris

Svoris	0,74kg
--------	--------

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt