

InLine Installation cab. Cat.7a PiMF 4x2x0.58 AWG23, 1200MHz, LSZH, 50m

Gamintojas: **INLINE** · Modelis: **70050I** · EAN: **4043718208074** · Prekės kodas: **874798**

97,90 €

Kaina su PVM

Be PVM: **80,91 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cost reduction through easy handling on site without additional drum tooling
- ✓ easy to carry, handy and stackable packaging to pack in construction vehicle
- ✓ Lightweight (also sendable by parcel service)
- ✓ Prevention of pollution and damage to the cable by means of cardboard packaging
- ✓ reduce the average cost for small quantities

Aprašymas

The installation cable is delivered in a drum box for easy refer to the required length. The packaging consists of a plastic roller on which the data cable is rolled up. This roller is fixed in a carton, whereby a simple and unwinding is guaranteed. The following are the advantages of drum box:

Cost reduction through easy handling on site without additional drum tooling

easy to carry, handy and stackable packaging to pack in construction vehicle

Lightweight (also sendable by parcel service)

Prevention of pollution and damage to the cable by means of cardboard packaging

reduce the average cost for small quantities

Specifications:

Cable for installation

Cat. 7a installation cable to 1200MHz

Construction: 4x2xAWG23/1 S-FTP PiMF

Suitable up to 10Gb

Full copper conductors

Impedance: 100 Ohm, DC resistance: max. 87 Ohm / km
Halogen-free jacket LSZH
Orange sheath
Structure: pairs in metal foil
Overall braid shielding
Cable diameter about 8.2mm
Installation temperature: 0 - 50°C, operating temperature: -20°C - 60°C
With meter-printing on cable
Reaction to fire Eca according to EN 50575:2014 / A1:2016

Note: The drum box is only available for the bundles 50m, 100m, 300m, whereas 500m is supplied on a cable drum.

Techninė specifikacija

Features	
Cable length	50 m
Cable standard	Cat7a
Cable shielding	S/FTP (S-STP)
Connector 1	No
Connector 2	No
Product colour	Orange
Connector 1 gender	No
Connector 2 gender	No
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
Ethernet interface type	10 Gigabit Ethernet
AWG wire size	23
Data transfer rate	10000 Mbit/s
Frequency	1200 MHz
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Storage temperature (T-T)	0 - 50 °C
Sustainability	
Doesn't contain	Halogen
Weight & dimensions	
Weight	3.67 kg
Packaging content	
Quantity per pack	1 pc(s)

Packaging data

Package width	210 mm
Package depth	330 mm
Package height	335 mm
Package weight	4.22 kg
Package volume	23200 cm ³

Matmenys ir svoris

Svoris	5,18kg
--------	--------

Dokumentai ir vaizdo įrašai

[› Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Intos Electronic AG

Siemensstraße 11, D-35394 Gießen, DE

service@inline-info.com

[intos.de](https://www.intos.de)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt