

InLine USB PD power supply, GaN charger, 2-port, USB-C + USB-A, 30W, w/ display

Gamintojas: **INLINE** · Modelis: **31550** · EAN: **4043718334131** · Prekės kodas: **874994**



24,90 €

Kaina su PVM

Be PVM: **20,58 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

✓ USB power adapter/charger

✓ Overvoltage and short circuit protection



Aprašymas

This USB power supply from InLine combines state-of-the-art charging technology with a smart consumption indicator. Gain valuable insights into energy consumption while the charger supplies smartphones and other devices with power reliably, quickly and safely. The built-in digital display allows you to keep an eye on the current energy consumption in watts at all times and compare different devices with each other. By displaying the energy consumption, you can monitor the efficiency of your devices, adjust your charging habits and learn to use energy more consciously.

The USB power supply from InLine is equipped with state-of-the-art, environmentally friendly technology to ensure fast and efficient charging performance. With a high output power of 30 watts, you can charge several devices at the same time without sacrificing charging speed.

Gallium nitride (GaN) technology increases durability, reliability, charging efficiency and power density in a more compact and lightweight design. Due to the lower energy consumption during charging, the reduced material consumption during production and the smaller transport volume, the InLine power supply unit is particularly environmentally friendly.

The charger supports Power Delivery 3.0 on the USB-C port and Quick Charge 3.0 on the USB-A port. These fast charging technologies optimise

charging performance and speed with minimal energy loss.

Intelligent charge detection adapts the charging speed to the device and the charge level. This shortens the charging time, protects the battery and increases its service life. The USB power supply is excellently insulated and has comprehensive protection against overvoltage, overheating and short circuits. The lightweight, compact design hardly weighs a thing when travelling and fits into any multiple socket strip. Thanks to its variety of connections and technologies, this power adapter can be used universally and is compatible with a wide range of devices, including iOS and Android devices. Enjoy the latest charging technology while keeping an eye on the energy consumption of your devices.

Technical characteristics

USB power adapter/charger

Input voltage: 100-240VAC, 0.85A

Input AC frequency: 50/60Hz

Output voltage/output current/output power:

USB-C output:

5.0VDC/3.0A/15.0W - 9.0VDC/3.0A/27.0W - 12.0VDC/2.5A/30.0W

USB-A output:

5.0VDC/3.0A/15.0W - 9.0VDC/2.0A/18.0W - 12.0VDC/1.5A/18.0W

USB-A + USB-C output:

5.0VDC/3.4A/17.0W

Average operating efficiency:

83.78% (230V, 50Hz, USB-A 5.0V/3.0A)

87.77% (230V, 50Hz, USB-A 12.0V/1.5A)

84.33% (230V, 50Hz, USB-C 5.0V/3.0A)

88.73% (230V, 50Hz, USB-C 12.0V/2.5A)

85.56% (230V, 50Hz, USB-A 5.0V/1.7A + USB-C 5.0V/1.7A)

Efficiency at low load (10%):

78.68% (230V, 50Hz, USB-A 5.0V/3.0A)

75.71% (230V, 50Hz, USB-A 12.0V/1.5A)

78.75% (230V, 50Hz, USB-C 5.0V/3.0A)

82.21% (230V, 50Hz, USB-C, 12.0V/2.5A)

79.47% (230V, 50Hz, USB-A 5.0V/1.7A + USB-C 5.0V/1.7A)

Power consumption at no load: 0.09W

Total output power: max. 30.0W

Overvoltage and short circuit protection

If the power supply temperature is too high, it switches off automatically and automatically continues charging after it has cooled down

Dimensions: 81.8x39x33.5mm (LxWxH)

Weight: Approx. 60g

Techninė specifikacija

Performance

Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
Number of simultaneously connected devices (max)	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
USB Type-C ports quantity	1
Wireless charging	No
Fast charging	Yes
Fast charging technology	Quick Charge 3.0
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
Power protection features	Over voltage, Short circuit
Design	
Product colour	Black
Gallium nitride (GaN) transistors	Yes
Power	
Input voltage	100 - 240 V
Input frequency	50/60 Hz
Input current	0.85 A
Maximum power	30 W
Maximum output voltage	12 V
Minimum output voltage	5 V
Port 1 output power	30 W
Port 2 output power	18 W
Output current (5V)	3 A
Output current (9V)	3 A
Output current (12V)	2.5 A
Port 1 output current	3 A
Power consumption (no load)	0.09 W
Average active efficiency	83.78% (230V, 50Hz, USB-A 5.0V/3.0A) / 87.77% (230V, 50Hz, USB-A 12.0V/1.5A) / 84.33% (230V, 50Hz, USB-C 5.0V/3.0A) / 88.73% (230V, 50Hz, USB-C 12.0V/2.5A) / 85.56% (230V, 50Hz, USB-A 5.0V/1.7A + USB-C 5.0V/1.7A)
Efficiency at low load (10%)	Yes
Power plug type	Type C
Efficiency (@10 %)	82.21%

Weight & dimensions

Width	40 mm
Depth	82 mm
Height	34 mm
Weight	61 g

Packaging data

Package width	60 mm
Package depth	125 mm
Package height	40 mm
Package volume	300 cm ³
Package weight	81 g
Package type	Hanging box

Certificates

Compliance certificates	CE
-------------------------	----

Logistics data

Country of origin	China
-------------------	-------

Other features

Dimensions (WxDxH)	40 x 82 x 34 mm
--------------------	-----------------

Matmenys ir svoris

Svoris	0,08kg
--------	--------

Dokumentai ir vaizdo įrašai[› Naudojimo instrukcija](#)**Gamintojo ir saugos informacija**

GAMINTOJAS

Intos Electronic AG

Siemensstraße 11, D-35394 Gießen, DE

service@inline-info.com

[intos.de](https://www.intos.de)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt