

InLine 35396E interface hub 2 x USB 3.2 Gen 1 (3.1 Gen 1) Type-B 5000 Mbit/s Black

Gamintojas: **INLINE** · Modelis: **35396E** · EAN: **4043718352128** · Prekės kodas: **875253**



110,90 €

Kaina su PVM

Be PVM: **91,65 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Host interface: 2 x USB 3.2 Gen 1 (3.1 Gen 1) Type-B
- ✓ Hub interfaces: USB 3.2 Gen 1 (3.1 Gen 1) Type-C
- ✓ Ports quantity: 7
- ✓ 5000 Mbit/s
- ✓ Black Aluminium



Aprašymas

7-port USB-C industrial hub, 5 Gb/s, DIN rail, 12-24 V power supply

Centralised expansion to seven USB-C ports: Expands a single USB-C port to seven USB-C ports for the simultaneous operation of multiple devices in industrial environments

Increased total power for multi-device operation: A powerful 48 W power supply ensures a reliable power supply to multiple connected devices during simultaneous use

Flexible power supply for industrial applications: Supports 12–24 V DC via terminal connection or DC IN, as well as operation via an external power supply

Robust design for demanding environments: An aluminium housing and extended temperature range enable use under extreme conditions

Safe operation thanks to integrated protection mechanisms: Protection against short circuits, overcurrent, overvoltage and ESD protection for stable data and power transmission

This USB-C industrial hub enables the central expansion of a USB-C port by seven additional USB-C ports. It has been specially developed for use in industrial environments and allows the simultaneous operation of multiple USB devices with stable performance.

Thanks to support for the USB 3.2 Gen.1 standard, the hub achieves data transfer rates of up to 5 Gb/s and is backwards compatible with older USB standards. This enables flexible use with existing systems and devices.

Power is supplied either via an external power supply unit or directly via industrial power sources in the range of 12–24 V DC. In addition, an alternative 2-pin terminal connection is available, allowing the hub to be optimally integrated into various installation environments.

The more powerful 48 W power supply supports the powering of multiple connected devices. The power per port remains at a maximum of 5 V / 3 A in accordance with BC1.2 and is distributed accordingly during simultaneous use.

The robust aluminium housing and the extended temperature range from -40 °C to +85 °C ensure reliable operation even under demanding conditions. Integrated protection mechanisms such as short-circuit, overcurrent and overvoltage protection, as well as ESD protection, ensure safe operation.

Installation is flexible via DIN rail or wall mount. An LED indicator facilitates status monitoring during operation. Plug & Play enables simple commissioning without additional drivers.

Technical specifications

Chipset: VL817

Inputs:

1x USB-C port for connection to host computer

1x DC input (5.5 x 2.5 mm)

1x alternative 2-pin terminal connection

Supported input voltage: 12–24 V DC

Outputs:

7x USB-C 3.2 Gen 1 ports (5 Gb/s)

BC1.2 – USB Battery Charging Specification 1.2 (max. 5 V / 3 A per port)

Note: When multiple USB ports are used simultaneously, the available power is distributed among the connected devices

Protection mechanisms:

Short circuit, overcurrent, overvoltage

ESD/antistatic protection: 4 kV / 8 kV / 350 W

Housing: Aluminium, black

Mounting: DIN rail or wall bracket

LED indicator: Yes

Plug & Play: No drivers required

Standby power consumption: 0.07 W

Operating temperature: -40 °C to +85 °C

Storage temperature: -40 °C to +125 °C

Humidity: 10–85% (non-condensing)

Operating systems: Windows, macOS, Linux

External power supply (power adaptor)

Type: external plug-in power adaptor
Input voltage: 100–240 V AC, 50/60 Hz
Output voltage: 12.0 V DC
Output current: 4.0 A
Output power: 48.0 W
Average operating efficiency: 88.59%
Efficiency at low load (10%): 87.92%
Power consumption at no load: 0.07 W

Contents

1x InLine® USB 3.2 Gen.1 Industrial Hub, USB-C, 7-port
1x USB-C to USB-C cable, 1 m
1x Mounting kit
1x DIN rail 10 cm & clip
1x Terminal block
1x External power supply 12 V / 4 A
1x User manual (German/English)

Techninė specifikacija

Ports & interfaces	
Ports quantity	7
Host interface	2 x USB 3.2 Gen 1 (3.1 Gen 1) Type-B
Hub interfaces	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	7
Terminal block port	Yes
DC-in jack	Yes
Features	
Data transfer rate	5000 Mbit/s
Product colour	Black
Housing material	Aluminium
Cable length	1 m
Plug and Play	Yes
Power	
Power supply type	DC
Input voltage	12 V
Input current	2 A
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	MacOS
Linux operating systems supported	Yes

Weight & dimensions

Width	66 mm
Depth	148 mm
Height	28 mm
Weight	198 g

Packaging data

Quantity per pack	1 pc(s)
Package width	160 mm
Package depth	200 mm
Package height	60 mm
Package volume	1900 cm ³
Package weight	585 g
Package type	Box

Packaging content

AC adapter included	Yes
Cables included	USB Type-C to USB Type-C
Manual	Yes

Operational conditions

Operating temperature (T-T)	-40 - 85 °C
Storage temperature (T-T)	-40 - 125 °C
Operating relative humidity (H-H)	10 - 85%

Technical details

Compliance certificates	TÜV mark
-------------------------	----------

Other features

Dimensions (WxDxH)	66 x 148 x 28 mm
Chipset	VL817S

Matmenys ir svoris

Svoris	0,58kg
--------	--------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Intos Electronic AG

Siemensstraße 11, D-35394 Gießen, DE

service@inline-info.com

[intos.de](https://www.intos.de)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt