

InLine 35396I interface hub USB 3.2 Gen 1 (3.1 Gen 1) Type-C 5000 Mbit/s Black

Gamintojas: **INLINE** · Modelis: **35396I** · EAN: **4043718352340** · Prekės kodas: **875257**



122,90 €

Kaina su PVM

Be PVM: **101,57 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C
- ✓ Hub interfaces: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, RJ-45
- ✓ Ports quantity: 4
- ✓ 5000 Mbit/s
- ✓ Black Aluminium



Aprašymas

Industrial PoE USB hub with USB-C, 4 ports, Gigabit Ethernet and 60 W power supply

Centralised power and data supply via PoE: Supplies power to the connected USB-C device and peripherals via a single Ethernet cable, significantly reducing installation effort

Flexible connectivity options: Offers three USB-A ports and one USB-C port for expanding existing systems with additional interfaces

Integrated network connection: Enables stable data transmission via Gigabit Ethernet at up to 1000 Mb/s

Robust for continuous operation: Protection functions such as overcurrent, overvoltage, short-circuit and ESD protection ensure reliable operation

Optimised for industrial environments: Aluminium housing improves heat dissipation and supports use at elevated temperatures

The InLine® Industrial PoE USB Hub expands a USB-C-enabled device with additional interfaces whilst simultaneously integrating a network connection and power supply via Power over Ethernet. This creates a compact and efficient solution for installations where data, network and power are provided centrally.

Power is supplied via the RJ45 port in accordance with IEEE802.3bt with up to 60 W total power. Up to 45 W is available for the connected host device. An external power supply is not required. This enables flexible integration even in locations with limited power infrastructure.

The combination of three USB-A ports and a USB-C host interface expands existing systems with additional connection options. At the same time, the integrated Gigabit Ethernet port provides a stable network connection at up to 1000 Mb/s.

The aluminium housing supports efficient heat dissipation and is designed for use in extended temperature ranges. Protective mechanisms such as overvoltage, overcurrent, short-circuit and ESD protection contribute to operational safety.

Mounting options such as mounting brackets and DIN rails enable structured integration into existing installation environments.

Technical specifications

Interfaces:

3x USB-A (USB 3.2 Gen 1)

1x USB-C (Host)

1x RJ45 (Gigabit Ethernet)

Data transfer:

USB up to 5 Gb/s, backwards compatible;

Network 10/100/1000 Mb/s

Power supply:

Power over Ethernet (PoE) in accordance with IEEE802.3bt, up to 60 W total power, up to 45 W for the host device, no external power supply required

Protection functions:

Surge protection, overcurrent protection, short-circuit protection, ESD protection and automatic recovery after faults

Compatibility:

Windows, macOS, Linux, Android, Chrome OS and USB-C devices with Power Delivery support

Housing:

Aluminium housing for improved heat dissipation

Environmental conditions:

Operating temperature: 0 °C to 70 °C

Storage temperature: -40 °C to +125 °C

Humidity: 10% to 85% (non-condensing)

Mounting:

Mounting possible using the included mounting brackets

Contents

1 x InLine® Industrial PoE USB Hub, 60 W, USB 3.2 Gen 1, 4-port
1 x USB-C to USB-C cable, approx. 1 m
1 x Mounting kit
1 x DIN rail 10 cm & clip
1 x User manual (German / English)

Techninė specifikacija

Ports & interfaces	
Ports quantity	4
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
Hub interfaces	USB 3.2 Gen 1 (3.1 Gen 1) Type-A, RJ-45
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
Ethernet LAN (RJ-45) ports	1
Terminal block port	Yes
DC-in jack	Yes
Features	
Data transfer rate	5000 Mbit/s
Product colour	Black
Housing material	Aluminium
Cable length	1 m
Plug and Play	Yes
Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	100,1000,10 Mbit/s
Power	
Power supply type	DC
Input voltage	12 V
Input current	2 A
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	MacOS
Linux operating systems supported	Yes
Weight & dimensions	
Width	67 mm

Depth	128 mm
Height	27 mm
Weight	192 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	80 mm
Package depth	174 mm
Package height	55 mm
Package volume	800 cm ³
Package weight	348 g
Package type	Box
Packaging content	
AC adapter included	Yes
Cables included	USB Type-C to USB Type-C
Manual	Yes
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 125 °C
Operating relative humidity (H-H)	10 - 85%
Technical details	
Compliance certificates	TÜV mark
Other features	
Dimensions (WxDxH)	67 x 128 x 27 mm
Chipset	VL817S
Matmenys ir svoris	
Svoris	0,35kg

Dokumentai ir vaizdo įrašai

› [Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Intos Electronic AG

Siemensstraße 11, D-35394 Gießen, DE

service@inline-info.com

[intos.de](https://www.intos.de)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt